

# Te Rārangi Ine Tukunga 2025

## Measuring Emissions Catalogue 2025

As at 2026-01-13

# Measuring Emissions Catalogue

## Table of contents

1. Introduction
  - 1.1. Purpose of this catalogue
    - 1.1.1. Feedback
  - 1.2. Important notes
  - 1.3. Gases included in the guide
    - 1.3.1. Kyoto and Montreal protocols and Paris Agreement
  - 1.4. Uncertainties
  - 1.5. Standards to follow
  - 1.6. How emission sources are categorised
2. How to quantify and report GHG emissions
  - 2.1. Step-by-step inventory preparation
  - 2.2. Using the emission factors
  - 2.3. Producing a GHG report
  - 2.4. Assurance and verification
    - 2.4.1. Choosing an assurance provider
3. Fuel emission factors
  - 3.1. Overview of changes since previous update
  - 3.2. Stationary combustion fuel
    - 3.2.1. Emissions factors
    - 3.2.2. GHG inventory development
    - 3.2.3. Emission factor derivation methodology
    - 3.2.4. Assumptions, limitations and uncertainties
  - 3.3. Transport fuel
    - 3.3.1. Emissions factors
    - 3.3.2. GHG inventory development
    - 3.3.3. When no fuel data are available
    - 3.3.4. Emission factor derivation methodology
    - 3.3.5. Assumptions, limitations and uncertainties
  - 3.4. Biofuels and biomass
    - 3.4.1. GHG inventory development
    - 3.4.2. Emission factor derivation methodology
    - 3.4.3. Assumptions, limitations and uncertainties
  - 3.5. Transmission and distribution losses for reticulated gases
    - 3.5.1. Emissions factors
    - 3.5.2. GHG inventory development

- 3.5.3. Emission factor derivation methodology
  - 3.5.4. Assumptions, limitations and uncertainties
- 4. Refrigerant and other gases
  - 4.1. Overview of changes since previous update
  - 4.2. Refrigerant use
  - 4.3. Global warming potentials (GWPs) of refrigerants and other GHGs
    - 4.3.1. GHG inventory development
    - 4.3.2. Method A: Top-up
    - 4.3.3. Methods B and C: Screening
  - 4.4. Medical gases use
    - 4.4.1. Global warming potentials of medical gases
    - 4.4.2. GHG inventory development
    - 4.4.3. Assumptions
- 5. Purchased electricity, heat and steam emission factors
  - 5.1. Overview of changes since previous update
  - 5.2. Indirect Scope 2 emissions from purchased electricity from the New Zealand grid – using the location-based method
    - 5.2.1. GHG inventory development
    - 5.2.2. Emission factor derivation methodology
    - 5.2.3. Assumptions, limitations and uncertainties
  - 5.3. Transmission and distribution losses for electricity
    - 5.3.1. GHG inventory development
    - 5.3.2. Emission factor derivation methodology
    - 5.3.3. Assumptions, limitations and uncertainties
  - 5.4. Imported heat and steam
  - 5.5. Geothermal energy
- 6. Indirect business-related emission factors
  - 6.1. Overview of changes since previous update
  - 6.2. Emissions associated with employees working from home
    - 6.2.1. GHG inventory development
    - 6.2.2. Emission factor derivation methodology
    - 6.2.3. Employee commuting
    - 6.2.4. The emissions benefits of working from home
    - 6.2.5. Assumptions, limitations and uncertainties
  - 6.3. Guidance on the use of cloud-based data centres
- 7. Travel emission factors
  - 7.1. Overview of changes since previous update
  - 7.2. Passenger vehicles
    - 7.2.1. GHG inventory development
    - 7.2.2. Emission factor derivation methodology
    - 7.2.3. Assumptions, limitations and uncertainties

- 7.3. Public transport passenger travel
  - 7.3.1. GHG inventory development
  - 7.3.2. Emission factor derivation methodology
  - 7.3.3. Auckland ferry
  - 7.3.4. Assumptions, limitations and uncertainties
- 7.4. Public transport vehicles
  - 7.4.1. GHG inventory development
  - 7.4.2. Emission factor derivation methodology
  - 7.4.3. Assumptions, limitations and uncertainties
- 7.5. Air travel
  - 7.5.1. Domestic air travel
  - 7.5.2. International air travel
- 7.6. Helicopters
  - 7.6.1. GHG inventory development
  - 7.6.2. Emission factor derivation methodology
  - 7.6.3. Assumptions, limitations and uncertainties
- 7.7. Accommodation
  - 7.7.1. GHG inventory development
  - 7.7.2. Assumptions, limitations and uncertainties
- 8. Freight transport emission factors
  - 8.1. Overview of changes since previous update
  - 8.2. Road freight
    - 8.2.1. Light commercial vehicle emission factors
    - 8.2.2. Heavy goods vehicles emission factors
    - 8.2.3. GHG inventory development
    - 8.2.4. Emission factor derivation methodology
    - 8.2.5. Assumptions, limitations and uncertainties
  - 8.3. Rail freight
    - 8.3.1. GHG inventory development
    - 8.3.2. Emission factor derivation methodology
    - 8.3.3. Assumptions, limitations and uncertainties
  - 8.4. Air freight
    - 8.4.1. GHG inventory development
    - 8.4.2. Emission factor derivation methodology
    - 8.4.3. Assumptions, limitations and uncertainties
  - 8.5. Coastal and international shipping freight
    - 8.5.1. GHG inventory development
    - 8.5.2. Emission factor derivation methodology
    - 8.5.3. Assumptions, limitations and uncertainties
- 9. Water supply and wastewater treatment emission factors
  - 9.1. Overview of changes since previous update

- 9.2. Water supply
  - 9.2.1. GHG inventory development
  - 9.2.2. Emission factor derivation methodology
  - 9.2.3. Assumptions, limitations and uncertainties
- 9.3. Wastewater treatment
  - 9.3.1. GHG inventory development
  - 9.3.2. Emission factor derivation methodology
  - 9.3.3. Assumptions, limitations and uncertainties
- 10. Materials and waste emission factors
  - 10.1. Overview of changes since previous update
  - 10.2. Construction materials
  - 10.3. Waste disposal
    - 10.3.1. GHG inventory development
    - 10.3.2. Emission factor derivation methodologies
    - 10.3.3. When composition of waste is known
    - 10.3.4. When composition of waste is unknown
    - 10.3.5. Determining with or without landfill gas recovery
    - 10.3.6. Composting and anaerobic digestion
    - 10.3.7. Assumptions, limitations and uncertainties
- 11. Agriculture, forestry and other land-use emission factors
  - 11.1. Overview of changes since previous update
  - 11.2. Land use, land-use change and forestry
    - 11.2.1. Overview of the sector
    - 11.2.2. LULUCF emission factors
    - 11.2.3. GHG inventory development
    - 11.2.4. Emission factor derivation methodology
    - 11.2.5. Assumptions, limitations and uncertainties
  - 11.3. Agriculture
    - 11.3.1. Enteric fermentation
    - 11.3.2. Manure management emission factors
    - 11.3.3. Agricultural soils
    - 11.3.4. Fertiliser use
- A. Appendix — Derivation of fuel emission factors
  - A.1. A.1 The importance of calorific value
  - A.2. A.2 Methane and nitrous oxide emission factors used in this guide
  - A.3. A.3 Oxidation factors used in this guide
  - A.4. A.4 Sector classification
  - A.5. A.5 Reference data
- B. Appendix — Alternative methods of calculating emissions from refrigerants and medical gas
  - B.1. B.1 Method B – Default annual leakage rate

B.2. B.2 Method C – Default annual leakage rate and default refrigerant charge

B.3. B.3 Assumptions

C. Appendix — Landfills with and without landfill gas recovery

D. Appendix — Spend-based emission factors

E. Appendix — Glossary

F. Appendix — Files

F.0.1. Published files for 2025

F.0.2. Historical downloads

This catalogue provides an explanation of how you create your emissions report and an explanation of the emissions factors - how to use them and how they were created.

The [files](#) page contains the Interactive Workbook and the Emissions Factors Flat File, a PDF version of this catalogue, and historical MEG files.

## List of Tables

### About the guide

- [Table 1.1](#) — Common GWPs
- [Table 1.2](#) — Emissions by scope, category and source

### Fuel

- [Table 3.1](#) — Summary of changes to fuel emission factors
- [Table 3.2](#) — Emission factors for the stationary combustion of fuels
- [Table 3.3](#) — Transport Fuel Emissions Factors
- [Table 3.4](#) — Biofuels and Biomass Emission Factors
- [Table 3.5](#) — Transmission and distribution loss emission factors for natural gas

### Refrigerant

- [Table 4.1](#) — Summary of changes to refrigerant and other gases emission factors
- [Table 4.2](#) — Refrigerants Emission Factors
- [Table 4.3](#) — Medical Gases Emission Factors

### Purchased energy

- [Table 5.1](#) — Summary of changes to purchased energy emission factors
- [Table 5.2](#) — Emission factors for purchased grid-average electricity – annual average

- [Table 5.3](#) — Emission factor for purchased grid-average electricity – calendar quarters
- [Table 5.4](#) — Information used to calculate the purchased electricity emission factor 2011-2023
- [Table 5.5](#) — Transmission and distribution losses for electricity consumption

## Indirect activities

- [Table 6.1](#) — Summary of changes to indirect business-related emission factors
- [Table 6.2](#) — Working from home emission factors
- [Table 6.3](#) — Data used to calculate the emission factors

## Travel

- [Table 7.1](#) — Summary of changes to travel emission factors
- [Table 7.2](#) — Vehicle engine sizes and common car types
- [Table 7.3](#) — Pre-2010 vehicle fleet emission factors per km travelled
- [Table 7.4](#) — Vehicle fleet emission factors per km travelled, 2010–2015
- [Table 7.5](#) — Vehicle fleet emissions per km travelled, 2015–2020
- [Table 7.6](#) — Post 2020 vehicle fleet emissions factors per km travelled
- [Table 7.7](#) — Default private car emission factors per km travelled for default age of vehicle and <3000 cc engine size
- [Table 7.8](#) — Default rental car emission factors per km travelled
- [Table 7.9](#) — Emission factors for taxi travel
- [Table 7.11](#) — Data used for calculating the taxi (regular) emission factor
- [Table 7.12](#) — Energy consumption per 100 km for average light passenger vehicles
- [Table 7.13](#) — Emission factors for public transport
- [Table 7.14](#) — National bus passenger kilometres in 2020/21
- [Table 7.15](#) — National bus passenger loading by region
- [Table 7.16](#) — Emission factor for national average bus
- [Table 7.17](#) — Auckland Transport 2023 data for electric and hydrogen buses
- [Table 7.18](#) — Auckland Transport 2023 data for diesel buses
- [Table 7.19](#) — Auckland train data
- [Table 7.20](#) — Ferry data
- [Table 7.21](#) — Bus emission factors per km travelled
- [Table 7.22](#) — Fuel/energy consumption per 100 km for pre-2010 fleet buses
- [Table 7.23](#) — Domestic air travel emission factors without a radiative forcing multiplier
- [Table 7.24](#) — Domestic air travel emission factors with a radiative forcing multiplier
- [Table 7.25](#) — Calculated emissions, without the radiative forcing multiplier, per aircraft type
- [Table 7.26](#) — Calculated emissions, with the radiative forcing multiplier, per aircraft type
- [Table 7.27](#) — Emission factors for international air travel without radiative forcing multiplier
- [Table 7.28](#) — Emission factors for international air travel with radiative forcing multiplier

- [Table 7.29](#) — Emission factors for helicopters
- [Table 7.30](#) — Accommodation emission factors by unit (room per night)

## Freight transport

- [Table 8.1](#) — Summary of changes to freight emission factors
- [Table 8.2](#) — Emission factors for light commercial vehicles manufactured pre-2010
- [Table 8.3](#) — Emission factors for light commercial vehicles manufactured between 2010 and 2015
- [Table 8.4](#) — Emission factors for light commercial vehicles manufactured between 2015 and 2020
- [Table 8.5](#) — Emission factors for light commercial vehicles manufactured after 2020
- [Table 8.6](#) — Default light commercial vehicle values (based on pre-2010 fleet and a 2000–3000 cc engine size)
- [Table 8.7](#) — Emission factors for heavy goods vehicles, based on a pre-2010 fleet
- [Table 8.8](#) — Emission factors for heavy goods vehicles manufactured between 2010 and 2015
- [Table 8.9](#) — Emission factors for heavy goods vehicles manufactured post-2015
- [Table 8.10](#) — Default emission factors for heavy goods vehicles
- [Table 8.11](#) — Emission factors for freighting goods by road
- [Table 8.12](#) — Light commercial vehicles (energy consumption per 100 km)
- [Table 8.13](#) — Heavy goods vehicles (energy consumption per 100 km)
- [Table 8.14](#) — Data used to calculate the road freight (tkm) emission factor
- [Table 8.15](#) — Emission factors for rail freight
- [Table 8.16](#) — Information provided by KiwiRail
- [Table 8.17](#) — Air freight emissions without radiative forcing multiplier
- [Table 8.18](#) — Air freight emissions with radiative forcing multiplier
- [Table 8.19](#) — Coastal shipping emission factors
- [Table 8.20](#) — International shipping emission factors
- [Table 8.21](#) — Coastal shipping data

## Water

- [Table 9.1](#) — Summary of changes to water supply and wastewater treatment emission factors
- [Table 9.2](#) — Water supply emission factors
- [Table 9.3](#) — Domestic wastewater treatment emission factors
- [Table 9.4](#) — Industrial wastewater treatment emission factors
- [Table 9.5](#) — Domestic wastewater treatment emissions calculation components
- [Table 9.6](#) — Industrial wastewater treatment methane emissions calculation information
- [Table 9.7](#) — Industrial wastewater treatment nitrous oxide emissions calculation information
- [Table 9.8](#) — Uncertainties with wastewater treatment emission source category

## Materials and waste

- Table 10.1 — Summary of changes to materials and waste emission factors
- Table 10.2 — Description of landfill types
- Table 10.3 — Waste disposal to municipal (class 1) landfills with gas recovery
- Table 10.4 — Waste disposal to municipal (class 1) landfills without gas recovery
- Table 10.5 — Waste disposal to non-municipal (class 2–5) landfills
- Table 10.6 — Biological treatment of waste emission factors
- Table 10.7 — Composition of waste sent to NZ landfills
- Table 10.8 — Information on managed solid waste
- Table 10.9 — Information on non-municipal solid waste
- Table 10.10 — Composition of typical office waste
- Table 10.11 — IPCC default data used to calculate composting and anaerobic digestion

## Agriculture

- Table 11.1 — Summary of changes to agriculture, forestry, and other land-use emission factors
- Table 11.2 — LULUCF forest growth emission factors
- Table 11.3 — LULUCF land-use change emission factors
- Table 11.4 — Implied emission factors from enteric fermentation
- Table 11.5 — Enteric fermentation figures per livestock type
- Table 11.6 — Implied emission factors from manure management
- Table 11.7 — Manure management source data
- Table 11.8 — Data used to calculate manure management emissions from dairy cattle
- Table 11.9 — Implied emission factors from agricultural soils
- Table 11.10 — Agricultural soils source data
- Table 11.11 — Nitrogen fertiliser, limestone and dolomite emission factors
- Table 11.12 — Examples of different categories of fertilisers
- Table 11.13 — Data used to calculate nitrogen fertiliser emission factors
- Table 11.14 — Data used to calculate limestone and dolomite emission factors
- Table 11.15 — Parameters for calculating emissions from fertilisers

## Appendix-A

- Table A.1 — Mappings used for industrial and commercial sectors
- Table A.2 — Underlying data used to calculate fuel emission factors

## Appendix-B

- [Table B.1](#) — Default refrigerant charges for refrigeration and air-conditioning equipment
- [Table B.2](#) — Detailed 100-year GWPs for various refrigerant mixtures

## Appendix-C

- [Table C.1](#) — Active landfills with landfill gas recovery

# 1. Introduction

## 1.1. Purpose of this catalogue

The Ministry for the Environment supports entities taking climate action. We recognise there is strong interest, and in some cases requirements, for entities across New Zealand to measure, report and reduce their emissions. We prepared this guide to help you measure and report your entity or organisation's greenhouse gas (GHG) emissions on a voluntary basis (see [Section 1.2](#) for important notes on this guide's use). Measuring and reporting empowers entities to manage and reduce emissions in line with the transition to a low-emissions, climate-resilient future.

The guide aligns with and endorses the use of the [GHG Protocol Corporate Accounting and Reporting Standard](#) (referred to here as the GHG Protocol) and [ISO 14064-1:2018](#) (see [Standards to follow](#)). It provides information about preparing a GHG inventory [Section 2](#), emission factors (sections 3–11) and methods to apply them to activity data. We have updated the guide in line with international best practice and [New Zealand's Greenhouse Gas Inventory 1990–2023](#) to provide new emission factors.

Emission factors shown in tables retain the same level of precision as provided in the emissions factor flat file and are not additionally rounded. Tables describing data used in the derivation of emission factors present values as-is. Users should take account of the uncertainties described in accompanying tables and text when applying emission factors in calculations. Example emissions calculations are rounded to three significant figures for clarity and consistency.

Most of the source data which was used in the development of these emission factors is from 2023, unless otherwise mentioned. This is done to align with [New Zealand's Greenhouse Gas Inventory 1990–2023](#). This contains data for the calendar years from 1990 to 2023 (inclusive). The inventory is published 15 months after the end of the period being reported on, following the United Nations Framework Convention on Climate Change (UNFCCC) reporting guidelines on annual inventories for Parties included in Annex I to the Convention. This allows time to collect and process the data and prepare its publication.

This catalogue explains how we derived the emission factors and sets out the assumptions surrounding their use. The emission factor information contained in this catalogue is not intended to be an exhaustively detailed explanation of every calculation performed, as this is not practical.

### 1.1.1. Feedback

We welcome your feedback on this update. Please email [emissions-guide@mfe.govt.nz](mailto:emissions-guide@mfe.govt.nz)

## 1.2. Important notes

The information in the Measuring Emissions Guide does not constitute legal advice, and users should take specific advice from qualified professionals before taking any action based on information in this guide.

The information in [Section 1](#) and [Section 2](#) are intended as guidance only. This guidance does not replace any mandatory reporting requirements that entities may have, eg. Climate-related disclosures in line with the Aotearoa New Zealand Climate Standards (NZCS), or the Carbon Neutral Government Programme (CNGP).

Emissions factors contained within this guide may be used by entities in both voluntary and mandatory GHG inventory preparation and reporting.

The emission factors and methods in this guide are for sources common to many New Zealand organisations and support the recommended disclosure of GHG emissions consistent with the NZCS and the CNGP.

If emission factors relevant to your organisation are not included in the Measuring Emissions Guide or in Auckland Council's spend-based emissions report (see [Appendix D](#)), we suggest using alternatives such as those published by the UK [Department for Energy Security and Net Zero](#) (formerly published by the [Department for Business Energy & Industrial Strategy](#)) and the [US Environmental Protection Agency \(USEPA\)](#).

This guide recognises and supports the Government's ambition for its target of Net Zero by 2050, and the many organisations that have already set, or are looking to set, ambitious emission reduction targets aligned with a science-based approach.

Measuring your emissions enables you to set reduction targets, take climate action and report quantified progress towards your goals. For support related to reaching your organisation's targets see the Ministry's [Interim guidance for voluntary climate change mitigation](#).

The information in this guide is not appropriate for use in an emissions trading scheme. Organisations required to participate in the New Zealand Emissions Trading Scheme (NZ ETS) need to comply with the scheme-specific reporting requirements. The NZ ETS regulations determine which emission factors and methods must be used to calculate and report emissions.

This guide, and the emission factors and methods, are not appropriate for a full life-cycle assessment or product carbon foot printing. The factors presented in this guide only include direct emissions from activities, and do not include all sources of emissions required for a full life-cycle assessment. If you want to do a full life-cycle assessment, we recommend using life-cycle assessment databases and/or software tools. A list of relevant life-cycle inventory databases can be found on the [Life Cycle Association of New Zealand website](#).

Users seeking guidance on preparing a regional inventory should refer to the [GHG Protocol for Community-scale Greenhouse Gas Emission Inventories](#).

## Climate-related disclosures

New Zealand's climate-related disclosure framework is made up of three climate standards, referred to as Aotearoa New Zealand Climate Standards (NZCS).

The aim is to support the allocation of capital towards activities that are consistent with a transition to a low-emissions, climate-resilient future. Climate-related disclosures are mandatory for around 200 entities in New Zealand, for reporting periods beginning on or after 1 January 2023. They include disclosure requirements covering governance, strategy, risk management, and metrics and targets. Metrics and targets have the requirement to disclose gross GHG emissions in metric tonnes of carbon dioxide equivalent (CO<sub>2</sub>-e) classified as:

- Scope 1
- Scope 2 (calculated using the location-based method)
- Scope 3

The following information must also be disclosed in relation to the reporting entity's GHG emissions:

- a statement describing the standard or standards that GHG emissions have been measured in accordance with;
- the GHG emissions consolidation approach used: equity share, financial control, or operational control;
- the source of emission factors and the GWP values used or a reference to the GWP source;
- a summary of specific exclusions of sources, including facilities, operations, or assets with a justification for their exclusion.

A limited number of adoption provisions apply to Scope 3 emissions.

The [Aotearoa New Zealand Climate Standards](#) and [Staff Guidance for All Sectors](#) can be found on the XRB's website. These standards contain additional requirements, especially related to disclosures for methods, risk, reporting requirements and uncertainty management.

## Carbon Neutral Government Programme

The Carbon Neutral Government Programme (CNGP) was set up by the government to accelerate the reduction of emissions within the public sector. The CNGP has published guidance for CNGP entities on measuring and reporting their [GHG emissions](#). It includes information on what sources of GHG emissions entities need to collect, standards to follow, methods for calculating emissions, the required information to report, who to report to, and by when.

For further guidance on this consult the [CNGP website](#) or contact [cngp@mfe.govt.nz](mailto:cngp@mfe.govt.nz).

Measuring your entity's emissions is the first step in the journey to reducing your emissions. Developing and implementing a reduction plan is the next important step. Examples of emission reduction plans published by New Zealand corporations are available online.

Measuring emissions enables you to set reduction targets, take climate action and report quantified progress towards your goals. To reach your targets see the Ministry's [Interim guidance for voluntary climate change mitigation](#).

Users seeking guidance on preparing a regional inventory should refer to the [GHG Protocol for Community-scale Greenhouse Gas Emission Inventories](#).

## 1.3. Gases included in the guide

Global Warming Potential (GWP) is an index to translate the level of emissions of various gases into a common measure, in order to compare the relative radiative forcing of different gases. GWPs are calculated as the ratio of the radiative forcing that would result from the emissions of one kg of a greenhouse gas, to that from the emission of one kg of carbon dioxide over a period of time (usually 100 years). This guide uses AR5 values for GWPs.

This guide covers the following GHGs: carbon dioxide (CO<sub>2</sub>), methane (CH<sub>4</sub>), nitrous oxide (N<sub>2</sub>O), hydrofluorocarbons (HFCs), perfluorocarbons (PFCs), sulphur hexafluoride (SF<sub>6</sub>), nitrogen trifluoride (NF<sub>3</sub>) and other gases (eg, Montreal Protocol refrigerant gases or medical gases).

GWPs are applied to the non-CO<sub>2</sub> gases to enable meaningful comparisons among the gas types compared with CO<sub>2</sub>. Where GWPs are applied to these gases, GHG emissions are commonly expressed as their carbon dioxide equivalent or CO<sub>2</sub>-e. The larger the GWP, the more a given gas warms the earth compared to CO<sub>2</sub> over that time period. The time period usually used for GWPs is 100 years to align with UNFCCC greenhouse gas inventory reporting requirements. This is used throughout the guide.

To do this, the emissions for each non-CO<sub>2</sub> gas is multiplied by its 100-year time-horizon GWP (GWP<sub>100</sub>) value (see [Table 1.1](#)). The IPCC provides more information on how these factors are calculated.

Throughout the guide, kilograms (kg) of CH<sub>4</sub> and N<sub>2</sub>O are reported in kg CO<sub>2</sub>-e by multiplying the actual CH<sub>4</sub> emissions by the GWP of 28 and actual N<sub>2</sub>O emissions by the GWP of 265, as per [Table 1.1](#).

The GWP index value depends on two things: how effective the gas is at trapping heat while it's in the atmosphere, and how long it stays in the atmosphere before it breaks down. For example, methane (CH<sub>4</sub>) breaks down relatively quickly, the average CH<sub>4</sub> molecule stays in the atmosphere for around 12 years. On the other hand, CH<sub>4</sub> traps heat more effectively than CO<sub>2</sub>, which has a much longer lifetime.

Changes in GWP values can be due to updated scientific estimates of the energy absorption, lifetime of the gases, or to changing atmospheric concentrations of GHGs that result in a change in the energy absorption of an additional tonne of emitted gas relative to another.

The change from IPCC Fourth Assessment Report (AR4) to AR5 GWPs may cause a significant change in some entities' inventories, including those that use large quantities of refrigerants, or that use emission factors with relatively high contributions of CH<sub>4</sub>. For those that see increases or reductions in their footprints, it would be misleading to interpret this as a true increase or reduction.

[Table 1.1](#) shows the GWPs for N<sub>2</sub>O and CH<sub>4</sub> comparing AR4 to AR5 values. The GWP of N<sub>2</sub>O has decreased by 11.1 per cent and the GWP of CH<sub>4</sub> has increased by 12 per cent. AR5 GWPs for other gases such as refrigerants are shown in [Table 4.2](#).

**Table 1.1: Common GWPs**

Greenhouse gases	Chemical formula	GWP_AR4	GWP_AR5
Carbon dioxide	CO <sub>2</sub>	1	1
Methane	CH <sub>4</sub>	25	28
Nitrous oxide	N <sub>2</sub> O	298	265

### 1.3.1. Kyoto and Montreal protocols and Paris Agreement

The [Kyoto Protocol](#)<sup>1</sup>, adopted in 1997, operationalised the UNFCCC by committing developed country parties to limit and reduce GHG emissions in accordance with agreed individual targets. It includes the following gases: CO<sub>2</sub>, CH<sub>4</sub>, N<sub>2</sub>O, HFCs, PFCs, SF<sub>6</sub> and nitrogen trifluoride (NF<sub>3</sub>).

The [Montreal Protocol](#)<sup>2</sup>, adopted in 1987, is an international environmental agreement to protect the ozone layer by phasing out production and consumption of ozone-depleting substances (ODS). The Montreal Protocol includes chlorofluorocarbons (CFCs), hydrochlorofluorocarbons (HCFCs), hydrobromofluorocarbons (HBFCs), methyl bromide, carbon tetrachloride, methyl chloroform and halons. New Zealand prohibits imports of CFCs and HCFCs as part of our implementation of the protocol.

Many of the ozone depleting substances controlled by the Montreal Protocol are also powerful greenhouse gases. This, together with the 2016 Kigali Amendment of the Montreal Protocol to include the phase-down of HFCs, means it has a significant role in mitigating climate change.

The Paris Agreement, adopted in 2015, commits Parties to the agreement to put forward their best efforts to limit global temperature rise through nationally determined contributions (NDCs), and to strengthen these efforts over time. From 2024 onwards, New Zealand's Greenhouse Gas Inventory reports under the Paris Agreement will apply the 100-year time horizon GWPs from the IPCC's AR5.

## 1.4. Uncertainties

[ISO 14064-1:2018](#) and the [GHG Protocol](#) require consideration of uncertainty: in particular, assessing and disclosing uncertainty associated with a GHG inventory.

- Compared with financial accounting, carbon accounting operates in a more unpredictable, dynamic and complex environment, where uncertainty is a known and accepted concept.
- Uncertainties associated with GHG inventories can be broadly categorised as scientific uncertainty and estimation uncertainty.
- Scientific uncertainty arises when the science of the actual emission and/or removal process is not completely understood. Quantifying such scientific uncertainty is extremely challenging and is likely beyond the capability of most entity inventory programmes.
- Estimation uncertainty arises any time GHG emissions are quantified and can be classed as either model uncertainty or parameter uncertainty. Model uncertainty refers to the uncertainty associated with the mathematical equations and models used to characterise the relationship between activity data and emissions. Parameter uncertainty refers to the uncertainty associated with the assumptions used and the activity data. Entities that choose to investigate uncertainty in their emission inventories will focus on the latter.

The following approach is used to disclose uncertainty, in order of preference.

- Disclose the quantified uncertainty of the data, if known.
- Disclose the qualitative uncertainty if known based on expert judgement from those providing the data.
- Disclose the uncertainty ranges in the [IPCC Guidelines](#) if provided.
- Disclose that the uncertainty is unknown.

## 1.5. Standards to follow

We recommend following [ISO 14064-1:2018](#) or the [GHG Protocol](#) and this guide is written to align with both. Depending on your intended final use and users, we recommend downloading the relevant standards and using them in tandem with this guidance:

- [ISO 14064-1:2018](#)<sup>3</sup> is shorter and more direct than the GHG Protocol. A PDF copy can be purchased.
- The [GHG Protocol](#)<sup>4</sup> gives more description and context around what to do to produce an inventory. It is free to download. The [Corporate Value Chain \(Scope 3\) Accounting and Reporting Standard](#) is also available. It is a guide for companies to assess their entire value chain emissions impact and identify where to focus reduction activities.

These standards provide comprehensive guidance on the core issues of GHG monitoring and reporting at an organisational level, including:

- principles underlying monitoring and reporting
- setting entity / organisational boundaries
- setting reporting boundaries
- establishing a base year
- managing the quality of a GHG inventory
- content of a GHG report.

## 1.6. How emission sources are categorised

The [GHG Protocol Corporate Accounting and Reporting Standard](#) places emission sources into Scope 1, Scope 2 and Scope 3 activities.

- Scope 1: Direct GHG emissions from sources owned or controlled by the entity (ie, within the organisational boundary). For example, emissions from combustion of fuel in vehicles owned or controlled by the entity.
- Scope 2: Indirect GHG emissions from the generation of purchased energy (in the form of electricity, heat or steam) that the entity uses.
- Scope 3: Other indirect GHG emissions occurring because of the activities of the entity but generated from sources that it does not own or control (eg, air travel).

The [GHG Protocol Corporate Value Chain \(Scope 3\) Accounting and Reporting Standard](#) goes into more detail, providing a method to enable GHG management of the entities' value chain emissions. In this standard, Scope 3 is broken down into 15 'categories' that cover the upstream and downstream emissions associated with the entity's activities. Some of the categories include purchased goods and services, upstream transportation and distribution, business travel and the use of sold products.

The [GHG Protocol Technical Guidance for Calculating Scope 3 Emissions](#) provides detailed guidance for each of its 15 Scope 3 categories, along with a useful table that summarises the different calculation methods available for each of these categories.

ISO 14064-1:2018 also categorises emissions as direct or indirect sources, and breaks Scope 3 down into six categories.

- Category 1: *Direct GHG emissions and removals* covers the same kind of activities reported under the GHG Protocol Scope 1.
- Category 2: *Indirect GHG emissions from imported energy* is the same as the GHG Protocol Scope 2.

The main difference with this standard is that Scope 3 emissions are separated into the following categories.

- Category 3: *Indirect GHG emissions from transportation*, where emissions from transportation sources outside the organisation boundary are reported, such as business travel in a car that is not owned by the reporting entity.
- Category 4: *Indirect GHG emissions from products used by an entity*, which covers emissions associated with goods used by the reporting entity, such as office paper.
- Category 5: *Indirect GHG emissions* associated with the use of products from the organisation, which covers emissions associated with goods sold by the reporting entity, such as the lifetime usage of a car where the reporting entity is a car manufacturer.
- Category 6: *Indirect GHG emissions from other sources*, which is for any emissions source (or removal) that cannot be reported in any other category.

Compared with the traditional Scope 1, Scope 2 and Scope 3 approach used in the [GHG Protocol Corporate Accounting and Reporting Standard](#), the categories provided in the [GHG Protocol Corporate Value Chain \(Scope 3\) Accounting and Reporting Standard](#) and ISO 14064:2018 enable a more granular approach to GHG reporting.

The category names help better describe the activities associated with emissions sources. They enhance the quality and clarity of reporting by enabling the inclusion and expansion of indirect emissions throughout the value chain. They help identify environmental hotspots inside and outside the entity’s boundaries, which helps inform the identification of carbon reduction opportunities. Using categories also helps to manage double counting of emissions (such as between an electricity generator’s direct emissions associated with generation and the indirect emissions linked to the user of that electricity).

A similar approach of breaking down Scope 3 emissions into categories is also used by ISO 14064:2018.

This guide reports emission factors for direct (Scope 1) and indirect (Scope 2) emissions, and a limited set of indirect (Scope 3) emissions. Table 2 shows the relationship between the GHG Protocol Scopes and the ISO categories.

**Table 1.2: Emissions by scope, category and source**

ISO inventory category	Scopes in the GHG Protocol	ISO sub-category (annex B)	GHG Protocol
Category 1: Direct GHG emissions and removals	1	Stationary combustion	Scope 1
	1	Mobile combustion	Scope 1
	1	Chemical and industrial processes	Scope 1
	1	Fugitive emissions	Scope 1
	1	Land use, land use change and forestry (LULUCF)	Scope 1

ISO inventory category	Scopes in the GHG Protocol	ISO sub-category (annex B)	GHG Protocol
Category 2: Indirect GHG emissions from imported energy	2	Purchased (imported) electricity and steam	Scope 2
	2	Energy	Scope 2
Category 3: Indirect GHG emissions from transportation	3	Upstream emissions from fuel generation	3. Fuel- and energy-related activities
	3	Upstream transport and distribution of goods purchased	4. Upstream transportation and distribution
	3	Downstream transport and distribution of goods sold	9. Downstream transportation and distribution
	3	Employee commuting	7. Employee commuting
	3	Business travel in vehicles not owned or operated by the organisation	6. Business travel
	3	Client and visitor transport	6. Business travel
	3	Business hotel stay	6. Business travel
Category 4: Indirect GHG emissions from products used by the organisation	3	Purchased goods and services, including upstream emissions	1. Purchased goods and services
	3	Capital goods, including upstream emissions	2. Capital goods
	3	Transmission of energy (transmission and distribution losses)	
	3	Waste disposal and treatment (liquid and solid)	5. Waste generated in operations
	3	Equipment leased by reporting organisation	8. Upstream leased assets
Category 5: Indirect GHG emissions associated with use of products from the organisation	3	Processing of sold goods, or intermediate products sold by the organisation to another	10. Processing of sold products
	3	Use stage of product sold	11. Use of sold product
	3	Downstream leased assets owned by the organisation and leased to others	13. Downstream leased assets 14. Franchises
	3	End-of-life stage of product sold	12. End-of-life treatment of sold products
	3	Investments such as equity debt, investment debt, project finance and others	15. Investments

ISO inventory category	Scopes in the GHG Protocol	ISO sub-category (annex B)	GHG Protocol
Category 6: Indirect GHG emissions from other sources	3		

Note<sup>1</sup>: Depending on your entity’s reporting and financial boundaries, some emission sources may be either Scope 1 or Scope 3.

Note<sup>2</sup>: Spend-based emission factors might be used for some of the indirect emissions where better quality, activity specific emission factors may be lacking.

Note<sup>3</sup>: Emissions inventories, in line with the Greenhouse Gas Protocol, report only Kyoto Protocol gases under direct (Scope 1) emissions. All non-Kyoto gases, such as the Montreal Protocol refrigerant gases or medical gases, should be reported separately as ‘other gases’.

Both the [ISO 14064-1:2018](#) and [GHG Corporate Protocol](#) require that entities calculate the emissions of each GHG separately and quantify them as CO<sub>2</sub>-e. Example calculations in this guide show this format (see also the [2024 example report for greenhouse gas emissions](#)). While the NZCS does not mandate a single approach for measuring GHG emissions, the International Sustainability Standards Board requires entities to report in accordance with the [GHG Protocol](#), unless there are other requirements, for instance, from an exchange they are listed on.

## 2. How to quantify and report GHG emissions

To quantify and report GHG emissions, entities need data about their activities (for example, the quantity of fuel used). They can then convert this into information about their emissions (measured in tonnes of CO<sub>2</sub>-e) using emission factors.

An emission factor allows the estimation of GHG emissions from a unit of available activity data (eg, litres of fuel used). The factors are set out in the [Emission factors flatfile](#).

### CALCULATION METHODOLOGY

$$E = Q * F$$

Where

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = activity data eg, quantity of fuel used
- F = emission factor for emissions source

This formula applies to the calculation of both CO<sub>2</sub>-e emissions and individual carbon dioxide, methane and nitrous oxide emissions, with the appropriate emission factors applied for F.

The preferred form of data is in the units expressed in the emission factor tables, which results in the most accurate emission calculation. If the data cannot be collected in this unit, use the appropriate conversion factors.

A **GHG inventory** (see [Section 2.1](#)) contains all applicable emissions for an entity within a defined boundary during a set period. A GHG inventory is key to measuring emissions.

A **GHG report** (see [Section 2.3](#)) expands on the inventory with context about the entity, methods used, as well as analysis of drivers and progress over time. A GHG report is key to reporting emissions.

Entities that wish to report in line with [ISO 14064-1:2018](#) should be aware that the standard has specific requirements about what to include in the inventory and report.

With voluntary reporting, it is best practice for entities to understand their full Scope 3 (value chain) emissions and report material sources.

Note that the [GHG Protocol](#) requires certain information to be reported alongside the GHG emissions totals if these are reported publicly. If you are planning to make a public GHG statement claiming conformity with the ISO standard, note that you are also required to publish a separate GHG report.

Entities may obtain assurance or verification over the GHG inventory or GHG report against the measurement (see [Section 2.4](#)).

### 2.1. Step-by-step inventory preparation

To prepare an inventory:

- Select the boundaries (organisational and reporting<sup>5</sup>) and measurement period (ie, calendar or financial year) you will report against for your entity, based on the intended uses of the inventory.
- Collect activity data on each emission source within the boundaries for that period.

- Multiply the activity data by the appropriate emission factor for each emission source and record the calculation (eg, in a spreadsheet).
- Produce a GHG report, if applicable.

If this is the first year your entity has produced an inventory, you can use it as a base year for measuring the change in emissions over time, as long as the scope and boundaries represent your usual operations, and that comparable reporting is used in future years. Both the [ISO 14064-1:2018](#) and [GHG Protocol](#) allow a base year to be quantified using an average of several years. This can be useful as a method of smoothing out unusual fluctuations when a single year's estimate is not representative of normal activity.

Ensuring time series consistency is central to the GHG inventory because it provides information on the emissions trends for your entity, such as any carbon reduction strategies you have undertaken. All emissions estimates in a time series should be estimated consistently. This means that the same methods and data sources should be used across all years covered by the GHG inventory. Using different methods and data in a time series will mask the trend and will not reflect real changes in emissions. To ensure the representativeness of your base year GHG inventory, therefore, it is good practice to undertake a base year review and recalculate the time series to account for any changes that have occurred due to:

- a structural change in your reporting or organisational boundary
- a change or refinement to calculation methodologies or emission factors, or
- the discovery of an error or cumulative errors in your activity data.

Any base year and time series recalculations should be documented in subsequent inventories.

If historic emission factors have changed, we suggest providing these figures in the document itself, or making them available elsewhere.

For some entities, certain GHG emissions may contribute such a small portion of the inventory that they make up less than (for instance) 1 per cent of the total inventory. These are known as *de minimis*<sup>6</sup> and may be excluded from the total inventory, provided that the total of excluded emissions does not exceed the materiality<sup>7</sup> threshold set by your entity. For example, if using an overall materiality threshold of 5 per cent, the total of all emission sources excluded as *de minimis* must not exceed 5 per cent of the inventory. Typically, an entity estimates any emissions considered *de minimis* using simplified methods to justify the classification. It is important these are transparently documented and justified. Often, you only need to re-estimate excluded emissions in subsequent years if the assumptions change.

However, if the user needs to report into a particular programme or satisfy an intended use or user, they may decide to, or be required to, include *de minimis* activities. Under the NZCS, information is considered to be 'significant' or 'material' if omitting, misstating or obscuring it could reasonably be expected to influence decisions that primary users make on the basis of those climate-related disclosures.

Most entities reporting voluntarily do so each calendar year or financial year. However, the Financial Sector (Climate-related Disclosures and Other Matters) Amendment Act 2021 (CRD) and the CNGP requires reporting based on financial year. Most commonly, a single year serves as their base year. However, it is also possible to choose an average of annual emissions over several consecutive years as a base year.

## 2.2. Using the emission factors

Emission factors rely on historical data. This version of the guidance is largely based on [New Zealand's Greenhouse Gas Inventory 1990–2023](#) as this was the latest complete set of data available. Emissions factors will be updated annually, when more recent data is available.

Simplified example calculations are provided throughout sections 3 to 11 to demonstrate how to use the emission factors.

The emission factors in this guide are:

- default factors, used in the absence of better entity-specific or industry-specific information.
- consistent with the reporting requirements of [ISO 14064-1:2018](#) and the [GHG Protocol](#)
- aligned with [New Zealand's Greenhouse Gas Inventory 1990–2023](#)
- presented in kg CO<sub>2</sub>-e per unit. Under the reporting requirements of [ISO 14064-1:2018](#) and the [GHG Protocol](#), GHG emissions should be reported in tonnes CO<sub>2</sub>-e. However, many emission factors are too small to be reported meaningfully in tonnes. Dividing by 1,000 converts kg to tonnes.

In line with the reporting requirements of the standards, the emission factors allow calculation of carbon dioxide, methane and nitrous oxide separately, as well as the total carbon dioxide equivalent for direct (Scope 1) emission sources.

Carbon dioxide emission factors are based on the carbon and energy content of a fuel. Therefore, the carbon dioxide emissions remain constant irrespective of how a fuel is combusted.

Non-carbon dioxide emissions (eg, methane and nitrous oxide) and emission factors depend on the way the fuel is combusted.<sup>8</sup> To reflect this variability, the guide provides uncertainty estimates for direct (Scope 1) emission factors. [Table 3.2](#) presents separate carbon dioxide equivalent emission factors for residential, commercial and industrial users. It follows the IPCC guidelines for combustion and adopts the uncertainties.<sup>9</sup>

We derived these emission factors primarily from technical information published by New Zealand government agencies. Each section below provides the source for each emission factor and describes how we derived the factors.

## 2.3. Producing a GHG report

A full GHG report provides context to the GHG inventory by including information about the entity, comparing annual inventories, discussing significant changes to emissions, listing excluded emissions, and stating the methods and references for the calculations.

### A GHG REPORT

To compile a full GHG report, entities should include:

- a description of the entity/organisation
- the person or entity responsible for the report
- a description of the inventory boundaries
  - entity/organisational boundary
  - reporting boundary
  - measurement period
- the chosen base year (initial measurement period for comparing annual results)
- emissions (and removals where appropriate) for all GHGs, separately reported in metric tonnes CO<sub>2</sub>-e
- emissions separated by scope
  - total Scope 1 and 2 emissions
  - total and specified Scope 3 emissions
- emissions from the combustion of biologically sequestered carbon, reported separately from the scopes

- a time series of emissions results from base year to present year
- significant changes to the inventory, including in the context of triggering any base year recalculations
- the methodologies for calculating emissions, and references to key data sources
- impacts of uncertainty on the inventory
- any specific exclusions of sources, facilities or operations
- a statement describing the recognised standard or standards that the GHG emissions have been measured in accordance with.

View an example reporting template on the [GHG Protocol Corporate Standard webpage](#).

## 2.4. Assurance and verification

Seeking independent<sup>10</sup> third-party assurance of your inventory is a key component of a responsible reporting approach. Obtaining assurance means to appoint an independent practitioner to undertake a selection of procedures to enable them to express an opinion or conclusion of your entity's reported statement and is intended to increase the confidence that users can place on the reported information.

There are differing levels of assurance which result in different types of reports. Reasonable assurance is the highest level of assurance, where your assurance practitioner will perform procedures to enable them to state, in their opinion, that the subject matter is not materially misstated. Limited assurance provides a lower level of assurance, where the assurance practitioner will perform fewer procedures comparative to reasonable assurance. A limited assurance conclusion will state nothing has come to the assurance practitioner's attention which indicates the information is materially misstated.

It is recommended that you speak to an assurance provider about your GHG data quality, available evidence and the level of assurance you require. Many assurance providers also provide pre-assurance or an assurance gap analysis, with the aim of providing you with a preliminary assessment of whether the pre-conditions to an assurance engagement are met and feedback ahead of formal assurance. The purpose of pre-assurance is to prepare the reporter for attaining assurance, though it will not provide guidance on whether or not assurance will be attained.

If you are a Climate Reporting Entity under the Financial Sector (Climate-related Disclosures and Other Matters) Amendment Act 2021 or required to report under the CNGP, specific assurance requirements apply.

If your entity is a covered entity under the Financial Markets Conduct Act 2013, as amended by the Financial Sector (Climate-related Disclosures and Other Matters) Amendment Act 2021 (the Financial Markets Conduct Act 2013 as amended), you are required to obtain third-party assurance in relation to the parts of your climate statement that relate to GHG emissions for periods that end on or after 27 October 2024. For more detail, please see [Assurance, External Reporting Board \[XRB\]](#).

If your entity is a participant to the CNGP, please note that you must seek assurance from an independent third party annually. Please see the [CNGP guide to measuring and reporting greenhouse gas emissions](#) for more information.

### 2.4.1. Choosing an assurance provider

If you are seeking independent assurance over your GHG disclosures, consider the following factors when choosing a verifier:

- independence and objectivity

- sufficient skills, with previous experience in GHG inventory verifications or assurance
- competence and understanding of GHG reporting and accounting standards and frameworks
- can carry out GHG inventory assurance in accordance with applicable assurance standards. [ISAE 3410](#) and [ISO 14064-3:2019](#) are widely used for the assurance or verification of GHG emissions reports. One or the other of these standards should be used:
  - [ISAE](#) standard – free to download
  - [ISO](#) standard – there is a download charge.

ISO 14064-3:2019 uses the terms ‘validation’ and ‘verification’, whereas ISAE 3410 uses ‘assurance’. However, assurance engagements undertaken in accordance with the two international assurance standards include the same, or substantively similar, procedures.

The topic of assurance over GHG reports and providers of such assurance is currently evolving in New Zealand. At the time of publication of this guide, the Ministry of Business, Innovation and Employment had not issued its decision following feedback on the licensing regime consultation for assurance providers. We recommend that entities regularly review developments in this area.

We also recommend that entities covered by the CRD monitor developments of the XRB, following its consultation on [assurance of GHG emissions disclosures](#).

## 3. Fuel emission factors

Fuel can be categorised by its end-use, that is, either stationary combustion or transport. This section also includes biofuels and the transmission and distribution losses for reticulated natural gas.

In line with the reporting requirements of [ISO 14064-1:2018](#) and the [GHG Protocol](#) we provide emission factors for direct (Scope 1) sources to allow separate estimation of carbon dioxide, methane and nitrous oxide emissions calculations.

### 3.1. Overview of changes since previous update

The fuel emission factors are based on data from *New Zealand's Greenhouse Gas Inventory 1990–2023*.

**Table 3.1: Summary of changes to fuel emission factors**

Domain	Emission factors	Size of change	Explanation for change
Fuel	All factors	Minor	The methodology remains unchanged. Diesel emission factors have increased by 0.12%, while petrol emission factors have risen by 0.44%. This slight increase impacts associated diesel and electric transportation emissions factors.

### 3.2. Stationary combustion fuel

Stationary combustion fuels are burnt in a fixed unit or asset, such as a boiler. Direct (Scope 1) emissions occur from the combustion of fuels within equipment owned or controlled by the reporting entity. If the entity does not own or control the assets where combustion takes place, then these emissions are indirect (Scope 3) emissions. For more information see [Section 1.6](#).

#### 3.2.1. Emissions factors

[Table 3.2](#) contains emission factors for common fuels used for stationary combustion in New Zealand. The Ministry of Business, Innovation and Employment (MBIE) provided the emission factors and supporting data. The same data were used in *New Zealand's Greenhouse Gas Inventory 1990–2023*.

Sectors for consumption statistics are based on [Australian and New Zealand Standard Industrial Classification \(ANZSIC\) codes](#).

Residential use emission factors are for fuel used primarily at residential properties. Commercial use is for fuels used at properties or sites where commercial activities take place. Industrial use emission factors can be applied where combustion takes place at sites where there are industrial processes or within engines that support industrial activities.

**Table 3.2: Emission factors for the stationary combustion of fuels**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Commercial Use</b>						
Coal - Bituminous	kg	2.656405269	2.637360379	0.007870951	0.0111739393	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Default	kg	2.073583996	2.059035293	0.0060127482	0.008535955	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Lignite	kg	1.430266751	1.420447873	0.0040579866	0.0057608917	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Sub-Bituminous	kg	2.004939942	1.991009477	0.0057572401	0.0081732248	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Diesel	litre	2.679858468	2.66380534	0.0102388965	0.0058142305	CO <sub>2</sub> e ±1.02%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Heavy Fuel Oil	litre	3.053591727	3.036601404	0.0108366525	0.0061536705	CO <sub>2</sub> e ±1.02%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
LPG	kg	2.971635097	2.963726347	0.00665	0.00125875	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Light Fuel Oil	litre	2.970880948	2.95400959	0.010760775	0.0061105829	CO <sub>2</sub> e ±1.02%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Natural Gas (GJ)	GJ	54.20775879	54.05790879	0.126	0.02385	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Natural Gas (kWh)	kWh	0.1951479317	0.1946084717	0.0004536	0.00008586	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
<b>Industrial Use</b>						

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Coal - Bituminous	kg	2.656405269	2.637360379	0.007870951	0.0111739393	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Default	kg	1.932675706	1.919196976	0.0055705452	0.0079081846	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Lignite	kg	1.430266751	1.420447873	0.0040579866	0.0057608917	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Sub-Bituminous	kg	2.004939942	1.991009477	0.0057572401	0.0081732248	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Diesel	litre	2.67269124	2.66380534	0.003071669	0.0058142305	CO <sub>2</sub> e ±1.0%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Heavy Fuel Oil	litre	3.04600607	3.036601404	0.0032509957	0.0061536705	CO <sub>2</sub> e ±1.0%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
LPG	kg	2.966315097	2.963726347	0.00133	0.00125875	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Light Fuel Oil	litre	2.963348405	2.95400959	0.0032282325	0.0061105829	CO <sub>2</sub> e ±1.0%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Natural Gas (GJ)	GJ	54.10695879	54.05790879	0.0252	0.02385	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Natural Gas (kWh)	kWh	0.1947850517	0.1946084717	0.00009072	0.00008586	CO <sub>2</sub> e ±2.0%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
<b>Residential Use</b>						
Coal - Bituminous	kg	2.884662847	2.637360379	0.2361285294	0.0111739393	CO <sub>2</sub> e ±4.49%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Coal - Default	kg	2.149899587	1.97042197	0.1713682282	0.0081093894	CO <sub>2</sub> e ±4.39%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Lignite	kg	1.547948363	1.420447873	0.1217395986	0.0057608917	CO <sub>2</sub> e ±4.34%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Coal - Sub-Bituminous	kg	2.171899906	1.991009477	0.1727172043	0.0081732248	CO <sub>2</sub> e ±4.38%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%

**Notes:** Commercial and industrial classifications are based on standard classification<sup>11</sup>. Use the default coal emission factor if it is not possible to identify the type of coal. Convert LPG-use data in litres to kilograms by multiplying by the specific gravity of 0.534 kg/litre.

### 3.2.2. GHG inventory development

To calculate stationary combustion fuel emissions, first collect data on the quantity of fuel used, and then multiply this by the appropriate emission factor from the table.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = quantity of fuel used (unit)
- F = appropriate emission factors from [Table 3.2](#).

Entities typically report emissions using data on the amount of fuel used during the reporting period.

#### STATIONARY COMBUSTION: EXAMPLE CALCULATION

An entity uses 1,400 kg of LPG to heat an office building in the reporting year:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	1,400 x 0.00665 kg CO <sub>2</sub> -e per kg	9.31 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	1,400 x 2.963726347 kg CO <sub>2</sub> -e per kg	4,150 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	1,400 x 0.00125875 kg CO <sub>2</sub> -e per kg	1.76 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	1,400 x 2.971635097 kg CO <sub>2</sub> -e per kg	4,160 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 3.2.3. Emission factor derivation methodology

We derived the kg CO<sub>2</sub>-e per activity unit emission factors supplied in [Table 3.2](#) using calorific values and emission factors for tonnes of gas per terajoule (tTJ). These are either sourced from the *New Zealand's Greenhouse Gas Inventory 1990–2023* or default emission factors from the IPCC.

To calculate the final emission factors for CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O, the calorific value is multiplied by the emission factor (t/TJ) for each gas type. The CH<sub>4</sub> and N<sub>2</sub>O values are then multiplied by their global warming potentials, 28 and 265 respectively.

The calorific values are in [Appendix A](#) alongside further information on the methodology.

### 3.2.4. Assumptions, limitations and uncertainties

We derived the kg CO<sub>2</sub>-e per activity unit emission factors in [Table 3.2](#) using calorific values, listed in [Appendix A: Derivation of fuel emission factors](#).

The emission factors above account for the direct (Scope 1) emissions from fuel combustion. They are not full fuel-cycle emission factors and do not incorporate indirect (Scope 3) emissions associated with the extraction, production and transport of the fuel.

We calculated the default coal emission factors by weighting the emission factors for the different ranks of coal (bituminous, sub-bituminous and lignite) by the amount of coal used for each sector (commercial, residential, industrial). The guide includes emission factors for residential coal for completeness.

## 3.3. Transport fuel

### 3.3.1. Emissions factors

Transport fuels are used in an engine to move a vehicle. [Table 3.3](#) lists the emission factors.

**Table 3.3: Transport Fuel Emissions Factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Transport Fuel</b>						
Aviation fuel – Kerosene (GJ)	GJ	68.45081772	67.93401772	0.0133	0.5035	CO <sub>2</sub> e ±1.06%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Aviation fuel – Kerosene (litre)	litre	2.518983736	2.499965544	0.0004894388	0.0185287532	CO <sub>2</sub> e ±1.06%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Aviation gas (GJ)	GJ	66.40829518	65.89149518	0.0133	0.5035	CO <sub>2</sub> e ±1.06%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Aviation gas (litre)	litre	2.249035005	2.231532654	0.0004504282	0.0170519228	CO <sub>2</sub> e ±1.06%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Diesel	litre	2.680680605	2.639279658	0.0039564045	0.0374445425	CO <sub>2</sub> e ±1.21%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Heavy Fuel Oil	litre	3.064699295	3.036601404	0.0075856567	0.020512235	CO <sub>2</sub> e ±1.05%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
LPG	litre	1.618252002	1.573145945	0.043769768	0.001336289	CO <sub>2</sub> e ±2.37%, CO <sub>2</sub> ±2.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Light Fuel Oil	litre	2.981910742	2.95400959	0.0075325425	0.0203686098	CO <sub>2</sub> e ±1.06%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Premium Petrol	litre	2.42269731	2.321331529	0.0307693765	0.070596405	CO <sub>2</sub> e ±1.86%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%
Regular Petrol	litre	2.383126924	2.283122022	0.0303562842	0.0696486174	CO <sub>2</sub> e ±1.86%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%

**Notes:** No estimates are available for marine diesel as Marsden Point oil refinery has stopped making the marine diesel blend. If an entity was using marine diesel, it is now likely to be using light fuel oil; use the corresponding emission factor for light fuel oil instead. These petrol emission factors may be different from those in the ETS regulations<sup>12</sup>.

### 3.3.2. GHG inventory development

To calculate transport fuel emissions, first collect data on the quantity of fuel, and then multiply this by the appropriate emission factor from the table.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = quantity of fuel used (unit)
- F = appropriate emission factors from [Table 3.3](#)

All entities across sectors typically report emissions using data on the amount of fuel used during the reporting period. Quantified units of fuel weight or volume (commonly in litres) are preferable. If this information is unavailable see [Section 3.3.3](#).

### TRANSPORT FUEL: EXAMPLE CALCULATION

Example calculation of 40000 liters of Regular Petrol used.

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	40,000 x 0.0303562842 kg CO <sub>2</sub> -e per litre	1,210 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	40,000 x 2.283122022 kg CO <sub>2</sub> -e per litre	91,300 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	40,000 x 0.0696486174 kg CO <sub>2</sub> -e per litre	2,790 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	40,000 x 2.383126924 kg CO <sub>2</sub> -e per litre	95,300 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 3.3.3. When no fuel data are available

If your records only provide information on kilometres (km) travelled, and you do not have information on fuel use, see [Section 7](#). Factors such as individual vehicle fuel efficiency and driving efficiency mean that kilometre-based estimates of carbon dioxide equivalent emissions are less accurate than calculating emissions based on fuel-use data. Therefore, only use the emission factors based on distance travelled if information on fuel use is not available.

Calculating transport fuel based on dollars spent is less accurate and should only be applied to taxis. See [Section 7.2](#).

### 3.3.4. Emission factor derivation methodology

We applied the same methodology to the transport fuels that we used to calculate the stationary combustion fuels, using the raw data in [Appendix A](#). The fuel properties of kerosene and aviation gas are 0.0371 and 0.0339 litres per GJ respectively.

### 3.3.5. Assumptions, limitations and uncertainties

We derived the kg CO<sub>2</sub>-e per activity unit emission factors in [Table 3.3](#) using calorific values. All emission factors incorporate relevant oxidation factors sourced from the 2006 IPCC Guidelines for National Greenhouse Gas Inventories<sup>13</sup>.

As with the fuels for stationary combustion, these emission factors are not full fuel-cycle emission factors and do not incorporate the indirect (Scope 3) emissions associated with the extraction, production and transport of the fuel.

## 3.4. Biofuels and biomass

This section provides emission factors for bioethanol, biodiesel and wood emission sources.

The carbon dioxide emitted from the combustion of biofuels and biomass (including wood) is biogenic, meaning it equates to the carbon dioxide absorbed by the feedstock during its lifespan. This means we treat the carbon dioxide portion of the combustion emissions of biofuels as carbon neutral. However, these CO<sub>2</sub> emissions still need to be reported separately in the inventory, under biogenic emissions. This is why the kg CO<sub>2</sub>-e/unit figures in Table 3.4 are the sum of the CH<sub>4</sub> and N<sub>2</sub>O.

The combustion of biofuels generates anthropogenic methane and nitrous oxide. Entities should calculate and report these gases as is done at the national level according to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories<sup>14</sup>.

Table 3.4 details the emission conversion factors for the GHG emissions from the combustion of biofuels.

**Table 3.4: Biofuels and Biomass Emission Factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties	BCO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)
<b>Biofuel</b>							
Biodiesel (GJ)	GJ	1.485825	0	0.504	0.981825	CO <sub>2</sub> e ±37.14%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	67.26
Biodiesel (litre)	litre	0.0541153105	0	0.0183562105	0.0357591	CO <sub>2</sub> e ±37.14%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	2.44968
Biodiesel blend B20	litre	2.155367546	2.111423727	0.0068363657	0.037107454	CO <sub>2</sub> e ±1.31%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	0.489936
Biodiesel blend B5	litre	2.549352341	2.507315676	0.0046763948	0.0373602704	CO <sub>2</sub> e ±1.23%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	0.122484
Bioethanol (GJ)	GJ	2.518	0	0.504	2.014	CO <sub>2</sub> e ±41.23%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	64.2

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties	BCO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)
Bioethanol (litre)	litre	0.0594248	0	0.0118944	0.0475304	CO <sub>2</sub> e ±41.23%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	1.51512
Bioethanol blend E10	litre	2.186370059	2.089198376	0.0288818789	0.0682898045	CO <sub>2</sub> e ±1.95%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	0.151512
Bioethanol blend E3	litre	2.31341586	2.214628361	0.0298024277	0.0689850709	CO <sub>2</sub> e ±1.89%, CO <sub>2</sub> ±1.0%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	0.0454536
<b>Biomass - Commercial Use</b>							
Wood - Chips	kg	0.1146552	0	0.101808	0.0128472	CO <sub>2</sub> e ±44.75%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	1.35542
Wood - Pellets	kg	0.143701184	0	0.12759936	0.016101824	CO <sub>2</sub> e ±44.75%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	1.698793067
<b>Biomass - Manufacturing Use</b>							
Wood - Chips	kg	0.023028	0	0.0101808	0.0128472	CO <sub>2</sub> e ±35.59%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	1.35542
Wood - Green	kg	0.01350976	0	0.005972736	0.007537024	CO <sub>2</sub> e ±35.59%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	0.7951797333

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties	BCO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)
Wood – Pellets	kg	0.02886176	0	0.012759936	0.016101824	CO <sub>2</sub> e ±35.59%, CH <sub>4</sub> ±50.0%, N <sub>2</sub> O ±50.0%	1.698793067

**Notes:** The total CO<sub>2</sub>-e emission factor for biofuels and biomass only includes methane and nitrous oxide emissions. This is based on [ISO 14064-1:2018](#) and the [GHG Protocol](#) reporting requirements for combustion of biomass as direct (Scope 1) emissions. Carbon dioxide emissions from the combustion of biologically sequestered carbon are reported separately.

### 3.4.1. GHG inventory development

Note that although the direct (Scope 1) carbon dioxide emissions of biomass combustion are considered carbon neutral over the short-term carbon cycle, entities should still report the carbon dioxide released through biofuel and biomass combustion<sup>15</sup>.

Calculate the carbon dioxide emissions in the same way as the direct emissions. Then, instead of including them within the emissions total (where CH<sub>4</sub> and N<sub>2</sub>O gases are reported), list them as a separate line item called 'biogenic emissions'. This ensures the entity is transparent regarding all potential sources of carbon dioxide from its activities.

To calculate biofuel and biomass emissions, first collect data on the quantity of fuel used then multiply this by the appropriate emission factor from the table.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = quantity of fuel used (unit)
- F = appropriate emission factors from [Table 3.4](#)

Entities can calculate emissions from biofuel blends if the specific per cent blend is known.

$$X\% \text{ biofuel blend emission factor} = (X\% \times \text{pure biofuel emission factor}) + ((1 - X\%) \times \text{fossil fuel emission factor})$$

#### BIOFUELS AND BIOMASS: EXAMPLE CALCULATION

An entity uses 100 per cent biofuel in five vehicles. They use 7,000 litres of biodiesel in the reporting year:

Non-biogenic component (reported as Scope/Category 1)

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	7,000 x 0.0183562105 kg CO <sub>2</sub> -e per litre	128 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	7,000 x 0 kg CO <sub>2</sub> -e per litre	0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	7,000 x 0.0357591 kg CO <sub>2</sub> -e per litre	250 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	7,000 x 0.0541153105 kg CO <sub>2</sub> -e per litre	379 kg CO <sub>2</sub> -e

Biogenic component (reported separately)

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
BCO <sub>2</sub> emissions	7,000 x 2.44968 kg CO <sub>2</sub> -e per litre	17,100 kg CO <sub>2</sub> -e

An entity wants to report on its Scope 1 fuel emissions (in kg CO<sub>2</sub>-e/litre) from a specific biodiesel blend of 10 per cent. It is known that

- mineral diesel emission factor 2.680680605 kg CO<sub>2</sub>-e/litre
- biodiesel emission factor 0.0541153105 kg CO<sub>2</sub>-e/litre

Therefore, 10 per cent biodiesel blend emission factor =  $(10\% \times 0.0541153105) + [(1-10\%) \times 2.680680605] = 2.41802407555$  kg CO<sub>2</sub>-e/litre biofuel blend

Note: Numbers may not add due to rounding.

### 3.4.2. Emission factor derivation methodology

We applied the same methodology to the biofuels that we used to calculate the stationary combustion fuels, using the raw data in [Appendix A](#).

The E3 and E10 bioethanol blends consist of 3 per cent and 10 per cent bioethanol respectively, with the remaining contribution made up of diesel. For the two biodiesel blends, B5 and B20, each consists of 5 per cent and 20 per cent biodiesel respectively, with the remaining contribution made up of diesel.

### 3.4.3. Assumptions, limitations and uncertainties

The same assumptions, limitations and uncertainties associated with transport and stationary combustion apply to biofuels.

## 3.5. Transmission and distribution losses for reticulated gases

### 3.5.1. Emissions factors

The emission factor for reticulated natural gas transmission and distribution losses accounts for fugitive emissions from the transmission and distribution system for natural gas. These emissions occur during the delivery of the gas to the end user.

If an entity consumes reticulated gas, for example, for cooking (as shown in the example calculation under [Section 3.5.2.1](#)), related natural gas transmission and distribution losses emissions would fall under Scope 3/ Category 3. See page 41 of the [GHG Protocol Corporate Value Chain \(Scope 3\) Accounting and Reporting Standard](#).

Fugitive emissions from reticulated natural gas transmission and distribution losses only fall under Scope 1 for specific sectors (eg, gas distribution businesses).

Reticulated gases are delivered via a piped gas system. Users should be aware what type of reticulated gas they are receiving: natural gas or liquefied petroleum gas (LPG). Reticulated LPG is supplied in parts of Canterbury and Otago only (natural gas is not available in the South Island). The guide assumes there are no transmission and distribution losses from reticulated LPG due to the chemical composition of the gas. Because LPG is a mixture of propane and butane, it does not emit fugitive greenhouse gases.

[Table 3.5](#) details the emission factors for the transmission and distribution losses for reticulated natural gas. These represent an estimate of the average amount of carbon dioxide equivalents emitted from losses associated with the delivery (transmission and distribution) of each unit of gas consumed through local distribution networks in 2023. They are average figures and therefore make no allowance for distance from off-take point, or other factors that may vary between individual consumers.

**Table 3.5: Transmission and distribution loss emission factors for natural gas**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Reticulated Gases</b>					
Natural gas used (GJ)	GJ	1.725606165	0.0149951976	1.710610967	0
Natural gas used (kWh)	kWh	0.0062121822	0.0000539827	0.0061581995	0

### 3.5.2. GHG inventory development

To calculate the emissions from transmission and distribution losses, entities should first collect data on the quantity of natural gas used and then multiply this by the emission factors for each gas.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = quantity of fuel used (unit)
- F = appropriate emission factors from [Table 3.5](#).

#### TRANSMISSION AND DISTRIBUTION LOSSES: EXAMPLE CALCULATION

An entity uses 800 gigajoules of distributed natural gas in the reporting period.

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	800 x 1.710610967 kg CO <sub>2</sub> -e per GJ	1,370 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	800 x 0.0149951976 kg CO <sub>2</sub> -e per GJ	12.0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	800 x 0 kg CO <sub>2</sub> -e per GJ	0 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	800 x 1.725606165 kg CO <sub>2</sub> -e per GJ	1,380 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 3.5.3. Emission factor derivation methodology

MBIE provided data on losses from transmission and distribution. The fugitive losses of natural gas are predominantly methane but include a component of carbon dioxide.

We derived the emission factor by using MBIE data for distribution and transmission gas losses, which is based on estimates provided by Firstgas.

Transmission emission estimates were modelled to include vented gas, own use gas and fugitive emissions from industry assets and work undertaken.

For distribution, an emissions estimate model using a best practice MarcoGaz template was applied, along with internationally published emission rates in the American Petroleum Institute's [Compendium of Greenhouse Gas Emissions Methodologies for the Natural Gas and Oil Industry](#), combined with company specific asset values. This is complemented by annual asset level leakage measurements.

The CO<sub>2</sub> values from these datasets are summed, and the CH<sub>4</sub> values are summed and then multiplied by the global warming potential of 28. These total losses are then divided by the total reticulated natural gas delivered.

### 3.5.4. Assumptions, limitations and uncertainties

The guide assumes there are no transmission and distribution losses from reticulated LPG.

## 4. Refrigerant and other gases

### 4.1. Overview of changes since previous update

Table 4.1: Summary of changes to refrigerant and other gases emission factors

Domain	Emission factors	Size of change	Explanation for change
Refrigerant & other gases	Propane (R-290)	-98%	Last year's edition of the Measure Emissions Guide used the AR4 value for this emissions factor. It has since been corrected to reflect the AR5 value.
	436A	-55%	This refrigerant blend contains R-290 and is affected by the correction to Propane (R-290). This gas has a low GWP at 1.35 kg CO <sub>2</sub> -e.
	436B	-51%	This refrigerant blend contains R-290 and is affected by the correction to Propane (R-290). This gas has a low GWP at 1.47 kg CO <sub>2</sub> -e.

### 4.2. Refrigerant use

GHG emissions from hydrofluorocarbons (HFCs) are associated with unintentional leaks and spills from refrigeration units, HVAC systems, air conditioners and heat pumps. Quantities of HFCs in a GHG inventory may be small, but HFCs have very high GWPs so emissions from this source may be material. Also, emissions associated with this sector have grown significantly as they replace ozone depleting chemicals such as CFCs and HCFCs.

The list of refrigerant gases is continuously evolving with technology and scientific knowledge. We note that if a known gas is not listed in this guide, it does not imply there is no impact.

Emissions from HFCs are determined by estimating refrigerant equipment leakage and multiplying the leaked amount by the GWP of that refrigerant. There are three methods depending on the data available, see [Section 4.3.1](#), [Section 4.3.2](#), and [Section 4.3.3](#).

If you consider it likely that emissions from refrigerant equipment and leakage are a significant proportion of your total emissions (eg, greater than 5 per cent), include them in your GHG inventory. You may need to carry out a preliminary screening test to determine if this is a material source.

If the reporting entity owns or controls the refrigeration units, emissions from refrigeration are direct (Scope 1). If the entity leases the unit, associated emissions should be reported under indirect (Scope 3) emissions.

## 4.3. Global warming potentials (GWPs) of refrigerants and other GHGs

Table 4.2 details the GWPs (shown in kg CO<sub>2</sub>-e) of the refrigerants included in this section. The GWP is effectively the emission factor for each unit of refrigerant gas lost to the atmosphere. The guide uses the 100 year GWPs from the IPCC's AR5 to ensure consistency with *New Zealand's Greenhouse Gas Inventory 1990-2023*.

Some refrigerants are a mixture (or blend) of gases. If you know the blend composition, you can calculate the GWP based on the percentage mass of each gas. Alternatively, for the AR5 GWP of various refrigerant mixtures, see [Section B.1](#).

These emission factors refer to direct emissions, not the indirect emissions associated with the production and supply of these refrigerants.

**Table 4.2: Refrigerants Emission Factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
<b>Refrigerants</b>		
Propane (R-290) - C <sub>3</sub> H <sub>8</sub>	kg	0.06
Isobutane(R-600a) - C <sub>4</sub> H <sub>10</sub>	kg	3
Nitrous oxide (R-744a) - N <sub>2</sub> O	kg	265
Carbon dioxide (R - 744) - CO <sub>2</sub>	kg	1
Methane - CH <sub>4</sub>	kg	28
<b>Substances controlled by the Montreal Protocol</b>		
CFC-13 (R-13) - CClF <sub>3</sub>	kg	13900
HCFC-123 (R-123) - CHCl <sub>2</sub> CF <sub>3</sub>	kg	79
Carbon tetrachloride (R-10) - CCl <sub>4</sub>	kg	1730
HCFC-225ca (R-225ca) - CHCl <sub>2</sub> CF <sub>2</sub> CF <sub>3</sub>	kg	127
HCFC-225cb (R- 225cb) - CHClF <sub>2</sub> CClF <sub>2</sub>	kg	525
Halon-1211 (R-1211) - CBrClF <sub>2</sub>	kg	1750
HCFC-124 (R-124) - HCFCF <sub>3</sub>	kg	527
HCFC-141b (R-141b) - CH <sub>3</sub> CCl <sub>2</sub> F	kg	782
HCFC-142b (R-142b) - CH <sub>3</sub> CClF <sub>2</sub>	kg	1980
CFC-115 (R-115) - CClF <sub>2</sub> CF <sub>3</sub>	kg	7670
HCFC-21 - CHCl <sub>2</sub> F	kg	148
CFC-114 (R-114) - CClF <sub>2</sub> CClF <sub>2</sub>	kg	8590
CFC-11 (R-11) - CCl <sub>3</sub> F	kg	4660

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
CFC-113 (R-113) - CCl <sub>2</sub> FCFCl <sub>2</sub>	kg	5820
Halon-1301 (R-1301) - CBrF <sub>3</sub>	kg	6290
Halon-2402 (R-2402) - CBrF <sub>2</sub> CBrF <sub>2</sub>	kg	1470
Methyl bromide - CH <sub>3</sub> Br	kg	2
Methyl chloroform - CH <sub>3</sub> CCl <sub>3</sub>	kg	160
CFC-12 (R-12) - CCl <sub>2</sub> F <sub>2</sub>	kg	10200
HCFC-22 (R-22) - CHClF <sub>2</sub>	kg	1760
<b>Hydrofluorocarbons</b>		
HFC-32 (R-32) - CH <sub>2</sub> F <sub>2</sub>	kg	677
HFC-236fa (R-236fa) - CF <sub>3</sub> CH <sub>2</sub> CF <sub>3</sub>	kg	8060
HFC-245fa (R-245fa) - CHF <sub>2</sub> CH <sub>2</sub> CF <sub>3</sub>	kg	858
HFC-236cb - CH <sub>2</sub> FCF <sub>2</sub> CF <sub>3</sub>	kg	1210
HFC-23 (R-23) - CHF <sub>3</sub>	kg	12400
HFC-227ea (R-227ea) - CF <sub>3</sub> CHF <sub>2</sub> CF <sub>3</sub>	kg	3350
HFC-245ca - CH <sub>2</sub> FCF <sub>2</sub> CHF <sub>2</sub>	kg	716
HFC-134 - CHF <sub>2</sub> CHF <sub>2</sub>	kg	1120
HFC-134a (R-134a) - CH <sub>2</sub> FCF <sub>3</sub>	kg	1300
HFC-125 (R-125) - CHF <sub>2</sub> CF <sub>3</sub>	kg	3170
HFC-152 - CH <sub>2</sub> FCH <sub>2</sub> F	kg	16
HFC-143 - CH <sub>2</sub> FCHF <sub>2</sub>	kg	328
HFC-43-10mee - CF <sub>3</sub> CHFCH <sub>2</sub> CF <sub>3</sub>	kg	1650
HFC-365mfc (R-365mfc) - CH <sub>3</sub> CF <sub>2</sub> CH <sub>2</sub> CF <sub>3</sub>	kg	804
HFC-236ea - CHF <sub>2</sub> CHF <sub>2</sub> CF <sub>3</sub>	kg	1330
HFC-161 - CH <sub>3</sub> CH <sub>2</sub> F	kg	4
HFC-152a (R-152a) - CH <sub>3</sub> CHF <sub>2</sub>	kg	138
HFC-143a (R-143a) - CH <sub>3</sub> CF <sub>3</sub>	kg	4800
HFC-41 - CH <sub>3</sub> F	kg	116
<b>Perfluorinated Compounds</b>		
Perfluorocyclopropane - c-C <sub>3</sub> F <sub>6</sub>	kg	9200
PFC-91-18 - C <sub>10</sub> F <sub>18</sub>	kg	7190
Sulphur hexafluoride - SF <sub>6</sub>	kg	23500
Trifluoromethyl sulphur pentafluoride - SF <sub>5</sub> CF <sub>3</sub>	kg	17400

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
PFC-318 – c-C <sub>4</sub> F <sub>8</sub>	kg	9540
PFC-51-14 – n-C <sub>6</sub> F <sub>14</sub>	kg	7910
PFC-41-12 – n-C <sub>5</sub> F <sub>12</sub>	kg	8550
Nitrogen trifluoride – NF <sub>3</sub>	kg	16100
PFC-31-10 – C <sub>4</sub> F <sub>10</sub>	kg	9200
PFC-116 – C <sub>2</sub> F <sub>6</sub>	kg	11100
PFC-14 – CF <sub>4</sub>	kg	6630
PFC-218 – C <sub>3</sub> F <sub>8</sub>	kg	8900
<b>Fluorinated Ethers</b>		
HFE-338pcc13 (HG-01) – CHF <sub>2</sub> OCF <sub>2</sub> CF <sub>2</sub> OCHF <sub>2</sub>	kg	2910
HFE-338mcf2 – CF <sub>3</sub> CH <sub>2</sub> OCF <sub>2</sub> CF <sub>3</sub>	kg	929
HFE-329mcc2 – CHF <sub>2</sub> CF <sub>2</sub> OCF <sub>2</sub> CF <sub>3</sub>	kg	3070
HCFE-235da2 (Isoflurane) – CHF <sub>2</sub> OCHClCF <sub>3</sub>	kg	491
HFE-227ea – CF <sub>3</sub> CHFOCF <sub>3</sub>	kg	6450
HFE-125 – CHF <sub>2</sub> OCF <sub>3</sub>	kg	12400
HFE-134 – CHF <sub>2</sub> OCHF <sub>2</sub>	kg	5560
HFE-143a – CH <sub>3</sub> OCF <sub>3</sub>	kg	523
HFE-347mcc3 – CH <sub>3</sub> OCF <sub>2</sub> CF <sub>2</sub> CF <sub>3</sub>	kg	530
HFE-347mcf2 – CHF <sub>2</sub> CH <sub>2</sub> OCF <sub>2</sub> CF <sub>3</sub>	kg	854
HFE-347pcf2 – CHF <sub>2</sub> CF <sub>2</sub> OCH <sub>2</sub> CF <sub>3</sub>	kg	889
HFE-356mec3 – CH <sub>3</sub> OCF <sub>2</sub> CHFCF <sub>3</sub>	kg	387
HFE-356pcc3 – CH <sub>3</sub> OCF <sub>2</sub> CF <sub>2</sub> CHF <sub>2</sub>	kg	413
HFE-356pcf2 – CHF <sub>2</sub> CH <sub>2</sub> OCF <sub>2</sub> CHF <sub>2</sub>	kg	719
HFE-356pcf3 – CHF <sub>2</sub> OCH <sub>2</sub> CF <sub>2</sub> CHF <sub>2</sub>	kg	446
HFE-365mcf3 – CF <sub>3</sub> CF <sub>2</sub> CH <sub>2</sub> OCH <sub>3</sub>	kg	1
HFE-374pc2 – CHF <sub>2</sub> CF <sub>2</sub> OCH <sub>2</sub> CH <sub>3</sub>	kg	627
HFE-245fa1 – CHF <sub>2</sub> CH <sub>2</sub> OCF <sub>3</sub>	kg	828
HFE-245fa2 – CHF <sub>2</sub> OCH <sub>2</sub> CF <sub>3</sub>	kg	812
HFE-254cb2 – CH <sub>3</sub> OCF <sub>2</sub> CHF <sub>2</sub>	kg	301
HFE-245cb2 – CH <sub>3</sub> OCF <sub>2</sub> CF <sub>3</sub>	kg	654
HFE-236ca12 (HG-10) – CHF <sub>2</sub> OCF <sub>2</sub> OCHF <sub>2</sub>	kg	5350

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
HFE-236ea2 - CHF <sub>2</sub> OCHF <sub>2</sub> CF <sub>3</sub>	kg	1790
HFE-236fa - CF <sub>3</sub> CH <sub>2</sub> OCF <sub>3</sub>	kg	979
HFE-263fb2 - CF <sub>3</sub> CH <sub>2</sub> OCH <sub>3</sub>	kg	1
HFE-43-10pccc124 (H-Galden 1040x) - CHF <sub>2</sub> OCF <sub>2</sub> OC <sub>2</sub> F <sub>4</sub> OCHF <sub>2</sub>	kg	2820
HFE-449sl (HFE-7100) - C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	kg	421
HFE-569sf2 (HFE-7200) - C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	kg	57
<b>Perfluoropolyethers</b>		
PFPME - CF <sub>3</sub> OCF(CF <sub>3</sub> )CF <sub>2</sub> OCF <sub>2</sub> OCF <sub>3</sub>	kg	9710
<b>Hydrocarbons and other compounds - Direct Effects</b>		
Chloroform - CHCl <sub>3</sub>	kg	16
Halon-1201 - CHBrF <sub>2</sub>	kg	376
Methyl chloride - CH <sub>3</sub> Cl	kg	12
Methylene chloride - CH <sub>2</sub> Cl <sub>2</sub>	kg	9
Dimethylether - CH <sub>3</sub> OCH <sub>3</sub>	kg	1
<b>Refrigerant blends: Zeotropes</b>		
416A - R-134a/124/600 (59.0/39.5/1.5)	kg	975.21
422A - R-125/134a/600a (85.1/11.5/3.4)	kg	2847.272
409A - R-22/124/142b (60.0/25.0/15.0)	kg	1484.75
436A - R-290/600 (56.0/44.0)	kg	1.3536
406A - R-22/600a/142b (55.0/4.0/41.0)	kg	1779.92
403B - R-290/22/218 (5.0/56.0/39.0)	kg	4456.603
410A - R-32/125 (50.0/50.0)	kg	1923.5
407C - R-32/125/134a (23.0/25.0/52.0)	kg	1624.21
407F - R-32/125/134a (30.0/30.0/40.0)	kg	1674.1
408A - R-125/143a/22 (7.0/46.0/47.0)	kg	3257.1
502 - R-22/115 (48.8/51.2)	kg	4785.92
436B - R-290/600 (52.0/48.0)	kg	1.4712
404A - R-125/143a/134a (44.0/52.0/4.0)	kg	3942.8

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
417A – R-125/134a/600 (46.6/50.0/3.4)	kg	2127.322
413A – R-218/134a/600a (9.0/88.0/3.0)	kg	1945.09
409B – R-22/124/142b (65.0/25.0/10.0)	kg	1473.75
<b>Refrigerant blends: Azeotropes</b>		
507A – R-125/143a (50.0/50.0)	kg	3985
<b>Medical Gases (AR5 GWPs)</b>		
HFE-347mmz1 (Sevoflurane) – (CF <sub>3</sub> ) <sub>2</sub> CHOCH <sub>2</sub> F	kg	216
Entonox – N <sub>2</sub> O/O <sub>2</sub> (57.9/42.1) (50.0/50.0 vol.)	kg	153.435
HCFE-235da2 (Isoflurane) – CHF <sub>2</sub> OCHClCF <sub>3</sub>	kg	491
HFE-236ea2 (Desflurane) – CHF <sub>2</sub> OCHFClCF <sub>3</sub>	kg	1790
Entonox – N <sub>2</sub> O/O <sub>2</sub> (57.9/42.1) (50.0/50.0 vol.)	kg	153.435
HCFE-235da2 (Isoflurane) – CHF <sub>2</sub> OCHClCF <sub>3</sub>	kg	491
HFE-236ea2 (Desflurane) – CHF <sub>2</sub> OCHFClCF <sub>3</sub>	kg	1790
HFE-347mmz1 (Sevoflurane) – (CF <sub>3</sub> ) <sub>2</sub> CHOCH <sub>2</sub> F	kg	216

### 4.3.1. GHG inventory development

There are three approaches to estimate HFC leakage from refrigeration equipment, depending on the data available. The ideal method is the top-up method, Method A. Method B is the next best option. Method C is the least preferred because it has the most assumptions.

It is stressed that for all methods, users must individually identify the type of refrigerant because the GWPs vary widely.

Entities should indicate the method(s) used in their inventories to reflect the levels of accuracy and uncertainty.

### 4.3.2. Method A: Top-up

The best method to determine if emissions have occurred is through confirming if any top-ups were necessary during the measurement period. A piece of equipment is ‘charged’ with refrigerant gas, and any leaked gas must be replaced. Assuming that the system was at capacity before the leakage occurred and is full again after

a top-up, the amount of top-up gas is equal to the gas leaked or lost to the atmosphere. The equipment maintenance service provider can typically provide information about the actual amount of refrigerant used to replace what has leaked.

$$\text{Gas used (kg)} \times \text{GWP} = \text{Emissions (kg CO}_2\text{-e)}$$

Where:

- E = emissions from equipment in kg CO<sub>2</sub>-e
- GWP = the 100-year global warming potential of the refrigerant used in equipment [Table 4.2](#), shown as kg CO<sub>2</sub>-e

### 4.3.3. Methods B and C: Screening

If top-up amounts are not available, we recommend using one of the following two methods for estimating leakage, depending on the equipment and available information. [Section B.1](#) details both methods.

Method B is based on default leakage rates and known refrigerant type and volume. Use Method B when the type and amount of refrigerant held in a piece of equipment are known.

Method C is the same as Method B except that it allows default refrigerant quantities to be used as well as default leakage rates. Use Method C to estimate both volume of refrigerant and leakage rate when the amount of refrigerant held in a piece of equipment is not known.

Methods B and C are based on the screening approach outlined in the [GHG Protocol HFC tool](#) (WRI/WBCSD, 2005).

For most equipment, Method B is acceptable, especially for factory and office situations where refrigeration and air-conditioning equipment is incidental rather than central to operations. In some cases, Method C is only suitable for a screening estimate. Screening is a way of determining if the equipment should be included or excluded based on materiality of emissions from refrigerants. Entities should then try to source data based on the top-up-method.

We provide refrigerant emissions calculation examples below.

Company A performs a stocktake of refrigeration-related equipment and identifies the following units:

- one large commercial-sized chiller unit
- one commercial-sized office air conditioning unit.

Using the top-up approach, the calculation is as follows:

#### REFRIGERANT USE METHOD A: EXAMPLE CALCULATION

##### Method A: Top-up

Chiller unit: During the 2022 calendar year, a service technician confirmed a top-up of 6 kg of HFC-134a (AR5 GWP = 1,300) in December 2022. The technician also confirmed that when last serviced at the end of December 2021, no top-ups were needed. So, we assume all the 6 kg of gas was lost during calendar year 2022.

So, for the 2022 calendar,

$$6 \text{ kg HFC-134a} \times 1300 = 7,800 \text{ kg CO}_2\text{-e}$$

Air conditioning unit: During the 2022 calendar year, a service technician confirmed a top-up of 6 kg of HFC-143a (AR5 = 4,800) in July 2022. The technician also confirmed that when last serviced at the end of July 2021, no top-ups were needed. So, we assume all the gas was lost at an even rate during the 12 months between service visits, and six of those months sit in the 2022 measurement period.

$$6 \text{ kg}/12 \text{ months} = 0.5 \text{ kg per month}$$

So, for the 2022 calendar year inventory,  $0.5 \times 6 \text{ months} = 3 \text{ kg}$ . Emissions calculate as:

$$3 \text{ kg HFC-143a} \times 4800 = 14,400 \text{ kg CO}_2\text{-e}$$

Note: Numbers may not add due to rounding.

If information was not available from the technician, Company A could use the following approach:

## REFRIGERANT USE METHOD B: EXAMPLE CALCULATION

### Method B: Screening method with default annual leakage rate

Chiller unit: Compliance plates on the equipment confirm the refrigerant is HFC-134a (AR5 GWP = 1,300) and the volume held is 12 kg. For the chiller unit size, the default leakage rate is 8%.

So, for the 2022 calendar year,

$$12 \text{ kg HFC-134a} \times 1300 * 8\% = 1,250 \text{ kg CO}_2\text{-e}$$

Air conditioning unit: A service technician confirms the refrigerant is HFC-143a (AR5 GWP = 4,800) and the volume held is 12 kg. For the size of the unit, the default leakage rate is 3%.

So, for the 2022 calendar year,

$$12 \text{ kg HFC-143a} \times 4800 * 3\% = 1,730 \text{ kg CO}_2\text{-e}$$

Note: Numbers may not add due to rounding.

The difference between Method A and Method B suggests that the leakage of refrigerant exceeds the default leakage rate, so improved maintenance of the refrigeration systems could help reduce leakage.

## 4.4. Medical gases use

This section covers emissions from medical gases. Anaesthetic medical gases can be a significant source of direct (Scope 1) emissions in hospitals. The most accurate way to calculate emissions from medical gases is based on consumption data.

### 4.4.1. Global warming potentials of medical gases

Table 4.3 details the GWPs of the medical gases included in this section (shown in kg CO<sub>2</sub>-e). The GWP is effectively the emission factor for each unit of medical gas lost to the atmosphere. The guide uses IPCC AR5 GWPs.

Some medical gases consist of a mixture (or blend) of gases. If you know the blend composition, you can calculate the GWP based on the percentage of each gas.

Table 4.3: Medical Gases Emission Factors

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
<b>Medical Gases (AR5 GWPs)</b>		
Entonox – N <sub>2</sub> O/O <sub>2</sub> (57.9/42.1) (50.0/50.0 vol.)	kg	153.435
HCFE-235da2 (Isoflurane) – CHF <sub>2</sub> OCHClCF <sub>3</sub>	kg	491
HFE-236ea2 (Desflurane) – CHF <sub>2</sub> OCHFClCF <sub>3</sub>	kg	1790
HFE-347mmz1 (Sevoflurane) – (CF <sub>3</sub> ) <sub>2</sub> CHOCH <sub>2</sub> F	kg	216

### 4.4.2. GHG inventory development

To calculate medical gas emissions, collect consumption data for each medical gas used by the entity, and multiply this by the GWP for each gas.

$$\text{Gas used (kg)} \times \text{GWP} = \text{Emissions (kg CO}_2\text{-e)}$$

Medical gases are supplied in bottles or cylinders. If only the volume of the gas is known, an additional calculation to calculate the mass of the gas is required to estimate emissions. This should be done by multiplying the volume (L) of gas by its density (g/mL or kg/L).

#### MEDICAL GAS USE: EXAMPLE CALCULATION

An entity uses 5 bottles of Isoflurane (HCFE-235da2, AR5 GWP = 491) in the reporting period. Each bottle holds 0.3 kg of Isoflurane. Its direct (Scope 1) emissions are:

$$5 \text{ bottles} \times 0.3 \text{ kg} = 1.5 \text{ kg}$$

$$\text{Total CO}_2\text{-e emissions} = 1.5 \times 491 = 736 \text{ kg CO}_2\text{-e}$$

An entity uses 5 250 mL bottles of Isoflurane (HCFE-235da2, AR5 GWP = 491) in the reporting period. The density of Isoflurane is 1.49 g/mL. Its direct (Scope 1) emissions are:

$5 \text{ bottles} \times 250 \text{ mL} \times 1.49/1,000 = 1.86 \text{ kg}$

Total CO<sub>2</sub>-e emissions =  $1.86 \times 491 = 913 \text{ kg CO}_2\text{-e}$

Note: Numbers may not add due to rounding.

### 4.4.3. Assumptions

This approach assumes that all anaesthetic gases used are eventually emitted, including the gases inhaled by patients.

## 5. Purchased electricity, heat and steam emission factors

Purchased energy, in the form of electricity, heat or steam, is an indirect (Scope 2) emission. This section also includes transmission and distribution losses for purchased electricity, which is an indirect (Scope 3) emissions source.

Note that both the emission factor for purchased electricity and the emission factor for transmission and distribution line losses align with the definitions in the [GHG Protocol](#).

In this guide, we have included a time series of historic electricity emission factors based on annual and quarterly periods. The quarterly time series extends back to March 2022, and the annual time series extends back to 2012. There is also an equivalent annual time series for transmission and distribution losses.

The guide provides information on reporting imported heat and steam and geothermal energy. It does not provide emission factors for these categories as they are unique to a specific site. Users could liaise directly with their supplier of the imported heat, steam, or geothermal energy, for supplier specific emissions intensities suitable for use in the entity inventory.

### 5.1. Overview of changes since previous update

**Table 5.1: Summary of changes to purchased energy emission factors**

Domain	Emission factors	Size of change	Explanation for change
Purchased Energy	Current/latest electricity factor	38.70%	There is no change in methodology. The increase in the emissions factor can be attributed to shifting electricity generation dynamics. In 2022 and 2023, emissions from electricity generation were relatively low due to favourable weather conditions and strong hydro inflows. In contrast, 2024 saw an increase in the proportion of fossil-based generation. This rise impacts associated emissions factors, including Travel and Freight (for electric and PHEV vehicles), and Working from home emissions factors. The 38.7% change is calculated as the difference between the 'Electricity Used - 2023' emission factor, as published in the 2024 Measure Emissions Guide, and the 'Electricity Used - 2024' emission factor in this edition.
Transmission & distribution losses	Electricity Transmission & distribution losses	9.30%	Since the transmission and distribution (T&D) loss factors for 2024 were unavailable, a new methodology was adopted, using the average loss ratio of purchased energy over the 2011–2023 period. The Electricity Transmission & distribution losses factors are affected by the rise in Purchased Energy emissions factors.
	Natural Gas Transmission & distribution losses	-12.90%	Estimated fugitive emissions from both natural gas distribution and transmission networks decreased in 2023 relative to 2022.

## 5.2. Indirect Scope 2 emissions from purchased electricity from the New Zealand grid – using the location-based method

This guide applies to electricity purchased from a supplier that sources electricity from the national grid (i.e., purchased electricity consumed by end users). It does not cover on-site, self-generated-electricity.

The grid-average emission factor best reflects the carbon dioxide equivalent emissions associated with the generation of a unit of electricity purchased from the national grid in New Zealand. We recommend the use of the emission factors in [Table 5.2](#) and [Table 5.3](#) for all electricity purchased from the national grid, apart from when a market-based method is being used.

The emission factor accounts for the emissions from fuel combustion at thermal power stations (ie, power stations which generate electricity by burning fossil fuels) and fugitive emissions from the generation of geothermal electricity.

The emission factor for purchased grid-average electricity does not include transmission and distribution losses. A separate average emission factor for this as an indirect (Scope 3) emission source is in [Section 5.3](#)

The provided emission factors are an average for the whole of New Zealand for a given quarter or year. The actual emissions produced for a given unit of electricity may differ depending on factors such as the time of year, time of day and geographical area.

Using quarterly emission factors accounts for the high seasonal variation seen in electricity emission factors. This variation is generally a result of the higher proportion of fossil-based electricity generation typically used in the winter months. Therefore, using an annual emission factor may over or underestimate your entity's GHG emissions.

Detailed additional guidance on reporting electricity emissions is available in the [GHG Protocol Scope 2 Guidance](#).

As with the fuels for stationary combustion emission factors, the electricity emission factors do not incorporate emissions associated with the extraction, production and transport of the fuels burnt to produce electricity.

The emission factors for the annual average purchased electricity based on annual generation from the New Zealand grid is in [Table 5.2](#).

**Table 5.2: Emission factors for purchased grid-average electricity – annual average**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Annual Averages</b>					
Electricity Used – 2012	kWh	0.1729810303	0.1686935231	0.0039810528	0.0003064544
Electricity Used – 2013	kWh	0.1461825561	0.1417469878	0.0042331574	0.000202411
Electricity Used – 2014	kWh	0.1221241874	0.1176384026	0.0043305912	0.0001551936

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Electricity Used - 2015	kWh	0.1168674104	0.1121866766	0.0045398643	0.0001408695
Electricity Used - 2016	kWh	0.0915447009	0.0873594028	0.0041121544	0.0000731438
Electricity Used - 2017	kWh	0.1031083889	0.0992217864	0.0038009348	0.0000856678
Electricity Used - 2018	kWh	0.097861135	0.0943356571	0.0034050511	0.0001204269
Electricity Used - 2019	kWh	0.1105547311	0.1073371928	0.0030453883	0.00017215
Electricity Used - 2020	kWh	0.1216915353	0.1185907619	0.0029089182	0.0001918553
Electricity Used - 2021	kWh	0.123323991	0.1202492404	0.0028198509	0.0002548997
Electricity Used - 2022	kWh	0.0818949105	0.0790391248	0.0027617069	0.0000940788
Electricity Used - 2023	kWh	0.0766302343	0.0741168037	0.0024372846	0.000076146
Electricity Used - 2024	kWh	0.1011189484	0.0981990601	0.0027303581	0.0001895301

The emission factors for the calendar quarters (quarter end) for 2022–2024 purchased electricity from the New Zealand grid are in [Table 5.3](#).

**Table 5.3: Emission factor for purchased grid-average electricity - calendar quarters**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Quarterly Averages</b>					
Electricity Used - Mar-2022	kWh	0.1096907589	0.1067391622	0.0027958305	0.0001557663
Electricity Used - Jun-2022	kWh	0.1191587201	0.11610675	0.0028724637	0.0001795064
Electricity Used - Sep-2022	kWh	0.0620184374	0.059341421	0.002644798	0.0000322184
Electricity Used - Dec-2022	kWh	0.0394184247	0.0366552982	0.002746336	0.0000167905
Electricity Used - Mar-2023	kWh	0.0769630732	0.0742775535	0.0026301779	0.0000553419
Electricity Used - Jun-2023	kWh	0.0529274691	0.0508234695	0.0020790999	0.0000248997
Electricity Used - Sep-2023	kWh	0.1004640282	0.097897541	0.0024613023	0.000105185

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Electricity Used – Dec-2023	kWh	0.074229804	0.0715148659	0.0025981717	0.0001167664
Electricity Used – Mar-2024	kWh	0.0893041532	0.0864942083	0.0026981896	0.0001117553
Electricity Used – Jun-2024	kWh	0.1365281823	0.1336055275	0.0026064576	0.0003161972
Electricity Used – Sep-2024	kWh	0.1324850764	0.1293692016	0.002824639	0.0002912359
Electricity Used – Dec-2024	kWh	0.0400047226	0.0371942488	0.0027919734	0.0000185005

### 5.2.1. GHG inventory development

To calculate the emissions from purchased electricity, first collect data on the quantity of electricity used during the period in kilowatt hours (kWh), then multiply this by the emission factor. Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = distance travelled by vehicle type (km)
- F = emission factors for correlating vehicle type from [Table 5.2](#) or [Table 5.3](#).

All entities across sectors typically report emissions using data on the amount of electricity used during the reporting period. Quantified units of electricity consumed are preferable.

#### PURCHASED ELECTRICITY: EXAMPLE CALCULATION

An entity uses 800,000 kWh of electricity in the 2023 reporting period. Its indirect (Scope 2) emissions from electricity are:

##### Example calculation of purchased electricity emissions

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	800,000 x 0.0024372846 kg CO <sub>2</sub> -e per kWh	1,950 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	800,000 x 0.0741168037 kg CO <sub>2</sub> -e per kWh	59,300 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	800,000 x 0.000076146 kg CO <sub>2</sub> -e per kWh	60.9 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	800,000 x 0.0766302343 kg CO <sub>2</sub> -e per kWh	61,300 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 5.2.2. Emission factor derivation methodology

MBIE calculated the generation emission factors based on emissions from the generation of public electricity and the amount of electricity generated.

[Table 5.4](#) details the MBIE data provided to calculate the annual emission factors

**Table 5.4: Information used to calculate the purchased electricity emission factor 2011-2023**

Year	Emissions of CO2 from public electricity generation (kt)	Public electricity generation (GWh)
2011	5,823	41,975
2012	7,224	41,762
2013	5,981	40,916
2014	5,035	41,232
2015	4,872	41,881
2016	3,799	41,501
2017	4,315	41,850
2018	4,110	41,999
2019	4,674	42,278
2020	4,967	41,706
2021	4,962	41,682
2022	3,237	41,920
2023	3,055	41,917

### 5.2.3. Assumptions, limitations and uncertainties

Using an annual average grid emission factor for electricity will inevitably introduce a certain level of inaccuracy, as the generation mix varies depending on your geographical location, by time of day and time of year.

We derived the emission factors in [Table 5.2](#) and [Table 5.3](#) for purchased electricity from generation data rather than consumption data. This emission factor does not account for the emissions associated with the electricity lost in transmission and distribution on the way to the end user. [Table 5.5](#) contains the emission factors for transmission and distribution line losses.

## 5.3. Transmission and distribution losses for electricity

The emission factor for transmission and distribution line losses accounts for the additional electricity generated to make up for electricity lost in the transmission and distribution network. Under the GHG Protocol, end users should report emissions from electricity consumed from a transmission and distribution system as an indirect (Scope 3) emission source. Electricity and distribution companies should however report these losses as indirect (Scope 2) emissions.<sup>16</sup>.

[Table 5.5](#) shows the emissions factors for transmission and distribution losses from the national grid.

**Table 5.5: Transmission and distribution losses for electricity consumption**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Electricity Consumption</b>					
2012	kWh	0.0131555601	0.0128294865	0.0003027672	0.0000233065
2013	kWh	0.0111174815	0.0107801475	0.0003219403	0.0000153938
2014	kWh	0.0092877935	0.0089466404	0.0003293503	0.0000118028
2015	kWh	0.0088880049	0.0085320255	0.0003452659	0.0000107134
2016	kWh	0.0069621612	0.0066438607	0.0003127377	0.0000055627
2017	kWh	0.0078416032	0.0075460192	0.0002890688	0.0000065152
2018	kWh	0.0074425389	0.0071744191	0.0002589611	0.0000091587
2019	kWh	0.0084079128	0.0081632124	0.000231608	0.0000130924
2020	kWh	0.0092548894	0.0090190693	0.0002212292	0.000014591
2021	kWh	0.009379041	0.0091452	0.0002144554	0.0000193856
2022	kWh	0.006228275	0.0060110866	0.0002100334	0.0000071549
2023	kWh	0.0058278856	0.0056367341	0.0001853605	0.0000057911
2024	kWh	0.0076903022	0.0074682388	0.0002076493	0.0000144142

### 5.3.1. GHG inventory development

To calculate the emissions from transmission and distribution losses for purchased electricity, collect data on the quantity of electricity used during the period in kilowatt hours (kWh) and multiply this by the emission factor. Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = distance travelled by vehicle type (km)
- F = emission factors for correlating vehicle type from [Table 5.5](#).

#### TRANSMISSION AND DISTRIBUTION LOSSES: EXAMPLE CALCULATION

An entity uses 800,000 kWh of electricity in the 2023 reporting period. Its indirect (Scope 3) emissions from transmission and distribution losses for purchased electricity are:

##### Example calculation of emissions from Transmission and Distribution Losses for purchased electricity

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	800,000 x 0.0001853605 kg CO <sub>2</sub> -e per kWh	148 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	800,000 x 0.0056367341 kg CO <sub>2</sub> -e per kWh	4,510 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	800,000 x 0.0000057911 kg CO <sub>2</sub> -e per kWh	4.63 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	800,000 x 0.0058278856 kg CO <sub>2</sub> -e per kWh	4,660 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

Alternatively, if your electricity provider gives a breakdown of the transmission and distribution losses this consumption data can be multiplied by a grid-average electricity emission factor from [Table 5.2](#)

### 5.3.2. Emission factor derivation methodology

Emission factors provided directly by MBIE, which uses actual transmission and distribution losses data, resulting in the emission factors more accurately reflect the actual losses on the electricity grid.

### 5.3.3. Assumptions, limitations and uncertainties

This emission factor covers grid-average electricity purchased by an end user. As with all emission factors for purchased electricity, we calculated those for transmission and distribution line losses as a national average.

As it is an average figure, the emission factor makes no allowance for distance from off-take point, or other factors that may vary between individual consumers.

This emission factor does not incorporate the emissions associated with the extraction, production and transport of the fuels burnt to produce the electricity.

## 5.4. Imported heat and steam

Entities that have a specific heat or steam external energy source (such as a district heating scheme) can calculate emissions using an emission factor specific to that scheme. This should be available from the owner of the external energy source.

## 5.5. Geothermal energy

Entities that have their own geothermal energy source can calculate emissions separately using a unique emission factor. Noting carbon emissions from geothermal power stations can be variable over time, this would consider factors such as the measured CO<sub>2</sub> output from the production wells and the CO<sub>2</sub> output at the surface, along with how the water by-product is used, for example, as industrial process heat.

Depending on the steam coming from the borehole, there may or may not be emissions associated with this energy type.

## 6. Indirect business-related emission factors

This section includes guidance and emission factors relating to indirect (Scope 3) emissions from business activities not covered in other sections.

### 6.1. Overview of changes since previous update

Table 6.1: Summary of changes to indirect business-related emission factors

Domain	Emission factors	Size of change	Explanation for change
Working from home	All factors	39.10%	Change is driven by the increase in the latest annual electricity factor, which is used to derive these emissions factors.

### 6.2. Emissions associated with employees working from home

This section provides three emission factors, which incorporate typical emission sources associated with the activities of employees working from home. Employers can use these emission factors to estimate the indirect (Scope 3) emissions associated with staff working from home. The three emission factors for working from home are:

- Working from home – Default
- Working from home – Without heating
- Working from home – With heating.

All three emission factors have been developed based on typical uses of the following emissions sources by staff members working from home a laptop plus monitor, lighting and optionally heating. The default factor assumes heating is run for five months of the year and could be used where more granular data on the actual use of home heating is not available.

Should an entity wish to quantify their employees' working from home emissions in more detail, they can survey staff and use the data provided in [Table 6.2](#), or various emission factors from other sections in this guide.

Note the Working from home – With heating factor should only be used when heating is additional to what would normally be used. In other words, when the heater is being used over and above the normal home heating use. Noting this factor assumes six hours of heating per day.

Table 6.2: Working from home emission factors

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Working From Home</b>					
Working from home – Default	employee days	0.4796520443	0.4658017185	0.0129513002	0.0008990256
Working from home – With heating	employee days	1.05090061	1.020555038	0.0283758391	0.0019697331
Working from home – Without heating	employee days	0.0716173544	0.0695493476	0.0019337723	0.0001342345

### 6.2.1. GHG inventory development

To calculate the emissions for an employee working from home, collect information on the number of days staff have worked from home during the reporting period. You will need to record which of these days heating was used and which it wasn't. If you do not have this data, use the default factor.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = number of employees working from home without heating (days)
- Qh = number of employees working from home with heating (days)
- F = the Working from home – Without heating emission factor from [Table 6.2](#)
- Fh = the Working from home – With heating emission factor from [Table 6.2](#)

#### WORKING FROM HOME: EXAMPLE CALCULATION

An entity has 20 employees and knows through an employee survey or some other means that, on a given day, 12 employees were working from home. Of these, eight used heating each day and four did not use heating. This same daily data was collected over a month and summed as either with or without heating.

Its indirect (Scope 3) emissions from working at home for a given month are:

With heating = 168 employee days

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	168 x 0.0283758391 kg CO <sub>2</sub> -e per employee days	4.77 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	168 x 1.020555038 kg CO <sub>2</sub> -e per employee days	171 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	168 x 0.0019697331 kg CO <sub>2</sub> -e per employee days	0.331 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	168 x 1.05090061 kg CO <sub>2</sub> -e per employee days	177 kg CO <sub>2</sub> -e

Without heating = 84 employee days

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	84 x 0.0019337723 kg CO <sub>2</sub> -e per employee days	0.162 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	84 x 0.0695493476 kg CO <sub>2</sub> -e per employee days	5.84 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	84 x 0.0001342345 kg CO <sub>2</sub> -e per employee days	0.0113 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	84 x 0.0716173544 kg CO <sub>2</sub> -e per employee days	6.02 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

## 6.2.2. Emission factor derivation methodology

To calculate the working from home emission factor, we decided the most appropriate unit would be employee days. Therefore, we would need to calculate how much electricity an employee typically used per day.

It is assumed for both the with and without heating emission factors a working day is 8 hours and all staff use a laptop, monitor and a 12W LED light.

Table 6.3 the emission sources used to derive the working from home factors. The default factor assumes heating is run for five months of the year, assuming a mix of heat pump and portable heater use. The without-heating factor only includes the office-based emission sources. The with-heating factor assumes 50 per cent of staff use electric portable heaters while 50 per cent use heat pumps. It is assumed heating used an average of six hours per working day, each heater type operating for three hours.

**Table 6.3: Data used to calculate the emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Assumptions
<b>Heating</b>						
Heat pump	Employee days	0.3264	0.3170	0.008814	0.000612	4 kWh capacity, 3 hrs per day, 50% of households
Portable electric heater	Employee days	0.6529	0.6340	0.017628	0.001224	2 kWh capacity, 6 hrs per day, 50% of households
<b>Office equipment</b>						
Monitor	Employee days	0.0176	0.0171	0.000477	0.000033	20W 8 hrs per day
Laptop	Employee days	0.0435	0.0423	0.001175	0.000082	50 W 8 hrs per day
Lighting	Employee days	0.0104	0.0101	0.000282	0.000020	12 W 8 hrs per day

### 6.2.3. Employee commuting

To account for the emissions produced by employees commuting between their homes and their worksites, refer to travel emissions in [Section 7](#).

### 6.2.4. The emissions benefits of working from home

There is ongoing discussion and research on whether working from home reduces an employee's carbon footprint.

The carbon benefits of working from home will depend on, among other things, whether avoided emissions are seen from employee commuting. For example, an employee who normally commutes by car for a return trip of 40 km will see a decrease in overall emissions from working at home, whereas someone who normally takes the train or drives an electric vehicle may see an increase in their overall emissions (the sum of that employee's emissions from working at home and commuting).

Similarly, through the increased use of collaborative technologies such as video conferencing and screen-sharing, there may be less need for certain workers to use company vehicles to visit and meet people in person. This would be expected to reduce the entity's vehicle fleet emissions and, in combination with working from home, reduces the employee's carbon footprint.

### 6.2.5. Assumptions, limitations and uncertainties

In the absence of accurate data for New Zealand, a number of assumptions have been made to establish a single default working from home emission factor. It is assumed that all staff use a laptop and one monitor, while in some cases desktops or multiple monitors may be used. There will also be variation in the wattage of the laptops being used, due to factors such as size and the way it is being used.

Acknowledging the likely high variation in the way New Zealand employees heat their office space, there is high uncertainty in this factor. It does not account for situations where unzoned central heating is used to heat the office space, for different heater sizes or for different heating fuels (eg, gas, solid fuels). Further, the assumed six hour running time may not apply in all cases, with some workspaces being better insulated than others. Future updates to the guidance will explore regional averages for heating type and duration.

The default factor assumes heating is used for five months of the year, which again is not likely to reflect all situations.

Given the above limitations, there is opportunity to improve your quality of data behind your inventory through having effective data collection, such as the staff survey suggested above. Since working from home is now ingrained in many New Zealand workplaces, routines have likely developed where many employees are consistently working from home on the same day(s) of the working week. In such cases, it may be relatively easy to ask employees to record which days they work from home, and which days where heating was used. Building on this with more accurate GHG data on employee commuting (which can be included in travel emission factors, [Section 7](#)), will help you understand whether working from home is positively or negatively impacting your carbon footprint.

## 6.3. Guidance on the use of cloud-based data centres

Emissions from data centres come under indirect (Scope 3) emissions. These emissions may be significant for any entity that operates with large third-party IT infrastructure.

Due to the diversity and country location of data centres used by entities in New Zealand it is not possible to produce a single emission factor that would inform users of the kg CO<sub>2</sub>-e each gigabyte of data produces.

Therefore, entities seeking to find out what the footprint is of the data centres where their 'cloud' is stored should contact the providers of their data centre to request this information. Large data centre providers are calculating the total emissions from their data centres and may be able to inform users of the carbon footprint of their usage. Examples of products or tools offered by data centre providers include the Google management tool Carbon Footprint, Microsoft's Emissions Impact Dashboard and Amazon's Customer Carbon Footprint Tool.

## 7. Travel emission factors

This travel emissions section provides detail on how to calculate emissions associated with both business travel and staff commuting.

Business travel emissions result from travel associated with (and generally paid for by) the entity. We provide factors for private and rental vehicles, taxis, public transport, air travel, helicopters and accommodation. Business travel emissions are indirect (Scope 3/Category 6: Business travel) if the entity does not directly own or control the vehicles used for travel. If the entity owns or has an operating lease for the vehicle(s) these emissions are direct (Scope 1/Category 1: Purchased goods and services GHG Protocol) and should be accounted for in transport fuels (see [Section 3.3](#)).

Staff commuting emissions result from employees travelling between their homes and their worksites. Emissions from staff commuting may arise from the use of private and rental vehicles, taxis, public transport, and air travel. Other emissions associated with working from home can be accounted for in *indirect business-related emission factors* (see [Section 6](#)).

Staff commuting emissions are indirect (Scope 3/Category 7: Employee commuting [Section 6.2.3](#)).

### 7.1. Overview of changes since previous update

Table 7.1: Summary of changes to travel emission factors

Domain	Emission factors	Size of change	Explanation for change
Travel	All electric and PHEV passenger vehicles, electric motorcycles	39.10%	The change in all-electric and PHEV passenger vehicles, as well as electric motorcycles, is driven by the increase in the latest annual electricity factor, which is used to derive these emissions factors.
	Business travel - Hotel Stays	-56.7% to +32.1%	The Cornell Hotel Sustainability Benchmarking Index has introduced a new hotel type classification, replacing the previous "All Hotels" group into separate "Resort" and "Non-Resort" categories, with the latter used to calculate the MEG 2025 emissions factors. This had a significant impact, with the factors decreasing for 40 out of the 48 countries provided. 26 of these countries decreased by over 20%.

Domain	Emission factors	Size of change	Explanation for change
	Domestic air travel	n/a	These factors have not been updated from the previous edition. The information required to update these factors was not available in time for this publication.
	International air travel	No change	The International air travel emission factors are sourced from the UK Greenhouse Gas Reporting: Conversion Factors 2022, published by the UK Department for Energy Security and Net Zero (DESNZ). These factors have remained unchanged in the 2023 and 2024 DESNZ editions, meaning they still reflect air travel data influenced by the COVID-19 pandemic. As a result, we continue to use the 2022 edition factors, which are based on pre-COVID air travel data which provides a more representative period for emissions reporting.

## 7.2. Passenger vehicles

This section covers emissions from private vehicles for which mileage is claimed, rental vehicles and taxi travel.

Travel, including rental vehicles, staff mileage and taxi travel are indirect (Scope 3) emissions. This is a change in guidance, to align better with leading practice. As with direct (Scope 1) emissions from transport fuels, the most accurate way to calculate emissions is based on fuel consumption data. Fuel-use data are preferable because factors such as individual vehicle fuel efficiency and driving efficiency mean that kilometre-based estimates of emissions are less accurate. However, this information may not be easily available.

The 2024 fleet statistics ([Table 7.3](#), [Table 7.4](#), [Table 7.5](#) and [Table 7.6](#)) were taken from the Te Manatū Waka Ministry of Transport Vehicle Fleet Emissions Model. This provides energy (fuel and electricity) use per km travelled by vehicle.

Fuel-use based emission factors are provided in [Section 3.3](#).

If the only information known is kilometres travelled, use the emission factors in this section. Factors such as individual vehicle fuel efficiency and driving efficiency mean that kilometre based estimates of carbon dioxide equivalent emissions are less accurate than calculating emissions based on fuel-use data.

If the vehicle size and engine type are known, use the factors in [Table 7.3](#), [Table 7.4](#), [Table 7.5](#) and [Table 7.6](#). [Table 7.7](#) lists default private car emission factors and [Table 7.8](#) lists the default rental car emission factors

based on distance travelled. Table 7.9 lists emission factors for taxi travel based on dollars spent and kilometres travelled.

Table 7.2 details engine sizes and typical corresponding vehicles.

**Table 7.2: Vehicle engine sizes and common car types**

Engine size	Vehicle size	Example vehicles	Comparative electric vehicles
<1350 cc	Very small	Fiat 500	Peugeot iOn
1350-<1600 cc	Small	Suzuki Swift	Renault Zoe
1600-<2000 cc	Medium	Toyota Corolla	Nissan Leaf
2000-<3000 cc	Large	Toyota RAV4	Hyundai Ioniq
>3000 cc	Very large	Ford Ranger	Nissan e-NV200

**Table 7.3: Pre-2010 vehicle fleet emission factors per km travelled**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Pre 2010 Fleet</b>					
Diesel hybrid vehicle: 1350 – <1600 cc	km	0.1823256532	0.1795097807	0.0002690936	0.0025467788
Diesel hybrid vehicle: 1600 – <2000 cc	km	0.1932439545	0.1902594577	0.0002852079	0.0026992889
Diesel hybrid vehicle: 2000 – <3000 cc	km	0.237569648	0.2339005767	0.000350628	0.0033184434
Diesel hybrid vehicle: <1350 cc	km	0.1894659048	0.1865397569	0.0002796319	0.002646516
Diesel hybrid vehicle: ≥3000 cc	km	0.2635284404	0.2594584565	0.0003889404	0.0036810435
Diesel vehicle: 1350 – <1600 cc	km	0.2033911669	0.2002499546	0.0003001841	0.0028410282
Diesel vehicle: 1600 – <2000 cc	km	0.2155709453	0.2122416261	0.0003181602	0.003011159
Diesel vehicle: 2000 – <3000 cc	km	0.265017934	0.2609249461	0.0003911388	0.0037018492
Diesel vehicle: <1350 cc	km	0.2113563878	0.2080921591	0.0003119399	0.0029522888
Diesel vehicle: ≥3000 cc	km	0.2939759494	0.2894357283	0.0004338778	0.0041063433
Motorcycle: <60cc, petrol	km	0.0662625199	0.0634818973	0.0008440524	0.0019365703

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Motorcycle: ≥ 60cc, petrol	km	0.1325250399	0.1269637945	0.0016881047	0.0038731407
Petrol hybrid vehicle: 1350 – <1600 cc	km	0.1542578336	0.147784599	0.0019649372	0.0045082974
Petrol hybrid vehicle: 1600 – <2000 cc	km	0.1736903139	0.16640162	0.0022124682	0.0050762257
Petrol hybrid vehicle: 2000 – <3000 cc	km	0.1929224594	0.1848267128	0.0024574474	0.0056382992
Petrol hybrid vehicle: <1350 cc	km	0.1490491275	0.1427944697	0.0018985886	0.0043560691
Petrol hybrid vehicle: ≥3000 cc	km	0.2307857458	0.2211011144	0.0029397501	0.0067448813
Petrol vehicle: 1350 – <1600 cc	km	0.1953932558	0.1871938254	0.0024889204	0.00571051
Petrol vehicle: 1600 – <2000 cc	km	0.2200077309	0.2107753853	0.0028024597	0.0064298859
Petrol vehicle: 2000 – <3000 cc	km	0.2443684485	0.2341138362	0.0031127667	0.0071418456
Petrol vehicle: <1350 cc	km	0.1887955615	0.180872995	0.0024048789	0.0055176876
Petrol vehicle: ≥3000 cc	km	0.2923286113	0.2800614116	0.0037236835	0.0085435163

**Table 7.4: Vehicle fleet emission factors per km travelled, 2010–2015**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>2010–2015 Fleet</b>					
Diesel hybrid vehicle: 1350 – <1600 cc	km	0.1615804965	0.1590850163	0.0002384759	0.0022570043
Diesel hybrid vehicle: 1600 – <2000 cc	km	0.1712565049	0.1686115865	0.0002527567	0.0023921617
Diesel hybrid vehicle: 2000 – <3000 cc	km	0.2105387861	0.2072871845	0.0003107333	0.0029408683
Diesel hybrid vehicle: <1350 cc	km	0.1679083247	0.1653151162	0.0002478151	0.0023453933
Diesel hybrid vehicle: ≥3000 cc	km	0.2335439666	0.2299370686	0.0003446865	0.0032622115

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Diesel vehicle: 1350 – <1600 cc	km	0.1805474809	0.1777590709	0.0002664692	0.0025219408
Diesel vehicle: 1600 – <2000 cc	km	0.1913592991	0.1884039093	0.0002824263	0.0026729635
Diesel vehicle: 2000 – <3000 cc	km	0.2352332395	0.2316002521	0.0003471797	0.0032858077
Diesel vehicle: <1350 cc	km	0.1876180957	0.1847204857	0.0002769047	0.0026207053
Diesel vehicle: ≥3000 cc	km	0.2609367369	0.2569067797	0.0003851154	0.0036448418
Electric vehicle: 1350 – <1600 cc	km	0.0210148273	0.0204080078	0.0005674308	0.0000393887
Electric vehicle: 1600 – <2000 cc	km	0.0236621497	0.0229788867	0.0006389123	0.0000443506
Electric vehicle: 2000 – <3000 cc	km	0.0262821801	0.0255232617	0.0007096569	0.0000492614
Electric vehicle: <1350 cc	km	0.0203052357	0.0197189063	0.0005482708	0.0000380587
Electric vehicle: ≥3000 cc	km	0.031440365	0.0305325	0.0008489354	0.0000589296
Motorcycle: <60cc, electricity	km	0.0049924743	0.0048483128	0.000134804	0.0000093575
Motorcycle: <60cc, petrol	km	0.0587366048	0.0562717976	0.0007481872	0.00171662
Motorcycle: ≥ 60cc, electricity	km	0.0099849487	0.0096966255	0.0002696081	0.0000187151
Motorcycle: ≥ 60cc, petrol	km	0.1174732097	0.1125435953	0.0014963744	0.00343324
PHEV (Diesel) – Diesel consumption: 1350 – <1600 cc	km	0.0845604598	0.0832544918	0.0001248024	0.0011811656
PHEV (Diesel) – Diesel consumption: 1600 – <2000 cc	km	0.0896242376	0.0882400636	0.000132276	0.001251898
PHEV (Diesel) – Diesel consumption: 2000 – <3000 cc	km	0.1101819647	0.1084802932	0.0001626171	0.0015390544
PHEV (Diesel) – Diesel consumption: <1350 cc	km	0.0878720233	0.0865149108	0.0001296899	0.0012274225

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
PHEV (Diesel) - Diesel consumption: ≥3000 cc	km	0.1222213425	0.1203337326	0.0001803859	0.001707224
PHEV (Diesel) - Electricity consumption: 1350 - <1600 cc	km	0.0101392239	0.0098464459	0.0002737737	0.0000190042
PHEV (Diesel) - Electricity consumption: 1600 - <2000 cc	km	0.0111094484	0.0107886545	0.0002999712	0.0000208228
PHEV (Diesel) - Electricity consumption: 2000 - <3000 cc	km	0.012574282	0.0122111898	0.0003395238	0.0000235683
PHEV (Diesel) - Electricity consumption: <1350 cc	km	0.0105565583	0.0102517295	0.0002850424	0.0000197865
PHEV (Diesel) - Electricity consumption: ≥3000 cc	km	0.0148720932	0.01444265	0.0004015681	0.0000278752
PHEV (Petrol) - Electricity consumption: 1350 - <1600 cc	km	0.0100170677	0.0097278171	0.0002704753	0.0000187753
PHEV (Petrol) - Electricity consumption: 1600 - <2000 cc	km	0.011278958	0.0109532693	0.0003045482	0.0000211405
PHEV (Petrol) - Electricity consumption: 2000 - <3000 cc	km	0.0125278392	0.0121660881	0.0003382698	0.0000234813
PHEV (Petrol) - Electricity consumption: <1350 cc	km	0.009678829	0.0093993453	0.0002613424	0.0000181413
PHEV (Petrol) - Electricity consumption: ≥3000 cc	km	0.014986574	0.014553825	0.0004046592	0.0000280898
PHEV (Petrol) - Petrol consumption: 1350 - <1600 cc	km	0.0715429404	0.0685407316	0.0009113144	0.0020908945

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
PHEV (Petrol) – Petrol consumption: 1600 – <2000 cc	km	0.0805554927	0.0771750835	0.0010261163	0.0023542929
PHEV (Petrol) – Petrol consumption: 2000 – <3000 cc	km	0.089475132	0.0857204214	0.0011397347	0.0026149758
PHEV (Petrol) – Petrol consumption: <1350 cc	km	0.0691272048	0.0662263692	0.0008805427	0.0020202928
PHEV (Petrol) – Petrol consumption: ≥3000 cc	km	0.1070356719	0.1025440556	0.001363421	0.0031281953
Petrol hybrid vehicle: 1350 – <1600 cc	km	0.1367062556	0.1309695508	0.0017413651	0.0039953397
Petrol hybrid vehicle: 1600 – <2000 cc	km	0.153927693	0.1474683124	0.0019607318	0.0044986488
Petrol hybrid vehicle: 2000 – <3000 cc	km	0.1709715898	0.1637969837	0.0021778371	0.004996769
Petrol hybrid vehicle: <1350 cc	km	0.1320902002	0.1265472023	0.0016825657	0.0038604322
Petrol hybrid vehicle: ≥3000 cc	km	0.2045267616	0.1959440552	0.002605263	0.0059774433
Petrol vehicle: 1350 – <1600 cc	km	0.1731612571	0.1658947643	0.0022057291	0.0050607637
Petrol vehicle: 1600 – <2000 cc	km	0.1949750778	0.1867931957	0.0024835936	0.0056982884
Petrol vehicle: 2000 – <3000 cc	km	0.2165640137	0.2074761793	0.0027585936	0.0063292408
Petrol vehicle: <1350 cc	km	0.1673142536	0.1602931229	0.0021312499	0.0048898807
Petrol vehicle: ≥3000 cc	km	0.2590672313	0.2481958032	0.0032999999	0.0075714282

**Table 7.5: Vehicle fleet emissions per km travelled, 2015–2020**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>2015–2020 Fleet</b>					

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Diesel hybrid vehicle: 1350 – <1600 cc	km	0.1523914328	0.1500378702	0.0002249138	0.0021286488
Diesel hybrid vehicle: 1600 – <2000 cc	km	0.1615171678	0.1590226656	0.0002383825	0.0022561197
Diesel hybrid vehicle: 2000 – <3000 cc	km	0.1985654702	0.1954987869	0.0002930619	0.0027736214
Diesel hybrid vehicle: <1350 cc	km	0.1583593982	0.1559136652	0.0002337219	0.0022120111
Diesel hybrid vehicle: ≥3000 cc	km	0.2202623489	0.2168605748	0.0003250842	0.0030766899
Diesel vehicle: 1350 – <1600 cc	km	0.1717168568	0.1690648287	0.0002534361	0.002398592
Diesel vehicle: 1600 – <2000 cc	km	0.1819998662	0.1791890252	0.0002686128	0.0025422282
Diesel vehicle: 2000 – <3000 cc	km	0.2236339702	0.2201801242	0.0003300604	0.0031237857
Diesel vehicle: <1350 cc	km	0.178441646	0.1756857589	0.0002633612	0.0024925259
Diesel vehicle: ≥3000 cc	km	0.2480700371	0.2442387957	0.0003661255	0.0034651159
Electric vehicle: 1350 – <1600 cc	km	0.0201048461	0.019524303	0.00054286	0.0000376831
Electric vehicle: 1600 – <2000 cc	km	0.0226375345	0.021983858	0.0006112462	0.0000424302
Electric vehicle: 2000 – <3000 cc	km	0.0251441127	0.0244180569	0.0006789275	0.0000471283
Electric vehicle: <1350 cc	km	0.0194259811	0.0188650408	0.0005245296	0.0000364107
Electric vehicle: ≥3000 cc	km	0.0300789385	0.0292103858	0.0008121749	0.0000563778
Motorcycle: <60cc, electricity	km	0.0050919711	0.0049449365	0.0001374906	0.000009544
Motorcycle: <60cc, petrol	km	0.0557618645	0.0534218886	0.0007102949	0.001629681
Motorcycle: ≥ 60cc, electricity	km	0.0098108435	0.0095275477	0.000264907	0.0000183887
Motorcycle: ≥ 60cc, petrol	km	0.1074379479	0.1029294506	0.0013685452	0.0031399522

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
PHEV (Diesel) – Diesel consumption: 1350 – <1600 cc	km	0.0797515165	0.0785198188	0.0001177049	0.0011139929
PHEV (Diesel) – Diesel consumption: 1600 – <2000 cc	km	0.0845273178	0.0832218617	0.0001247535	0.0011807027
PHEV (Diesel) – Diesel consumption: 2000 – <3000 cc	km	0.1039159294	0.1023110318	0.0001533691	0.0014515286
PHEV (Diesel) – Diesel consumption: <1350 cc	km	0.0828747517	0.0815948181	0.0001223145	0.0011576191
PHEV (Diesel) – Diesel consumption: ≥3000 cc	km	0.1152706292	0.1134903675	0.0001701274	0.0016101344
PHEV (Diesel) – Electricity consumption: 1350 – <1600 cc	km	0.0097001765	0.0094200764	0.0002619188	0.0000181813
PHEV (Diesel) – Electricity consumption: 1600 – <2000 cc	km	0.0106283886	0.0103214856	0.0002869819	0.0000199211
PHEV (Diesel) – Electricity consumption: 2000 – <3000 cc	km	0.0120297921	0.0116824225	0.0003248218	0.0000225478
PHEV (Diesel) – Electricity consumption: <1350 cc	km	0.0100994396	0.0098078105	0.0002726995	0.0000189297
PHEV (Diesel) – Electricity consumption: ≥3000 cc	km	0.0142281038	0.0138172563	0.0003841794	0.0000266681
PHEV (Petrol) – Electricity consumption: 1350 – <1600 cc	km	0.00958331	0.0093065844	0.0002587633	0.0000179623
PHEV (Petrol) – Electricity consumption: 1600 – <2000 cc	km	0.0107905581	0.0104789723	0.0002913607	0.0000202251

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
PHEV (Petrol) – Electricity consumption: 2000 – <3000 cc	km	0.0119853604	0.0116392738	0.0003236221	0.0000224645
PHEV (Petrol) – Electricity consumption: <1350 cc	km	0.0092597177	0.0089923361	0.0002500258	0.0000173558
PHEV (Petrol) – Electricity consumption: ≥3000 cc	km	0.0143376274	0.0139236172	0.0003871367	0.0000268734
PHEV (Petrol) – Petrol consumption: 1350 – <1600 cc	km	0.0674743019	0.0646428283	0.000859488	0.0019719855
PHEV (Petrol) – Petrol consumption: 1600 – <2000 cc	km	0.0759743113	0.0727861456	0.0009677612	0.0022204045
PHEV (Petrol) – Petrol consumption: 2000 – <3000 cc	km	0.0843866918	0.0808455112	0.0010749182	0.0024662624
PHEV (Petrol) – Petrol consumption: <1350 cc	km	0.0651959488	0.0624600834	0.0008304664	0.001905399
PHEV (Petrol) – Petrol consumption: ≥3000 cc	km	0.1009485659	0.0967123873	0.0012858834	0.0029502953
Petrol hybrid vehicle: 1350 – <1600 cc	km	0.128931787	0.123521328	0.0016423338	0.0037681252
Petrol hybrid vehicle: 1600 – <2000 cc	km	0.1451738433	0.1390818069	0.0018492252	0.0042428111
Petrol hybrid vehicle: 2000 – <3000 cc	km	0.1612484557	0.1544818686	0.0020539837	0.0047126034
Petrol hybrid vehicle: <1350 cc	km	0.1245782462	0.1193504779	0.0015868784	0.0036408898
Petrol hybrid vehicle: ≥3000 cc	km	0.1928953489	0.18480074	0.002457102	0.0056375068
Petrol vehicle: 1350 – <1600 cc	km	0.1633135969	0.1564603487	0.0020802895	0.0047729586

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Petrol vehicle: 1600 – <2000 cc	km	0.1838868682	0.1761702888	0.002342352	0.0053742274
Petrol vehicle: 2000 – <3000 cc	km	0.2042480439	0.1956770336	0.0026017127	0.0059692976
Petrol vehicle: <1350 cc	km	0.1577991118	0.151177272	0.002010046	0.0046117938
Petrol vehicle: ≥3000 cc	km	0.2443341086	0.2340809374	0.0031123293	0.007140842

**Table 7.6: Post 2020 vehicle fleet emissions factors per km travelled**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Post 2020 Fleet</b>					
Diesel hybrid vehicle: 1350 – <1600 cc	km	0.1444720988	0.1422408439	0.0002132257	0.0020180292
Diesel hybrid vehicle: 1600 – <2000 cc	km	0.1531235962	0.1507587259	0.0002259944	0.0021388758
Diesel hybrid vehicle: 2000 – <3000 cc	km	0.1882466075	0.1853392907	0.0002778323	0.0026294845
Diesel hybrid vehicle: <1350 cc	km	0.1501299266	0.1478112911	0.0002215761	0.0020970594
Diesel hybrid vehicle: ≥3000 cc	km	0.2088159632	0.2055909693	0.0003081905	0.0029168034
Diesel vehicle: 1350 – <1600 cc	km	0.1642241802	0.1616878704	0.0002423777	0.0022939321
Diesel vehicle: 1600 – <2000 cc	km	0.1740585017	0.1713703087	0.0002568922	0.0024313008
Diesel vehicle: 2000 – <3000 cc	km	0.2138213793	0.2105190807	0.000315578	0.0029867205
Diesel vehicle: <1350 cc	km	0.1706555405	0.1680199035	0.0002518697	0.0023837673
Diesel vehicle: ≥3000 cc	km	0.2371852426	0.2335221081	0.0003500606	0.0033130739
Electric vehicle: 1350 – <1600 cc	km	0.0193672425	0.0188079983	0.0005229436	0.0000363006
Electric vehicle: 1600 – <2000 cc	km	0.021807012	0.0211773176	0.0005888209	0.0000408735
Electric vehicle: 2000 – <3000 cc	km	0.0242216293	0.0235222109	0.0006540191	0.0000453993

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Electric vehicle: <1350 cc	km	0.0187132837	0.0181729231	0.0005052858	0.0000350748
Electric vehicle: ≥3000 cc	km	0.028975407	0.0281387196	0.000782378	0.0000543094
Motorcycle: <60cc, electricity	km	0.0048625099	0.0047221012	0.0001312948	0.0000091139
Motorcycle: <60cc, petrol	km	0.0532490495	0.0510145206	0.0006782867	0.0015562422
Motorcycle: ≥ 60cc, electricity	km	0.0096935254	0.0094136173	0.0002617392	0.0000181689
Motorcycle: ≥ 60cc, petrol	km	0.1061532049	0.1016986202	0.0013521801	0.0031024046
PHEV (Diesel) - Diesel consumption: 1350 - <1600 cc	km	0.0756070651	0.074439375	0.0001115881	0.0010561019
PHEV (Diesel) - Diesel consumption: 1600 - <2000 cc	km	0.080134682	0.0788970666	0.0001182704	0.001119345
PHEV (Diesel) - Diesel consumption: 2000 - <3000 cc	km	0.0985157246	0.0969942288	0.0001453989	0.0013760969
PHEV (Diesel) - Diesel consumption: <1350 cc	km	0.0785679949	0.0773545757	0.0001159582	0.0010974611
PHEV (Diesel) - Diesel consumption: ≥3000 cc	km	0.1092803541	0.1075926073	0.0001612864	0.0015264604
PHEV (Diesel) - Electricity consumption: 1350 - <1600 cc	km	0.0093442979	0.0090744741	0.0002523096	0.0000175143
PHEV (Diesel) - Electricity consumption: 1600 - <2000 cc	km	0.0102384559	0.0099428125	0.0002764531	0.0000191902
PHEV (Diesel) - Electricity consumption: 2000 - <3000 cc	km	0.0115884449	0.0112538195	0.0003129048	0.0000217206

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
PHEV (Diesel) - Electricity consumption: <1350 cc	km	0.0097289129	0.009447983	0.0002626947	0.0000182352
PHEV (Diesel) - Electricity consumption: ≥3000 cc	km	0.0137061053	0.0133103308	0.0003700847	0.0000256897
PHEV (Petrol) - Electricity consumption: 1350 - <1600 cc	km	0.0092317189	0.0089651459	0.0002492698	0.0000173033
PHEV (Petrol) - Electricity consumption: 1600 - <2000 cc	km	0.0103946757	0.0100945214	0.0002806713	0.000019483
PHEV (Petrol) - Electricity consumption: 2000 - <3000 cc	km	0.0115456433	0.0112122539	0.0003117491	0.0000216403
PHEV (Petrol) - Electricity consumption: <1350 cc	km	0.0089199985	0.0086624267	0.0002408529	0.000016719
PHEV (Petrol) - Electricity consumption: ≥3000 cc	km	0.0138116107	0.0134127897	0.0003729335	0.0000258875
PHEV (Petrol) - Petrol consumption: 1350 - <1600 cc	km	0.0638126603	0.0611348429	0.000812846	0.0018649714
PHEV (Petrol) - Petrol consumption: 1600 - <2000 cc	km	0.0718513981	0.0688362452	0.0009152435	0.0020999094
PHEV (Petrol) - Petrol consumption: 2000 - <3000 cc	km	0.0798072622	0.0764582516	0.0010165854	0.0023324253
PHEV (Petrol) - Petrol consumption: <1350 cc	km	0.0616579471	0.0590705495	0.0007853993	0.0018019983
PHEV (Petrol) - Petrol consumption: ≥3000 cc	km	0.0954703697	0.0914640766	0.0012161021	0.002790191

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Petrol hybrid vehicle: 1350 – <1600 cc	km	0.1219350197	0.1168181711	0.001553209	0.0035636396
Petrol hybrid vehicle: 1600 – <2000 cc	km	0.137295665	0.1315342264	0.001748873	0.0040125657
Petrol hybrid vehicle: 2000 – <3000 cc	km	0.1524979532	0.1460985698	0.0019425198	0.0044568636
Petrol hybrid vehicle: <1350 cc	km	0.1178177333	0.1128736614	0.001500763	0.0034433089
Petrol hybrid vehicle: ≥3000 cc	km	0.1824274581	0.1747721209	0.002323762	0.0053315751
Petrol vehicle: 1350 – <1600 cc	km	0.154638797	0.1481495758	0.0019697899	0.0045194313
Petrol vehicle: 1600 – <2000 cc	km	0.1741192688	0.1668125744	0.0022179322	0.0050887623
Petrol vehicle: 2000 – <3000 cc	km	0.1933989111	0.1852831708	0.0024635164	0.0056522238
Petrol vehicle: <1350 cc	km	0.1494172272	0.1431471226	0.0019032775	0.0043668271
Petrol vehicle: ≥3000 cc	km	0.2313557067	0.2216471576	0.0029470103	0.0067615388

**Table 7.7: Default private car emission factors per km travelled for default age of vehicle and <3000 cc engine size**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Private car default</b>					
Diesel	km	0.265017934	0.2609249461	0.0003911388	0.0037018492
Diesel hybrid	km	0.237569648	0.2339005767	0.000350628	0.0033184434
Electric	km	0.0262821801	0.0255232617	0.0007096569	0.0000492614
PHEV (Diesel) – Diesel consumption	km	0.1101819647	0.1084802932	0.0001626171	0.0015390544
PHEV (Diesel) – Electricity consumption	km	0.012574282	0.0122111898	0.0003395238	0.0000235683
PHEV (Petrol) – Electricity consumption	km	0.0125278392	0.0121660881	0.0003382698	0.0000234813

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
PHEV (Petrol) – Petrol consumption	km	0.089475132	0.0857204214	0.0011397347	0.0026149758
Petrol	km	0.2443684485	0.2341138362	0.0031127667	0.0071418456
Petrol hybrid	km	0.1929224594	0.1848267128	0.0024574474	0.0056382992

**Note:** Defaults are based on the average age of the vehicle fleet (pre-2010 for petrol and diesel including hybrids, and 2010–2015 for all plug-in cars) and most common engine size (2000–3000 cc). Source: Te Manatū Waka Ministry of Transport

**Table 7.8: Default rental car emission factors per km travelled**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Rental car default</b>					
Diesel	km	0.1819998662	0.1791890252	0.0002686128	0.0025422282
Diesel hybrid	km	0.1615171678	0.1590226656	0.0002383825	0.0022561197
Electric	km	0.0226375345	0.021983858	0.0006112462	0.0000424302
PHEV (Diesel) – Diesel consumption	km	0.0845273178	0.0832218617	0.0001247535	0.0011807027
PHEV (Diesel) – Electricity consumption	km	0.0106283886	0.0103214856	0.0002869819	0.0000199211
PHEV (Petrol) – Electricity consumption	km	0.0107905581	0.0104789723	0.0002913607	0.0000202251
PHEV (Petrol) – Petrol consumption	km	0.0759743113	0.0727861456	0.0009677612	0.0022204045
Petrol	km	0.1838868682	0.1761702888	0.002342352	0.0053742274
Petrol hybrid	km	0.1451738433	0.1390818069	0.0018492252	0.0042428111

**Note:** Defaults assume a 2015–2020 fleet for rental cars and engine size of 1600 – <2000 cc.

We were unable to source more up-to-date data on the New Zealand taxi fleet to produce a representative vehicle type for the taxi (regular) factor. Therefore, this factor is derived from an average of the factors for a petrol, diesel, petrol plug-in hybrid and electric vehicle, for a 2010–2015 fleet and 2000–3000 cc vehicle class.

**Table 7.9: Emission factors for taxi travel**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Taxi Travel</b>					

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Electric	km	0.0262821801	0.0255232617	0.0007096569	0.0000492614
Electric – dollars spent	\$	0.0072602708	0.0070506248	0.0001960378	0.0000136081
Petrol hybrid	km	0.1709715898	0.1637969837	0.0021778371	0.004996769
Petrol hybrid – dollars spent	\$	0.0472297209	0.0452477855	0.0006016125	0.0013803229
Regular	km	0.1622627558	0.1570991692	0.0014983168	0.0036652697
Regular – dollars spent	\$	0.0448239657	0.0433975606	0.0004138997	0.0010125055

### 7.2.1. GHG inventory development

Entities should gather the activity data on passenger vehicle use with as much detail as possible, including age of the vehicle, engine size, fuel type and kilometres travelled. If information is not available, we provide conservative defaults to allow for overestimation rather than underestimation.

If fuel-use data are available, see [Section 3.3](#).

If fuel-use data are not available, collect data on kilometres travelled by vehicle type and multiply this by the emission factor based on distance travelled for each GHG. If the vehicle is electric and the charging point is within the entity's boundaries, this is a direct (Scope 1) emission source and emissions are zero. If travel is by rideshare apps (eg, Uber, YourRide, Waka Rider, Ola or Share Your Ride) we recommend using the taxi travel emission factors by distance travelled [Table 7.9](#). If this information is not available, use the taxi emission factors per dollars spent.

Because plug-in hybrids operate on both a fossil fuel and electricity, two separate emission factors should be applied, that for the fossil fuel (petrol or diesel) and that for electricity. The plug-in hybrid electric vehicle electricity factor includes both the electricity and the electricity transmission and distribution loss factor.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = distance travelled by vehicle type (km)
- F = emission factors for correlating vehicle type from [Table 3.3](#) and [Table 7.3](#) to [Table 7.9](#)

#### PASSENGER VEHICLES: EXAMPLE CALCULATION 1

An entity has 15 petrol vehicles. They use 40,000 litres of regular petrol in the reporting period.

##### Example calculation of standard private vehicle consumption

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	40,000 x 0.0303562842 kg CO <sub>2</sub> -e per litre	1,210 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	40,000 x 2.283122022 kg CO <sub>2</sub> -e per litre	91,300 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	40,000 x 0.0696486174 kg CO <sub>2</sub> -e per litre	2,790 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	40,000 x 2.383126924 kg CO <sub>2</sub> -e per litre	95,300 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

## PASSENGER VEHICLES: EXAMPLE CALCULATION 2

An entity owns three post-2020 petrol plug-in hybrid electric vehicles (PHEVs). They are all between 1600 and 2000 cc and travel a total of 37,800 km in the reporting period. We need to capture both the fossil fuel and electricity-based emissions.

For the petrol-based emissions, use the PHEV (Petrol) – Petrol consumption emission factor:

### Petrol component

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	37,800 x 0.0009152435 kg CO <sub>2</sub> -e per km	34.6 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	37,800 x 0.0688362452 kg CO <sub>2</sub> -e per km	2,600 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	37,800 x 0.0020999094 kg CO <sub>2</sub> -e per km	79.4 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	37,800 x 0.0718513981 kg CO <sub>2</sub> -e per km	2,720 kg CO <sub>2</sub> -e

Then also use the PHEV (Petrol) – Electricity consumption emission factor:

### Electricity component

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	37,800 x 0.0002806713 kg CO <sub>2</sub> -e per km	10.6 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	37,800 x 0.0100945214 kg CO <sub>2</sub> -e per km	382 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	37,800 x 0.000019483 kg CO <sub>2</sub> -e per km	0.736 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	37,800 x 0.0103946757 kg CO <sub>2</sub> -e per km	393 kg CO <sub>2</sub> -e

The sum of the above totals is the total emissions:

- 2,720 kg CO<sub>2</sub>-e + 393 kg CO<sub>2</sub>-e = 3,110 kg CO<sub>2</sub>-e

Note: Numbers may not add due to rounding.

## PASSENGER VEHICLES: EXAMPLE CALCULATION 3

An entity uses petrol rental cars to travel 12,000 km. It also spends \$18,000 on hybrid taxi travel.

- Total CO<sub>2</sub>-e emissions from rental cars = 12,000 km × 0.1838868682 = 2,210 kg CO<sub>2</sub>-e
- Total CO<sub>2</sub>-e emissions from hybrid taxi travel = \$18,000 × 0.0472297209 = 850 kg CO<sub>2</sub>-e

Note: Numbers may not add due to rounding.

## 7.2.2. Emission factor derivation methodology

The 2024 fleet statistics were taken from the Te Manatū Waka Ministry of Transport Vehicle Fleet Emissions Model. This provides energy (fuel and electricity) use per 100 km travelled by vehicle.

We split the fleet into four categories and develop average emission factors for these.

- The pre-2010 fleet is based on the average fuel consumption data from 1970 to 2010. We assume there are no electric vehicles or plug-in hybrid vehicles.
- The 2010–2015 fleet is based on the average fuel consumption data from vehicles produced between 2010 and 2015.
- The 2015–2020 fleet is based on the average fuel consumption data from vehicles produced between 2015 and 2020.
- The post-2020 fleet is based on the average fuel consumption data from vehicles produced from 2021 onwards.

Note that some guidance documents, such as those published by the UK Department for Energy Security and Net Zero (formerly published by the Department of Business, Energy and Industrial Strategy), apply an uplift factor to passenger vehicles. This accounts for the real-world effects on fuel consumption, such as the use of air conditioning, vehicle payload, gradient and weather. We do not apply an uplift factor here, because the Vehicle Fleet Emissions Model is based on real-world driving and fuel use.

For each category, default vehicles are based on the 2000–3000 cc engine size, as it is the most common size for light passenger vehicles in New Zealand based on [Motor Vehicle Register](#) open data.

**Table 7.10: Fuel consumption in litres per 100 km**

CC	Unit	Pre 2010 Fleet	2010-2015 Fleet	2015-2020 Fleet	Post 2020 Fleet
Diesel hybrid vehicle					
1350 - <1600 cc	Litres	6.801469	6.027592	5.684804	5.389381
1600 - <2000 cc	Litres	7.208765	6.388546	6.02523	5.712116
2000 - <3000 cc	Litres	8.862288	7.85393	7.407278	7.022344
<1350 cc	Litres	7.067828	6.263645	5.907433	5.600441
>=3000 cc	Litres	9.830654	8.712115	8.216658	7.789662
Diesel vehicle					
1350 - <1600 cc	Litres	7.587296	6.735136	6.405719	6.126212
1600 - <2000 cc	Litres	8.04165	7.138459	6.789316	6.493071
2000 - <3000 cc	Litres	9.886218	8.775131	8.342433	7.976384
<1350 cc	Litres	7.88443	6.998898	6.65658	6.366127
>=3000 cc	Litres	10.966467	9.733973	9.253995	8.847949
Electric vehicle					
1350 - <1600 cc	kWh	21.751352	19.313457	18.477148	17.799261
1600 - <2000 cc	kWh	24.491458	21.74645	20.804788	20.041506
2000 - <3000 cc	kWh	27.203315	24.154362	23.108433	22.260634
<1350 cc	kWh	21.016891	18.661314	17.853244	17.198247

Source: Te Manatū Waka Ministry of Transport Vehicle Fleet Emissions Model

CC	Unit	Pre 2010 Fleet	2010-2015 Fleet	2015-2020 Fleet	Post 2020 Fleet
>=3000 cc	kWh	32.542283	28.894938	27.643733	26.629544
Motorcycle					
<60cc, electricity	Litres	5.137236	4.588281	4.508276	4.454366
<60cc, petrol	Litres	2.780486	2.464686	2.339861	2.234419
>=60cc, electricity	Litres	10.274472	9.176562	9.016553	8.908733
>=60cc, petrol	Litres	5.560973	4.929373	4.679723	4.468839
PHEV (Diesel) - Diesel consumption					
1350 - <1600 cc	Litres	3.559435	3.15444	2.975047	2.820443
1600 - <2000 cc	Litres	3.772587	3.343339	3.153204	2.989341
2000 - <3000 cc	Litres	4.637931	4.110224	3.876476	3.675027
<1350 cc	Litres	3.69883	3.277974	3.091556	2.930897
>=3000 cc	Litres	5.144709	4.55934	4.300051	4.07659
PHEV (Diesel) - Electricity consumption					
1350 - <1600 cc	kWh	10.494582	9.318347	8.914845	8.587779
1600 - <2000 cc	kWh	11.498811	10.210022	9.767909	9.409545
2000 - <3000 cc	kWh	13.014984	11.556262	11.055854	10.650239
<1350 cc	kWh	10.926543	9.701894	9.281784	8.941255
>=3000 cc	kWh	15.393328	13.668041	13.07619	12.596452
PHEV (Petrol) - Electricity consumption					
1350 - <1600 cc	kWh	10.368145	9.206081	8.80744	8.484314
1600 - <2000 cc	kWh	11.674262	10.365808	9.916949	9.553118
2000 - <3000 cc	kWh	12.966913	11.513579	11.01502	10.610902
<1350 cc	kWh	10.018051	8.895226	8.510046	8.197831
>=3000 cc	kWh	15.511822	13.773254	13.176846	12.693416
PHEV (Petrol) - Petrol consumption					
1350 - <1600 cc	Litres	3.387493	3.002062	2.831335	2.677686
1600 - <2000 cc	Litres	3.81423	3.380243	3.188009	3.015005
2000 - <3000 cc	Litres	4.236566	3.754527	3.541007	3.348846
<1350 cc	Litres	3.27311	2.900693	2.735731	2.587271
>=3000 cc	Litres	5.068042	4.491396	4.235971	4.006097
Petrol hybrid vehicle					

Source: Te Manatū Waka Ministry of Transport Vehicle Fleet Emissions Model

CC	Unit	Pre 2010 Fleet	2010-2015 Fleet	2015-2020 Fleet	Post 2020 Fleet
1350 - <1600 cc	Litres	6.472917	5.736424	5.410194	5.116598
1600 - <2000 cc	Litres	7.288337	6.459064	6.091738	5.761156
2000 - <3000 cc	Litres	8.09535	7.174254	6.766255	6.39907
<1350 cc	Litres	6.254351	5.542726	5.227512	4.94383
>=3000 cc	Litres	9.684157	8.582286	8.094212	7.654962
Petrol vehicle					
1350 - <1600 cc	Litres	8.199029	7.266137	6.852912	6.488903
1600 - <2000 cc	Litres	9.231893	8.181481	7.716201	7.306336
2000 - <3000 cc	Litres	10.25411	9.087389	8.57059	8.115342
<1350 cc	Litres	7.922178	7.020787	6.621515	6.269797
>=3000 cc	Litres	12.266598	10.870895	10.252669	9.708073

Source: Te Manatū Waka Ministry of Transport Vehicle Fleet Emissions Model

Vehicle emissions per kilometre are calculated by combining real-world fuel consumption with fuel-specific emission factors expressed in carbon dioxide equivalent (CO<sub>2</sub>-e):

$$\text{emissions per km (kg CO}_2\text{-e km}^{-1}\text{)} = \frac{\text{fuel consumption (L per 100 km)} \times \text{fuel emission factor (kg CO}_2\text{-e L}^{-1}\text{)}}{100}$$

Dividing by 100 gives a factor for litres (or kWh) per fuel per km. Use this with the fuel emission factors to calculate emissions per km.

Multiply the values for fuel consumption by the emission conversion factors in [Table 3.3](#).

New Zealand Transport Agency vehicle registration data is unchanged from the 2022 guidance, where the average year of manufacture for the taxi fleet was 2012, and 2015 for the rental fleet<sup>17</sup>. We assumed a 2010–2015 fleet for taxis and post-2015 fleet for rental cars.

The taxi (regular) factor is derived from an average of the factors for a petrol, diesel, petrol plug-in hybrid and electric vehicle, for a 2000–3000 cc vehicle class. These workings are in [Table 7.11](#).

**Table 7.11: Data used for calculating the taxi (regular) emission factor**

Vehicle	CC	Unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Total kg CO <sub>2</sub> -e/unit
Electric	2000 - <3000 cc	km	0.025523	0.00071	0.000049	0.026282
Diesel	2000 - <3000 cc	km	0.2316	0.000347	0.003286	0.235233
Petrol	2000 - <3000 cc	km	0.207476	0.002759	0.006329	0.216564

Vehicle	CC	Unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Total kg CO <sub>2</sub> -e/unit
Petrol hybrid	2000 - <3000 cc	km	0.163797	0.002178	0.004997	0.170972
Taxi (regular)	Average	km	0.157099	0.001498	0.003665	0.162263

TaxiCharge NZ Ltd advised that the current average price per kilometre in a taxi is \$3.62. North Island's average rate = \$3.4, while South Island's average = \$3.99.

The calculation to develop the emission factors for taxi based by \$ spend is:

$$\text{emissions per \$ spend} = \frac{\text{emissions per km}}{\text{average price per km}}$$

The private car default is based on the average age of light passenger vehicles in the New Zealand fleet, back-calculated to the year of manufacture, with the fuel consumption factors in Table 7.12 applied.

According to Te Manatū Waka Ministry of Transport's *The New Zealand 2024 Vehicle Fleet: Data Spreadsheet*<sup>18</sup>, the average age of light passenger vehicles in 2024 was 15.2 years. This corresponds to a 2009 year of manufacture.

**Table 7.12: Energy consumption per 100 km for average light passenger vehicles**

Engine type	Unit	Units per 100 km for a 2000–3000 cc engine
Petrol	Litres	10.25411
Diesel	Litres	9.886218
Petrol hybrid	Litres	6.766255
Diesel hybrid	Litres	7.407278
PHEV (Petrol) - Petrol consumption	Litres	3.541007
PHEV (Petrol) - Electricity consumption	kWh	11.01502
PHEV (Diesel) - Diesel consumption	Litres	3.876476
PHEV (Diesel) - Electricity consumption	kWh	11.055854
Electric	kWh	23.108433

The default emission factor for rental cars is the same as for vehicles in the post-2015 1600–2000 cc category.

### 7.2.3. Assumptions, limitations and uncertainties

Emission factors from fuel are multiplied by real-world consumption rates for vehicles with different engine sizes. The uncertainties embodied in these figures carry through to the emission factors. For petrol vehicles,

we multiplied the real-world consumption by 'regular petrol' emission factors from the fuel emission source category. This may overestimate emissions for some and underestimate emissions for others.

According to Te Manatū Waka Ministry of Transport's The New Zealand 2024 Vehicle Fleet: Data Spreadsheet, the most common size of light passenger vehicle is between 2000 cc and 3000 cc. Therefore, the default emission factors (for vehicles of unknown engine size) are the same as for a <3000 cc vehicle.

The Vehicle Fleet Emissions Model contains uncertainties about the fuel consumption figures provided. Emission factors represent the average fuel consumption of vehicles operating in the real world under different driving conditions, across all vehicle types in that classification.

We assume there are no electric cars or hybrids in the pre-2010 fleet.

### 7.3. Public transport passenger travel

The emission factors for public transport for passenger travel on buses, trains and a ferry were provided by Auckland Transport. The unit used for these emission sources are passenger kilometres (pkm).

The national average for the bus factor is unchanged from the previous edition.

**Table 7.13: Emission factors for public transport**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Bus</b>						
Average Bus	pkm	0.1545879756	0.1521743592	0.0002806001	0.0021330164	Unknown
Diesel Bus	pkm	0.1700575897	0.1674311876	0.0002509872	0.0023754149	Unknown
Electric Bus	pkm	0.020624096	0.0200535933	0.00053611	0.0000343928	Unknown
Hydrogen Bus	pkm	0.0371185712	0.0361255988	0.0009278171	0.0000651553	Unknown
National Average for Bus	pkm	0.155	0.153	0.000125	0.002125	Unknown
<b>Ferry</b>						
Ferry Average	pkm	0.3462605439	0.3409128294	0.0005110444	0.0048366701	Unknown
<b>Rail</b>						
Metropolitan Average	pkm	0.0268170819	0.0261757766	0.0005104428	0.0001308624	Unknown
Metropolitan Diesel	pkm	0.274856378	0.2706114432	0.0004056593	0.0038392755	Unknown
Metropolitan Electric	pkm	0.0202225932	0.0196770957	0.0005132286	0.0000322688	Unknown

### 7.3.1. GHG inventory development

To calculate public transport passenger emissions, collect data on the type of transport and distance travelled, and multiply this by the emission factors for each gas. Entities could conduct a staff travel survey to quantify these emissions.<sup>19</sup>

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = distance travelled, by vehicle type (km)
- F = emission factors for correlating vehicle type, from Table 7.13.

#### PASSENGER BUS: EXAMPLE CALCULATION

An employee takes a return trip on an electric Wellington bus from the CBD to the airport (9.4 km each way). This happens five times in the reporting year.

Passenger kilometres travelled = 2 trips × 9.4 km × 5 times = 94 pkm

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	94 × 0.00053611 kg CO <sub>2</sub> -e per pkm	0.0504 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	94 × 0.0200535933 kg CO <sub>2</sub> -e per pkm	1.89 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	94 × 0.0000343928 kg CO <sub>2</sub> -e per pkm	0.00323 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	94 × 0.020624096 kg CO <sub>2</sub> -e per pkm	1.94 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 7.3.2. Emission factor derivation methodology

#### 7.3.2.1. National average bus

To calculate the emission factor for national average bus travel we used the New Zealand Transport Agency passenger travel data Table 7.14 to estimate the national average loading capacity of seven people per bus.

Table 7.14: National bus passenger kilometres in 2020/21

Region	Mode	Breakdown	2020/21
New Zealand	Bus	pkm	534,976,704
New Zealand	Bus	Service km	122,934,050

The passenger loading per bus for the different regions for 2020/21 is shown in Table 7.15.

Table 7.15: National bus passenger loading by region

Region	Unit	End Use
National average	Passenger/bus	7

Region	Unit	End Use
Auckland	Passenger/bus	7
Bay of Plenty	Passenger/bus	3
Canterbury	Passenger/bus	Missing data
Gisborne	Passenger/bus	8
Hawkes Bay	Passenger/bus	1
Manawatū-Whanganui	Passenger/bus	5
Marlborough-Nelson-Tasman	Passenger/bus	6
Northland	Passenger/bus	8
Otago	Passenger/bus	Missing data
Southland	Passenger/bus	3
Taranaki	Passenger/bus	12
Waikato	Passenger/bus	4
Wellington	Passenger/bus	20

We then divided the per kilometre emission factor for diesel buses in [Table 7.14](#) by the national passenger/bus loading rate to give the emissions per gas, see [Table 7.22](#).

**Table 7.16: Emission factor for national average bus**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Public Transport Vehicle</b>					
Diesel bus: ≥ 12000 kg	km	1.081684768	1.06497902	0.0015964537	0.0151092939

### 7.3.2.2. Auckland buses

To calculate the emissions from Auckland buses we used the most recent data available, which were from the year 2024. This information was from Auckland Transport.

Data for the electric and hydrogen buses are in [Table 7.17](#). The distance travelled by electric and hydrogen buses for each 2023 quarter was multiplied by an estimated average bus power rating of 1.08 kWh and 5.76 kWh per kilometre respectively.<sup>20</sup> The resultant energy consumption was multiplied by its respective quarterly electricity emission factor (including the transmission and distribution loss factor of electricity) to produce quarterly emissions totals. These totals were then divided by the quarterly totals for passenger kilometres travelled. The final emission factor is weighted based on the quarterly emissions totals and quarterly passenger kilometres travelled.

**Table 7.17: Auckland Transport 2023 data for electric and hydrogen buses**

Bus type	2023/24 Quarter	Distance (km)	Fuel consumption rate (kWh/km)	Electricity consumption	pkm
Electric	Q1	1,816,925.055	1.083652	1,968,915.085638	8,769,389.589
Electric	Q2	2,214,166.563	1.083652	2,399,386.774931	12,071,135.61
Electric	Q3	2,011,190.4	1.083652	2,179,431.181134	13,121,883.46
Electric	Q4	2,152,556.505	1.083652	2,332,622.891473	12,454,403.58
Hydrogen	Q1	1,089.389	5.761427	6,276.434671	20,565.56657
Hydrogen	Q2	1,226.141	5.761427	7,064.32127	20,056.62695
Hydrogen	Q3	1,507.266	5.761427	8,684.002299	27,451.51811
Hydrogen	Q4	2,045.531	5.761427	11,785.176543	34,286.74539

Data for the diesel buses are in Table 7.18. The annual distance travelled was multiplied by an estimated fuel efficiency of 0.457 litres per kilometre travelled.<sup>21</sup>The resultant energy consumption was multiplied by the diesel emission factor, to produce an annual emissions total. This total was then divided by the annual passenger kilometres travelled, to produce the final emission factor.

**Table 7.18: Auckland Transport 2023 data for diesel buses**

Distance (km)	Fuel consumption rate (l/km)	Fuel consumption (litres)	pkm
55,858,421.04	0.457388	25,548,975.392733	402,737,937

### 7.3.2.3. Auckland trains

To calculate the emissions from Auckland trains we used the most recent data available, which were from the year 2023/24 for electric trains. Diesel trains stopped operating in the region in August 2022. This information was from Auckland Transport.

Data for the electric and diesel trains are in Table 7.19. The diesel fuel used by diesel trains was multiplied by the diesel emission factor in Table 3.3 to produce an annual emissions total. This total was then divided by the annual passenger kilometres travelled, to produce the final emission factor.

The electricity used by electric trains for each year quarter, was multiplied by the respective quarterly electricity emission factors (including the transmission and distribution loss factor of electricity) to produce quarterly emissions totals. These totals were then divided by the quarterly totals for passenger kilometres travelled. The final emission factor is weighted based on the quarterly emissions totals and quarterly passenger kilometres travelled.

The diesel fuel used by diesel trains was multiplied by the diesel emission factor (in Table 3.3) to produce an annual emissions total. This total was then divided by the annual passenger kilometres travelled, to produce the final emission factor.

**Table 7.19: Auckland train data**

Train type	Quarter/Year	Unit	Fuel consumption per unit	pkm
Electric	Sep-23	kWh	8,271,508	39,934,857

Train type	Quarter/Year	Unit	Fuel consumption per unit	pkm
Electric	Dec-23	kWh	7,447,841	38,607,309
Electric	Mar-24	kWh	7,598,900	40,232,907
Electric	Jun-24	kWh	7,717,790	44,101,512
Diesel	2021/22	Litres	443,997	4,330,313

The train average factor is weighted based on the emission factors for electric and diesel trains and the respective passenger kilometres travelled.

### 7.3.3. Auckland ferry

To calculate the emissions from ferry travel we used the most recent data available, which were from 2024. This information was from Auckland Transport and covers the 30 ferries operating in the Auckland region.

The annual distance travelled by diesel ferries over the 4 quarters was multiplied by an estimated average fuel consumption rate of 4.84 l/km to estimate the diesel used by public transport ferries in Auckland region.<sup>22</sup> The diesel used was then multiplied by the diesel emission factor (in Table 3.3) to produce an annual emissions total. This total was then divided by the annual passenger kilometres travelled, to produce the final emission factor.

Table 7.20: Ferry data

Distance	Fuel consumption (litres)	pkm
1,462,099	8,930,329	69,136,84

### 7.3.4. Assumptions, limitations and uncertainties

Limited data are available for areas outside the Auckland region.

These metro commuter rail emission factors are assumed to be appropriate for use on any commuter rail line in New Zealand.

## 7.4. Public transport vehicles

Public transport vehicle emissions include those from buses. Emissions are calculated for the whole vehicle. This approach is appropriate for transport operators or if a bus is chartered. Table 7.21 details these emission factors.

Buses: We calculated the emissions of different buses using Te Manatū Waka Ministry of Transport Vehicle Fleet Emissions Model data for fuel consumption in litres per 100 kilometres. The guide presents the data in emissions per kilometre.

The change in all-electric and PHEV vehicle emission factors is driven by the increase in the latest annual electricity factor, which is used to derive these emissions factors.

Table 7.21 details the data provided to calculate the emission conversion factors.

**Table 7.21: Bus emission factors per km travelled**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Public Transport Vehicle</b>					
Diesel bus: 7500 – 12000 kg	km	0.7804570209	0.7684034925	0.001151873	0.0109016554
Diesel bus: < 7500 kg	km	0.5634573521	0.5547552084	0.0008316042	0.0078705396
Diesel bus: ≥ 12000 kg	km	1.081684768	1.06497902	0.0015964537	0.0151092939
Diesel hybrid bus: 7500 – 12000 kg	km	0.5522890998	0.5437594407	0.000815121	0.0077145381
Diesel hybrid bus: < 7500 kg	km	0.3987296488	0.3925715914	0.0005884833	0.0055695741
Diesel hybrid bus: ≥ 12000 kg	km	0.7654524092	0.7536306149	0.0011297278	0.0106920665
Electric bus: 7500 – 12000 kg	km	0.0869461467	0.0844355091	0.0023476719	0.0001629657
Electric bus: < 7500 kg	km	0.0627714842	0.0609589088	0.001694921	0.0001176544
Electric bus: ≥ 12000 kg	km	0.1205041662	0.1170245147	0.0032537871	0.0002258644

### 7.4.1. GHG inventory development

To calculate public transport emissions, collect data on the type of transport and distance travelled, and multiply this by the emission factors for each gas.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = distance travelled, by vehicle type (km)
- F = emission factors for correlating vehicle type, from [Table 7.21](#).

#### DIESEL BUS: EXAMPLE CALCULATION

An entity charters a diesel bus (<7,500 kg) to travel 500 km. The emissions would be:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	500 x 0.0008316042 kg CO <sub>2</sub> -e per km	0.416 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	500 x 0.5547552084 kg CO <sub>2</sub> -e per km	277 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	500 x 0.0078705396 kg CO <sub>2</sub> -e per km	3.94 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	500 x 0.5634573521 kg CO <sub>2</sub> -e per km	282 kg CO <sub>2</sub> -e

This result is for the entire bus.

Note: Numbers may not add due to rounding.

## 7.4.2. Emission factor derivation methodology

The average age of the bus fleet is 16.4 years (according to Te Manatū Waka Ministry of Transport fleet statistics). Therefore, we applied an average fuel consumption factor for a pre-2010 fleet to the bus fleet from the Vehicle Fleet Emissions Model.

**Table 7.22: Fuel/energy consumption per 100 km for pre-2010 fleet buses**

Emission source	Weight class	Unit	Pre-2010 units of energy per 100 km
Diesel bus	<7500 kg	Litre	21.01919
	7500 - 12000 kg	Litre	29.114137
	>=12000 kg	Litre	40.351124
Diesel hybrid bus	<7500 kg	Litre	14.874195
	7500 - 12000 kg	Litre	20.60257
	>=12000 kg	Litre	28.554405
Electric bus	<7500 kg	kWh	57.689474
	7500 - 12000 kg	kWh	79.906944
	>=12000 kg	kWh	110.748089

Using the information in [Table 7.22](#) and appropriate emission factor, the equation is:

$$\text{Emissions per km (kg CO}_2\text{-e km}^{-1}\text{)} = \frac{\text{Energy use (unit per 100 km)} \times \text{Emission factor (kg CO}_2\text{-e unit}^{-1}\text{)}}{100}$$

Where:

- fuel/energy consumption = units of energy per 100 km travelled (L for diesel/hybrid and kWh for electric)
- emission factor = the emission factor from [Table 3.3](#) or [Table 5.2](#)

This allows you to use distance travelled as a unit for calculating emissions. If there are data on the quantity of fuel used, refer to transport fuel emission factors.

### 7.4.3. Assumptions, limitations and uncertainties

The Vehicle Fleet Emissions Model historical year results have been carefully calibrated to give a total road fuel use that matches MBIE’s road fuel sales figures. The sources used to develop these emission factors will have inbuilt assumptions, limitations and uncertainties. To investigate these, see the documents referenced.

## 7.5. Air travel

This section covers emission factors for domestic and international air travel for entities seeking to determine the emissions from business travel.

### 7.5.1. Domestic air travel

This section provides emission factors based on data from 2023. Domestic air travel is a common source of indirect (Scope 3) emissions for many New Zealand entities.

For air travel emission factors, multipliers or other corrections may be applied to account for the radiative forcing of emissions arising from aircraft transport at high altitude (jet aircraft). Radiative forcing helps entities account for the wider climate effects of aviation, including water vapour and indirect GHGs. This is an area of active research and uncertainty, aiming to express the relationship between emissions and the climate warming effects of aviation, but there is yet to be consensus on this aspect.

In this guidance, emission factors with a radiative forcing multiplier refers to the indirect climate change effects (non-CO<sub>2</sub> emissions eg, water vapour, contrails, NO<sub>x</sub>). Emission factors without a radiative forcing multiplier refers to the direct climate change effects (CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O). If multipliers are applied, entities should disclose the specific factor used including its source and produce comparable reporting. Therefore, avoid reporting with air travel conversion factors in one year and without in another year, as this may skew the interpretation of your reporting.

The decision to apply the Radiative Forcing Index, and to what type of air travel (flight altitude) should be guided by the requirements of your intended use and users.

In terms of the small and medium aircraft, a radiative forcing multiplier may not be required given the lower altitude at which these aircrafts typically fly. However, these emission factors are provided in the tables below for completeness, and for users wanting to take a conservative approach to their reporting.

Table 7.23 provides the emission factors without the radiative forcing multiplier applied. Table 7.24 provides emission factors with a radiative forcing multiplier of 1.7 applied.

**Table 7.23: Domestic air travel emission factors without a radiative forcing multiplier**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Without Radiative Forcing factors</b>					
Large aircraft	pkm	0.1042303604	0.1034434268	0.000020252	0.0007666817
Medium aircraft	pkm	0.1198521492	0.1189472719	0.0000232873	0.00088159
National average	pkm	0.1146405571	0.1137750271	0.0000222747	0.0008432554

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Small aircraft	pkm	0.3524624434	0.3405366516	0.0028841629	0.009041629

**Table 7.24: Domestic air travel emission factors with a radiative forcing multiplier**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>With Radiative Forcing factors</b>					
Large aircraft	pkm	0.1766407592	0.1758538256	0.000020252	0.0007666817
Medium aircraft	pkm	0.2031152396	0.2022103623	0.0000232873	0.00088159
National average	pkm	0.1942830761	0.193417546	0.0000222747	0.0008432554
Small aircraft	pkm	0.5908380995	0.5789123077	0.0028841629	0.009041629

We have provided a national average emission factor, and three factors based on the aircraft size: large, medium or small aircraft. A large aircraft in New Zealand would be an Airbus A320neo, A320ceo and A321neo. A medium aircraft has between 50 and 70 seats (ie, regional services on an ATR 72 or de Havilland Q300) and a small aircraft has fewer than 50 seats. If the aircraft type is unknown, we recommend using the national average.

### 7.5.1.1. GHG inventory development

To calculate emissions for domestic air travel, collect information on passengers flying, their departure and destination airports, flight length, travel class and, if practical, the type of aircraft. Your travel provider may be able to provide this information.

If the type of aircraft is unknown, use the national average emission factors. Calculate distances using online calculators such as [www.airmilescalculator.com](http://www.airmilescalculator.com). Multiply the number of passengers by the distance travelled to obtain the pkm.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = passengers multiplied by distance flown (pkm)
- F = emission factors from [Table 7.23](#) to [Table 7.24](#)

#### DOMESTIC AIR TRAVEL: EXAMPLE CALCULATION

An entity flies an employee on a return flight from Christchurch to Wellington (304 km each way). This happens five times in the reporting year on an aircraft of unknown size. The national average emission factor with radiative forcing is used.

Passenger kilometres travelled =  $(2 \times 304) \times 5 = 3,040$  pkm

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	$3,040 \times 0.0000222747$ kg CO <sub>2</sub> -e per pkm	0.0677 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	$3,040 \times 0.193417546$ kg CO <sub>2</sub> -e per pkm	588 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	$3,040 \times 0.0008432554$ kg CO <sub>2</sub> -e per pkm	2.56 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	$3,040 \times 0.1942830761$ kg CO <sub>2</sub> -e per pkm	591 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 7.5.1.2. Emission factor derivation methodology

We developed emission factors for aircraft type with data from various data sources. We calculated an average emission factor for domestic air travel using data from the 2016, 2020 and 2023 calendar years.

An average emission factor has also been provided where the aircraft type is unknown (see [Table 7.23](#) and [Table 7.24](#)). Entities that own aircraft could calculate emissions based on the fuel consumption data.

To calculate the emission factor, first calculate average fuel (kg) per flight for each aircraft:

$$\frac{\text{average total fuel used (kg)}}{\text{average number of flights}}$$

Then calculate average fuel (kg) per passenger:

$$\frac{\text{average total fuel (kg) per flight}}{\text{average number of seats} \times 0.8}$$

Using this, next calculate fuel per passenger per km:

$$\frac{\text{average fuel (kg) per passenger}}{\text{average flight distance (km)}}$$

The density of kerosene (the assumed aviation fuel) is 0.79 kg/l.<sup>23</sup>

Emission factors for each aircraft were determined by multiplying the fuel (litres) per passenger per kilometre by the kerosene (aviation fuel) emission factor in [Table 3.3](#)

**Table 7.25: Calculated emissions, without the radiative forcing multiplier, per aircraft type**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Without radiative forcing factors</b>						
Aerospatiale/ Alenia ATR 72	pkm	0.1135302273	0.1126730802	0.0000220589	0.0008350882	
Airbus A320	pkm	0.1105000756	0.109665806	0.0000214702	0.0008127995	
Beechcraft Beech 1900D	pkm	0.1790597259	0.1777078345	0.0000347913	0.0013171	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
British Aerospace Jetstream 32	pkm	0.2277260737	0.2260067541	0.0000442472	0.0016750724	
Cessna Light Aircraft	pkm	0.5298459145	0.5258456063	0.0001029491	0.0038973591	
De Havilland Canada DHC-8-300 Dash 8/8Q	pkm	0.2200666746	0.218405183	0.000042759	0.0016187326	
FOKKER F50	pkm	0.0870854283	0.086427938	0.0000169207	0.0006405696	
Pilatus PC-12	pkm	0.1806018705	0.1792383361	0.000035091	0.0013284435	
Saab SF-340	pkm	0.0930101527	0.092307931	0.0000180719	0.0006841498	

**Note:** 2016 or 2020 data unless denoted otherwise. Airbus A320, Aerospatiale/Alenia ATR 72, De Havilland Q300 updated using 2023 data.

**Table 7.26: Calculated emissions, with the radiative forcing multiplier, per aircraft type**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>With radiative forcing factors</b>						
Aerospatiale/Alenia ATR 72	pkm	0.1924013834	0.1915442363	0.0000220589	0.0008350882	
Airbus A320	pkm	0.1872661398	0.1864318702	0.0000214702	0.0008127995	
Beechcraft Beech 1900D	pkm	0.30345521	0.3021033187	0.0000347913	0.0013171	
British Aerospace Jetstream 32	pkm	0.3859308016	0.384211482	0.0000442472	0.0016750724	
Cessna Light Aircraft	pkm	0.8979378389	0.8939375307	0.0001029491	0.0038973591	
De Havilland Canada DHC-8-300 Dash 8/8Q	pkm	0.3729503027	0.3712888111	0.000042759	0.0016187326	
FOKKER F50	pkm	0.147584985	0.1469274947	0.0000169207	0.0006405696	
Pilatus PC-12	pkm	0.3060687057	0.3047051713	0.000035091	0.0013284435	
Saab SF-340	pkm	0.1576257044	0.1569234827	0.0000180719	0.0006841498	

**Note:** 2016 or 2020 data unless denoted otherwise. Airbus A320, Aerospatiale/Alenia ATR 72 using 2023 data.

For situations where the aircraft type is unknown, average emission factors are also provided for a domestic average, and for large, medium and small aircraft (see [Table 7.23](#) and [Table 7.24](#)).

We then calculated a weighted average emission factor for each size category, using the aircraft types within that size range. The weighted averages are calculated using the annual flight domestic distance travelled and the total number of domestic flights for each aircraft type. This method applies an equal weighting of 50 per cent to both distance travelled and number of flights.

- Large aircraft: A320neo, A320ceo and A321neo
- Medium aircraft: ATR 72 and Q300
- Small aircraft: British Aerospace Jetstream 32, Cessna Light Aircraft.

A national average emission factor was calculated using the same weighted average approach described above, this time considering the contribution each of the five large and medium aircraft types make to the overall distance travelled and number of flights.

### 7.5.1.3. Assumptions, limitations and uncertainties

We assume the fuel for domestic flights is kerosene (aviation fuel) and all the kerosene is combusted. The domestic emission factors are based on fuel delivery data. Therefore, it is not necessary to apply a distance uplift factor to account for delays/circling and non-direct routes (ie, not along the straight-line/great-circle between destinations). However, this should be considered for international air travel.

## 7.5.2. International air travel

The International air travel emission factors are sourced from the *UK Greenhouse Gas Reporting: Conversion Factors 2022*, published by the UK Department for Energy Security and Net Zero (DESNZ). These factors have remained unchanged in the 2023 and 2024 DESNZ editions, meaning they still reflect air travel data influenced by the COVID-19 pandemic. As a result, we continue to use the 2022 edition factors, which are based on pre-COVID air travel data which provides a more representative period for emissions reporting.

Because the DESNZ 2022 emission factors were developed using the GWP values from the AR4, the factors presented here have been converted to AR5 GWP values.

Entities wishing to report their international air travel emissions based on distance travelled per passenger could use the [International Civil Aviation Organisation \(ICAO\) calculator](#). This calculator considers aircraft types and load factors for specific airline routes but does not apply the radiative forcing multiplier (accounting for the wider climate effect of emissions arising from aircraft transport at altitude) or distance uplift factor to account for delays/circling and non-direct routes (ie, not along the straight-line/great-circle between destinations). If using the [ICAO calculator](#) to calculate emissions for international air travel, multiply the output by 1.08 to account for the 8 per cent distance uplift factor (see [Section 7.5.2.3](#)) and then by 1.7 to apply a radiative forcing multiplier.

If you prefer not to use the ICAO calculator, we recommend the emission factors in [Table 7.27](#) and [Table 7.28](#). These emission factors follow those published online by the [UK Department of Business, Energy and Industrial Strategy conversion factors](#) (Conversion factors 2022: condensed set (for most users)) and include a distance uplift of 8 per cent and a radiative forcing multiplier of 1.7.

**Table 7.27: Emission factors for international air travel without radiative forcing multiplier**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Without Radiative Forcing</b>					

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Long-haul (>3700km): Average passenger	pkm	0.1019748913	0.10111	0.0000112	0.0008536913
Long-haul (>3700km): Business class	pkm	0.2264776349	0.22457	0.0000224	0.0018852349
Long-haul (>3700km): Economy class	pkm	0.0781003611	0.07744	0.0000112	0.0006491611
Long-haul (>3700km): First class	pkm	0.3123779369	0.30975	0.0000224	0.0026055369
Long-haul (>3700km): Premium economy class	pkm	0.1249516362	0.1239	0.0000112	0.0010404362
Short-haul (<3700km): Average passenger	pkm	0.0810870389	0.0804	0.0000112	0.0006758389
Short-haul (<3700km): Business class	pkm	0.1196371732	0.11863	0.0000112	0.0009959732
Short-haul (<3700km): Economy class	pkm	0.0797581463	0.07908	0.0000112	0.0006669463

**Table 7.28: Emission factors for international air travel with radiative forcing multiplier**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>With Radiative Forcing</b>					
Long-haul (>3700km): Average passenger	pkm	0.1929848913	0.19212	0.0000112	0.0008536913
Long-haul (>3700km): Business class	pkm	0.4285876349	0.42668	0.0000224	0.0018852349
Long-haul (>3700km): Economy class	pkm	0.1477903611	0.14713	0.0000112	0.0006491611
Long-haul (>3700km): First class	pkm	0.5911479369	0.58852	0.0000224	0.0026055369

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Long-haul (>3700km): Premium economy class	pkm	0.2364616362	0.23541	0.0000112	0.0010404362
Short-haul (<3700km): Average passenger	pkm	0.1534470389	0.15276	0.0000112	0.0006758389
Short-haul (<3700km): Business class	pkm	0.2263971732	0.22539	0.0000112	0.0009959732
Short-haul (<3700km): Economy class	pkm	0.1509381463	0.15026	0.0000112	0.0006669463

The emission factors from the UK DESNZ are calculated regarding the indirect and direct climate change effects. For continuity in this guidance, we have categorised the international air travel emission factors by whether a radiative forcing multiplier was applied, as outlined in this section. Further information can be found in paragraphs 8.37 to 8.41 in the [2023 UK DESNZ Methodology Paper for Conversion Factors](#).

### 7.5.2.1. GHG inventory development

To calculate emissions for international air travel, collect information on passengers flying, their departure and destination airports, flight length, travel class and, if practical, the type of aircraft. Your travel provider may be able to provide this information. Information on flight distance will be required to determine whether the short- or long-haul factors should be used.

To calculate emissions for international air travel, gather the information on how far each passenger flew for each flight. Multiply this by the factors in [Table 7.27](#) or [Table 7.28](#). Use the specified emission factors for different cabin classes if information is available. If unknown, use the average emission factors.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = passengers multiplied by distance flown (pkm)
- F = appropriate emission factors from [Table 7.27](#) or [Table 7.28](#).

#### INTERNATIONAL AIR TRAVEL: EXAMPLE CALCULATION

An entity makes five flights from Auckland to Shanghai (9,346 km each way). On the first trip, two people flew return to Shanghai on the same flight in economy class. On the second trip, three people flew return to Shanghai and the cabin classes were not recorded. Long-haul (>3,700 km) emission factors with radiative forcing are used.

For the two people who travel economy class: Passenger kilometres travelled =  $(2 \times 9,346) \times 2 = 37,384$  pkm

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	$37,384 \times 0.0000112$ kg CO <sub>2</sub> -e per pkm	0.419 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	$37,384 \times 0.14713$ kg CO <sub>2</sub> -e per pkm	5,500 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	$37,384 \times 0.0006491611$ kg CO <sub>2</sub> -e per pkm	24.3 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	$37,384 \times 0.1477903611$ kg CO <sub>2</sub> -e per pkm	5,520 kg CO <sub>2</sub> -e

For the three people with unknown (average) travel classes: Passenger kilometres travelled =  $(3 \times 9,346) \times 2 = 56,076$  pkm

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	56,076 x 0.0000112 kg CO <sub>2</sub> -e per pkm	0.628 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	56,076 x 0.19212 kg CO <sub>2</sub> -e per pkm	10,800 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	56,076 x 0.0008536913 kg CO <sub>2</sub> -e per pkm	47.9 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	56,076 x 0.1929848913 kg CO <sub>2</sub> -e per pkm	10,800 kg CO <sub>2</sub> -e

Total CO<sub>2</sub>-e emissions from international air travel = 5,520 kg CO<sub>2</sub>-e + 10,800 kg CO<sub>2</sub>-e = 16,300 kg CO<sub>2</sub>-e

Note: Numbers may not add due to rounding.

### 7.5.2.2. Emission factor derivation methodology

The [2023 UK DESNZ Methodology Paper for Conversion Factors](#) publication discusses the methodology in more detail, including changes over time.

### 7.5.2.3. Assumptions, limitations and uncertainties

The emission factors in [Table 7.27](#) and [Table 7.28](#) are based on UK and European data. The short-haul emission factor applies to international flights of less than 3,700 km. The long-haul factor applies to flights of more than 3,700 km.

The UK DESNZ endorses a great circle distance uplift factor to account for non-direct (ie, not along the straight-line/great-circle between destinations) routes and delays/circling. The 8 percent uplift factor applied by UK DESNZ is based on the analysis of flights arriving and departing from the United Kingdom. This figure is likely to be overstated for international flights to/from New Zealand (initial estimates from Airways New Zealand suggest it is likely to be less than 5 per cent). In the absence of a New Zealand-specific figure for international flights, we recommend an 8 per cent uplift factor. This figure is comparable to an IPCC publication, *Aviation and the Global Atmosphere* (refer to section 8.2.2.3)<sup>24</sup>, which suggests for European flights the average flight distance is about 99 per cent to 1010 per cent greater than the actual flight track distance.

The emission factors refer to aviation's direct GHG emissions including carbon dioxide, methane and nitrous oxide. There is currently uncertainty over the other climate change impacts of aviation (including water vapour and indirect GHGs, among other factors), which the IPCC estimated to be up to two to four times those of carbon dioxide alone. However, the science is currently uncertain and [New Zealand's Greenhouse Gas Inventory 1990-2023](#) does not use a multiplier.

International travel is divided by class of travel. Emissions vary by class because they are based on the number of people on a flight. Business class passengers use more space and facilities than economy class travellers. If everyone flew business class, fewer people could fit on the flight and therefore emissions per person would be higher.

## 7.6. Helicopters

This section provides emission factors for some commonly used helicopters in New Zealand. Business activities that require the use of helicopters might include entities involved in tourism, air transport, agricultural operations, or emergency services.

**Table 7.29: Emission factors for helicopters**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Helicopter</b>					
Bell 206B	hours	320.5909112	318.170467	0.0622908427	2.358153331
Eurocopter AS 350B Squirrel	hours	465.0289696	461.5180258	0.0903551703	3.420588592
Eurocopter AS 350B3 Squirrel	hours	481.1247858	477.4923194	0.0934825889	3.538983721
Robinson R22 Beta	hours	123.9417068	122.9771726	0.0248225722	0.9397116614
Robinson R44	hours	179.0278644	177.6346408	0.0358550177	1.357368526

### 7.6.1. GHG inventory development

These emission factors can be used where the amount of fuel used is not known. Obtaining fuel data will provide a more accurate estimate of your carbon emissions. To calculate emissions from operating helicopters when only the number of operating hours is known.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = hours of operating time (hours)
- F = emission factors for correlating helicopter type, from [Table 7.29](#).

#### HELICOPTER USE: EXAMPLE CALCULATION

An agricultural operation used a Eurocopter AS 350B Squirrel to apply topdressing and other spraying activities. They could not obtain data on the amount of fuel used, but had recorded 10 flying hours over a given year.

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	10 x 0.0903551703 kg CO <sub>2</sub> -e per hours	0.904 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	10 x 461.5180258 kg CO <sub>2</sub> -e per hours	4,620 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	10 x 3.420588592 kg CO <sub>2</sub> -e per hours	34.2 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	10 x 465.0289696 kg CO <sub>2</sub> -e per hours	4,650 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 7.6.2. Emission factor derivation methodology

These emission factors were derived from the Swiss Federal Office of Civil Aviation’s (FOCA) *Guidance on the Determination of Helicopter Emissions*. This contains air emissions data (non-GHG) for one hour of flying time, including fuel consumption, for a range of helicopter models. This contains air emissions data (non-GHG) for one hour of flying time, including fuel consumption, for a range of helicopter models.

The one-hour emissions values are used, which assume a combination of rotations and cruise per flight-hour.

The fuel consumption (provided in kgs) was converted to litres using assumed densities of 0.804 kg per litre and 0.69 kg per litre, for Jet A1 and aviation gas respectively. Turbine engine helicopters are assumed to use Jet A1 while piston helicopters are assumed to use aviation gas. We then applied the Jet A1 and aviation gas emission factors from Transport fuels section above to determine the emission factor for one hour of operation.

We used the aircraft register on the New Zealand Civil Aviation Authority (CAA) website<sup>25</sup> to identify the most commonly registered helicopter models in the country.

### 7.6.3. Assumptions, limitations and uncertainties

Obtaining the amount of fuel used for helicopter activities would provide a more accurate estimate of carbon emissions, than using this emission factor which is based on operating hours.

A number of factors will influence the accuracy of this emission factor for a given operating hour, such as the cruising speed, the take-off and approach, and the way the helicopter is being used.

Finally, if your entity has a helicopter model that is not provided here, you may wish to choose the model that seems to be the best fit. However, this approach will have limitations, due to variations that include engine operating power, and the size and number of engines.

## 7.7. Accommodation

Accommodation is an indirect (Scope 3) emissions source associated with business travel. The emission factors for hotel stays have been updated using factors from the 2024 edition of the Cornell Hotel Sustainability Benchmarking Index (CHSB) Index,<sup>26</sup> which provides data for the 2022 calendar year.

We obtained the emission factors from the M1 tab of the source spreadsheet, using the median values for all hotels. The factors are in CO<sub>2</sub>-e and are not available by gas type. For more information on the Cornell methodology, see the Hotel Sustainability Benchmarking Index 2024 guidance document.<sup>27</sup>

Note these emission factors are based on either AR4 or AR5 GWP values, depending on the country. The reason is some countries submit their emission factors to this study in terms of CO<sub>2</sub>-e, while other countries break it down into the three main GHG types. In the latter cases, the AR5 GWPs were applied.

The provision of these emission factors can be limited by the availability of data in different countries. If the factor for a certain country is not available in [Table 7.30](#), we recommend using factors from a previous edition of this guidance.

The Cornell Hotel Sustainability Benchmarking Index has introduced a new hotel type classification, replacing the previous “All Hotels” group into separate “Resort” and “Non-Resort” categories, with the latter used to calculate the 2025 emissions factors. This had a significant impact, with the factors decreasing for 40 out of the 48 countries provided. 26 of these countries decreased by over 20%.

**Table 7.30: Accommodation emission factors by unit (room per night)**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
Hotel Stays		

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
Argentina	Room per night	15.32536591
Australia	Room per night	34.11941583
Austria	Room per night	10.0507584
Bahrain	Room per night	102.8526699
Belgium	Room per night	14.552063
Brazil	Room per night	6.757310062
Canada	Room per night	10.62474158
Caribbean Region	Room per night	43.77455914
Chile	Room per night	31.45942816
China	Room per night	58.30625072
Colombia	Room per night	16.27678951
Costa Rica	Room per night	5.631959026
Czech Republic	Room per night	20.79396066
Egypt	Room per night	51.80399693
Finland	Room per night	10.76387424
France	Room per night	7.208308927
Germany	Room per night	13.03291589
Greece	Room per night	26.14054121
Hong Kong	Room per night	79.27066469
Hungary	Room per night	22.22753295
India	Room per night	48.93327122
Indonesia	Room per night	52.31393587
Italy	Room per night	15.33321042
Japan	Room per night	37.39716278
Jordan	Room per night	63.32658195
Kazakhstan	Room per night	73.75667032
Macau	Room per night	130.3482989
Malaysia	Room per night	55.17545263
Mexico	Room per night	18.43939187
Netherlands	Room per night	15.56062372
New Zealand	Room per night	10.30784912
Oman	Room per night	76.39205262
Panama	Room per night	21.19874686

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit
Peru	Room per night	16.31695679
Philippines	Room per night	55.76161689
Poland	Room per night	29.33200281
Portugal	Room per night	12.77550297
Qatar	Room per night	90.61959799
Saudi Arabia	Room per night	72.51266367
Singapore	Room per night	23.30541411
South Africa	Room per night	52.74867755
South Korea	Room per night	45.61996656
Spain	Room per night	11.51795365
Switzerland	Room per night	7.94082916
Thailand	Room per night	43.879308
Turkey	Room per night	32.6361285
United Arab Emirates	Room per night	54.72447283
United Kingdom	Room per night	10.37875541
United States	Room per night	14.23988937
Vietnam	Room per night	76.44083626

### 7.7.1. GHG inventory development

To calculate emissions from accommodation during business trips, collect data on the number of nights and the country stayed in.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = rooms per night
- F = emission factors for the country stayed in from [Table 7.30](#).

#### ACCOMODATION: EXAMPLE CALCULATION

An entity sends six people to a conference in Australia. They book three rooms for four nights. 3 rooms x 4 nights = 12

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	12 x 34.11941583 kg CO <sub>2</sub> -e per Room per night	409 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

## 7.7.2. Assumptions, limitations and uncertainties

The Hotel Sustainability Benchmarking Index 2024 guidance document outlines the limitations of the study. These include:

- it is skewed towards upmarket and chain hotels, meaning the data may not be representative of the entire hotel industry, particularly the economy and midscale segments
- the results do not distinguish a property's facilities, except for outsourced laundry services, which are taken into consideration. This means it is difficult to compare two hotels because some may contain distinct attributes (such as restaurants, fitness centres and swimming pools) while others do not
- the data have not been independently verified by a third-party provider.

## 8. Freight transport emission factors

We provide emission factors for freighting goods (in tonne kilometres, tkm) and for the actual freight vehicles (in km). We provide freight vehicle emission factors (in km) for road light commercial and heavy goods vehicles (HGVs). Users should note that these are average emission factors for certain vehicle categories of the New Zealand vehicle fleet. The actual emissions for a specific vehicle in a specific trip could be different.

### 8.1. Overview of changes since previous update

Table 8.1: Summary of changes to freight emission factors

Domain	Emission factors	Size of change	Explanation for change
Freight	All electric, PHEV light commercial vehicles, Electric heavy goods vehicles	39.10%	The change in all-electric, PHEV light commercial vehicles and Electric heavy goods vehicles, is driven by the increase in the latest annual electricity factor, which is used to derive these emissions factors.
	Air freight and International sea freight	Minor	The Air freight and International sea freight emission factors were updated using factors from DESNZ 2024.

### 8.2. Road freight

Entities freighting goods through third-party providers can categorise road freight emissions as indirect (Scope 3). We generated emission factors for freight vehicles (in km travelled) and an average emission factor for freighting goods by road in tkm. Where the entity's goods are only part of the load, the tkm emission factor should be used as the way of allocating emissions between the different goods on the same truck.

Downstream and upstream transportation and distribution can also be considered. Refer to the [GHG Protocol](#).

The three road freight emission factors provided in tkm are for urban delivery heavy trucks, long-haul heavy trucks and all trucks. Urban delivery heavy trucks include vans and road user charge (RUC) type 2 trucks, such as those powered vehicles with two axles. Please note these trucks could carry trailers and most of their travel would be for urban delivery. Long-haul heavy trucks include other RUC types, such as those powered vehicles with three or more axles. Most of them would be used for relatively long-distance travel. The emission factor for 'all trucks' should be used for a large fleet with a good mix of small and large trucks. Users should be aware that the emission behaviour of individual vehicles could vary greatly.

Te Manatū Waka Ministry of Transport's Vehicle Fleet Emissions Model provided the real-world fuel consumption rates of the vehicle fleet. We decided to split the fleet into three categories and develop average emission factors for these.

- Pre-2010 fleet is based on the average fuel consumption data from 1970 to 2010. We assume there are no electric vehicles or diesel hybrids.

- 2010–2015 fleet is based on the average fuel consumption data from vehicles produced between 2010 and 2015.
- Post-2015 fleet is based on the average fuel consumption data from vehicles produced from 2015 onwards.

## TONNE KILOMETRES (TKM)

A tkm is the distance travelled multiplied by the weight of freight carried by the Light Commercial Vehicle or Heavy Goods Vehicle. For example, a Heavy Goods Vehicle carrying 5 tonnes freight over 100 km has a tkm value of 500 tkm. The carbon emissions are calculated from these factors by multiplying the number of tkm the user has for the distance and weight of the goods being moved, by the emission factors provided in [Table 8.11](#).

### 8.2.1. Light commercial vehicle emission factors

**Table 8.2: Emission factors for light commercial vehicles manufactured pre-2010**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Pre 2010 Fleet</b>						
Diesel hybrid: 1350 – <1600 cc	km	0.1919217402	0.1889576639	0.0002832564	0.0026808198	
Diesel hybrid: 1600 – <2000 cc	km	0.2554898405	0.2515440063	0.0003770763	0.0035687579	
Diesel hybrid: 2000 – <3000 cc	km	0.273950743	0.269719795	0.0004043227	0.0038266253	
Diesel hybrid: <1350 cc	km	0.1994377945	0.1963576389	0.0002943493	0.0027858063	
Diesel hybrid: ≥3000 cc	km	0.2773983583	0.2731141647	0.000409411	0.0038747826	
Diesel: 1350 – <1600 cc	km	0.2140959651	0.2107894259	0.0003159833	0.002990556	
Diesel: 1600 – <2000 cc	km	0.285008587	0.2806068596	0.0004206429	0.0039810846	
Diesel: 2000 – <3000 cc	km	0.3056024225	0.3008826399	0.0004510372	0.0042687454	
Diesel: <1350 cc	km	0.2224804082	0.219044378	0.0003283578	0.0031076724	
Diesel: ≥3000 cc	km	0.3094483678	0.3046691877	0.0004567135	0.0043224667	
Petrol hybrid: 1350 – <1600 cc	km	0.1811448791	0.1735433637	0.0023074245	0.0052940908	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Petrol hybrid: 1600 – <2000 cc	km	0.2444085155	0.2341522219	0.003113277	0.0071430166	
Petrol hybrid: 2000 – <3000 cc	km	0.2585373943	0.2476882002	0.0032932508	0.0075559434	
Petrol hybrid: <1350 cc	km	0.1687030305	0.1616236216	0.0021489402	0.0049304688	
Petrol hybrid: ≥3000 cc	km	0.2952303035	0.2828413379	0.0037606453	0.0086283203	
Petrol: 1350 – <1600 cc	km	0.2294501801	0.2198215941	0.0029227377	0.0067058484	
Petrol: 1600 – <2000 cc	km	0.3095841196	0.2965928144	0.0039434843	0.009047821	
Petrol: 2000 – <3000 cc	km	0.3274806995	0.3137383869	0.004171451	0.0095708616	
Petrol: <1350 cc	km	0.2136905054	0.2047232541	0.0027219909	0.0062452604	
Petrol: ≥3000 cc	km	0.3739583844	0.3582656946	0.004763484	0.0109292057	

**Table 8.3: Emission factors for light commercial vehicles manufactured between 2010 and 2015**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>2010–2015 Fleet</b>						
Diesel hybrid: 1350 – <1600 cc	km	0.1701406787	0.1675129934	0.0002511099	0.0023765755	
Diesel hybrid: 1600 – <2000 cc	km	0.2264944807	0.2229964564	0.0003342822	0.0031637421	
Diesel hybrid: 2000 – <3000 cc	km	0.2428602685	0.2391094878	0.0003584364	0.0033923443	
Diesel hybrid: <1350 cc	km	0.1768037414	0.1740731504	0.0002609438	0.0024696471	
Diesel hybrid: ≥3000 cc	km	0.2459166164	0.2421186329	0.0003629472	0.0034350363	
Diesel: 1350 – <1600 cc	km	0.1896759937	0.1867466012	0.0002799419	0.0026494506	
Diesel: 1600 – <2000 cc	km	0.2525002605	0.2486005979	0.000372664	0.0035269986	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Diesel: 2000 - <3000 cc	km	0.2707451452	0.2665637051	0.0003995915	0.0037818486	
Diesel: <1350 cc	km	0.1971041	0.1940599863	0.0002909051	0.0027532086	
Diesel: ≥3000 cc	km	0.2741524187	0.269918356	0.0004046203	0.0038294424	
Electric vehicle: 1350 - <1600 cc	km	0.0247218571	0.0240079942	0.000667526	0.0000463369	
Electric vehicle: 1600 - <2000 cc	km	0.0279698734	0.0271622215	0.0007552271	0.0000524247	
Electric vehicle: 2000 - <3000 cc	km	0.0344485331	0.033453805	0.0009301603	0.0000645679	
Electric vehicle: <1350 cc	km	0.0230238483	0.0223590167	0.0006216773	0.0000431543	
Electric vehicle: ≥3000 cc	km	0.0402682137	0.0391054377	0.0010873001	0.0000754759	
PHEV (Diesel) - Diesel consumption: 1350 - <1600 cc	km	0.0890402885	0.0876651332	0.0001314142	0.0012437412	
PHEV (Diesel) - Diesel consumption: 1600 - <2000 cc	km	0.1185321116	0.1167014788	0.000174941	0.0016556917	
PHEV (Diesel) - Diesel consumption: 2000 - <3000 cc	km	0.1270968739	0.1251339653	0.0001875817	0.0017753269	
PHEV (Diesel) - Diesel consumption: <1350 cc	km	0.0925272914	0.0910982821	0.0001365606	0.0012924487	
PHEV (Diesel) - Diesel consumption: ≥3000 cc	km	0.1286963626	0.1267087512	0.0001899424	0.001797669	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
PHEV (Diesel) – Electricity consumption: 1350 – <1600 cc	km	0.0106919653	0.0103832265	0.0002886986	0.0000200403	
PHEV (Diesel) – Electricity consumption: 1600 – <2000 cc	km	0.0117150818	0.0113767997	0.0003163242	0.0000219579	
PHEV (Diesel) – Electricity consumption: 2000 – <3000 cc	km	0.0132597709	0.0128768847	0.000358033	0.0000248532	
PHEV (Diesel) – Electricity consumption: <1350 cc	km	0.0111320508	0.0108106042	0.0003005815	0.0000208651	
PHEV (Diesel) – Electricity consumption: ≥3000 cc	km	0.0156828477	0.0152299933	0.0004234596	0.0000293948	
PHEV (Petrol) – Electricity consumption: 1350 – <1600 cc	km	0.0117840852	0.0114438106	0.0003181874	0.0000220872	
PHEV (Petrol) – Electricity consumption: 1600 – <2000 cc	km	0.0133323063	0.0129473256	0.0003599916	0.0000249891	
PHEV (Petrol) – Electricity consumption: 2000 – <3000 cc	km	0.0164204675	0.0159463137	0.0004433764	0.0000307774	
PHEV (Petrol) – Electricity consumption: <1350 cc	km	0.010974701	0.010657798	0.0002963328	0.0000205702	
PHEV (Petrol) – Electricity consumption: ≥3000 cc	km	0.0191945152	0.0186402586	0.0005182797	0.0000359768	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
PHEV (Petrol) – Petrol consumption: 1350 – <1600 cc	km	0.0839862797	0.0804619019	0.0010698177	0.0024545601	
PHEV (Petrol) – Petrol consumption: 1600 – <2000 cc	km	0.1133179258	0.1085626826	0.0014434444	0.0033117988	
PHEV (Petrol) – Petrol consumption: 2000 – <3000 cc	km	0.11986866	0.1148385236	0.0015268877	0.0035032488	
PHEV (Petrol) – Petrol consumption: <1350 cc	km	0.0782177227	0.0749354151	0.0009963378	0.0022859698	
PHEV (Petrol) – Petrol consumption: ≥3000 cc	km	0.1368810147	0.1311369764	0.0017435911	0.0040004472	
Petrol hybrid: 1350 – <1600 cc	km	0.1604833371	0.1537488572	0.0020442377	0.0046902422	
Petrol hybrid: 1600 – <2000 cc	km	0.2165310683	0.2074446164	0.002758174	0.0063282779	
Petrol hybrid: 2000 – <3000 cc	km	0.229048395	0.2194366693	0.0029176197	0.0066941059	
Petrol hybrid: <1350 cc	km	0.1494606166	0.1431886912	0.0019038302	0.0043680952	
Petrol hybrid: ≥3000 cc	km	0.2615560791	0.2505802097	0.0033317028	0.0076441666	
Petrol: 1350 – <1600 cc	km	0.2032788936	0.1947485525	0.0025893677	0.0059409735	
Petrol: 1600 – <2000 cc	km	0.2742726865	0.2627631808	0.003493687	0.0080158187	
Petrol: 2000 – <3000 cc	km	0.2901279669	0.2779531144	0.0036956517	0.0084792008	
Petrol: <1350 cc	km	0.189316781	0.1813723422	0.0024115182	0.0055329206	
Petrol: ≥3000 cc	km	0.3313043669	0.3174015989	0.0042201569	0.0096826111	

**Table 8.4: Emission factors for light commercial vehicles manufactured between 2015 and 2020**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>2015-2020 Fleet</b>						
Diesel hybrid: 1350 – <1600 cc	km	0.1615971001	0.1591013634	0.0002385004	0.0022572363	
Diesel hybrid: 1600 – <2000 cc	km	0.2151211077	0.2117987359	0.0003174963	0.0030048755	
Diesel hybrid: 2000 – <3000 cc	km	0.2306650909	0.2271026549	0.0003404376	0.0032219985	
Diesel hybrid: <1350 cc	km	0.1679255785	0.1653321036	0.0002478406	0.0023456343	
Diesel hybrid: ≥3000 cc	km	0.2335679649	0.2299606964	0.0003447219	0.0032625467	
Diesel: 1350 – <1600 cc	km	0.1796210944	0.1768469916	0.000265102	0.0025090008	
Diesel: 1600 – <2000 cc	km	0.2391149888	0.2354220509	0.0003529087	0.0033400291	
Diesel: 2000 – <3000 cc	km	0.2563926954	0.2524329173	0.0003784088	0.0035813693	
Diesel: <1350 cc	km	0.1866554299	0.1837726875	0.0002754839	0.0026072585	
Diesel: ≥3000 cc	km	0.2596193461	0.255609735	0.000383171	0.0036264401	
Electric vehicle: 1350 – <1600 cc	km	0.0238448895	0.0231563498	0.0006438466	0.0000446932	
Electric vehicle: 1600 – <2000 cc	km	0.0269776877	0.026198686	0.0007284367	0.0000505651	
Electric vehicle: 2000 – <3000 cc	km	0.0332265276	0.0322670857	0.0008971644	0.0000622774	
Electric vehicle: <1350 cc	km	0.0222071148	0.0215658671	0.0005996243	0.0000416234	
Electric vehicle: ≥3000 cc	km	0.0388397644	0.037718236	0.0010487299	0.0000727985	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
PHEV (Diesel) - Diesel consumption: 1350 - <1600 cc	km	0.0845691491	0.0832630469	0.0001248152	0.001181287	
PHEV (Diesel) - Diesel consumption: 1600 - <2000 cc	km	0.1125800464	0.1108413385	0.0001661564	0.0015725515	
PHEV (Diesel) - Diesel consumption: 2000 - <3000 cc	km	0.1207147309	0.1188503894	0.0001781623	0.0016861792	
PHEV (Diesel) - Diesel consumption: <1350 cc	km	0.0878810528	0.0865238009	0.0001297033	0.0012275486	
PHEV (Diesel) - Diesel consumption: ≥3000 cc	km	0.1222339017	0.1203460978	0.0001804045	0.0017073994	
PHEV (Diesel) - Electricity consumption: 1350 - <1600 cc	km	0.0103126852	0.0100148984	0.0002784574	0.0000193294	
PHEV (Diesel) - Electricity consumption: 1600 - <2000 cc	km	0.0112995083	0.0109732262	0.0003051031	0.000021179	
PHEV (Diesel) - Electricity consumption: 2000 - <3000 cc	km	0.0127894022	0.0124200982	0.0003453324	0.0000239715	
PHEV (Diesel) - Electricity consumption: <1350 cc	km	0.0107371594	0.0104271156	0.0002899189	0.000020125	
PHEV (Diesel) - Electricity consumption: ≥3000 cc	km	0.0151265243	0.0146897341	0.0004084381	0.0000283521	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
PHEV (Petrol) – Electricity consumption: 1350 – <1600 cc	km	0.011366064	0.01103786	0.0003069002	0.0000213037	
PHEV (Petrol) – Electricity consumption: 1600 – <2000 cc	km	0.0128593645	0.0124880403	0.0003472215	0.0000241027	
PHEV (Petrol) – Electricity consumption: 2000 – <3000 cc	km	0.0158379781	0.0153806442	0.0004276484	0.0000296856	
PHEV (Petrol) – Electricity consumption: <1350 cc	km	0.0105853914	0.01027973	0.0002858209	0.0000198405	
PHEV (Petrol) – Electricity consumption: ≥3000 cc	km	0.018513621	0.0179790258	0.0004998946	0.0000347006	
PHEV (Petrol) – Petrol consumption: 1350 – <1600 cc	km	0.0795340896	0.0761965423	0.0010131057	0.0023244416	
PHEV (Petrol) – Petrol consumption: 1600 – <2000 cc	km	0.107310838	0.1028076747	0.0013669261	0.0031362373	
PHEV (Petrol) – Petrol consumption: 2000 – <3000 cc	km	0.1135143118	0.1087508276	0.0014459459	0.0033175383	
PHEV (Petrol) – Petrol consumption: <1350 cc	km	0.0740713291	0.0709630196	0.000943521	0.0021647885	
PHEV (Petrol) – Petrol consumption: ≥3000 cc	km	0.1296248259	0.1241852843	0.0016511618	0.0037883798	
Petrol hybrid: 1350 – <1600 cc	km	0.1519759674	0.1455984885	0.0019358707	0.0044416082	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Petrol hybrid: 1600 – <2000 cc	km	0.2050525567	0.196447786	0.0026119606	0.0059928101	
Petrol hybrid: 2000 – <3000 cc	km	0.2169063283	0.2078041291	0.002762954	0.0063392452	
Petrol hybrid: <1350 cc	km	0.1415375715	0.1355981266	0.0018029064	0.0041365385	
Petrol hybrid: ≥3000 cc	km	0.2476907501	0.2372967216	0.0031550862	0.0072389423	
Petrol: 1350 – <1600 cc	km	0.192502892	0.1844247521	0.0024521029	0.005626037	
Petrol: 1600 – <2000 cc	km	0.2597332385	0.2488338622	0.0033084835	0.0075908928	
Petrol: 2000 – <3000 cc	km	0.2747480159	0.2632185635	0.0034997418	0.0080297106	
Petrol: <1350 cc	km	0.1792809239	0.1717576271	0.0022836814	0.0052396154	
Petrol: ≥3000 cc	km	0.3137416168	0.3005758474	0.0039964425	0.0091693269	

**Table 8.5: Emission factors for light commercial vehicles manufactured after 2020**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Post 2020 Fleet</b>						
Diesel hybrid: 1350 – <1600 cc	km	0.1551980033	0.1528010955	0.000229056	0.0021678518	
Diesel hybrid: 1600 – <2000 cc	km	0.2066025093	0.2034117004	0.0003049237	0.0028858852	
Diesel hybrid: 2000 – <3000 cc	km	0.221530965	0.2181095982	0.0003269566	0.0030944103	
Diesel hybrid: <1350 cc	km	0.1612758797	0.158785104	0.0002380263	0.0022527494	
Diesel hybrid: ≥3000 cc	km	0.2243188879	0.2208544638	0.0003310712	0.0031333528	
Diesel: 1350 – <1600 cc	km	0.171701201	0.1690494147	0.000253413	0.0023983733	
Diesel: 1600 – <2000 cc	km	0.2285718774	0.2250417694	0.0003373482	0.0031927598	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Diesel: 2000 - <3000 cc	km	0.2450877715	0.2413025888	0.0003617239	0.0034234587	
Diesel: <1350 cc	km	0.178425377	0.1756697412	0.0002633372	0.0024922986	
Diesel: ≥3000 cc	km	0.2481721521	0.2443393336	0.0003662762	0.0034665423	
Electric vehicle: 1350 - <1600 cc	km	0.0232047837	0.0225347275	0.0006265628	0.0000434934	
Electric vehicle: 1600 - <2000 cc	km	0.0262534833	0.0254953935	0.0007088821	0.0000492077	
Electric vehicle: 2000 - <3000 cc	km	0.0323345757	0.0314008897	0.0008730804	0.0000606056	
Electric vehicle: <1350 cc	km	0.0216109743	0.0209869406	0.0005835276	0.0000405061	
Electric vehicle: ≥3000 cc	km	0.0377971277	0.0367057062	0.0010205772	0.0000708442	
PHEV (Diesel) - Diesel consumption: 1350 - <1600 cc	km	0.0812202884	0.0799659066	0.0001198727	0.0011345091	
PHEV (Diesel) - Diesel consumption: 1600 - <2000 cc	km	0.1081219799	0.1064521232	0.0001595767	0.0015102799	
PHEV (Diesel) - Diesel consumption: 2000 - <3000 cc	km	0.1159345384	0.114144023	0.0001711073	0.001619408	
PHEV (Diesel) - Diesel consumption: <1350 cc	km	0.0844010437	0.0830975378	0.0001245671	0.0011789388	
PHEV (Diesel) - Diesel consumption: ≥3000 cc	km	0.1173935513	0.1155805027	0.0001732606	0.001639788	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
PHEV (Diesel) – Electricity consumption: 1350 – <1600 cc	km	0.0100358456	0.0097460528	0.0002709824	0.0000188105	
PHEV (Diesel) – Electricity consumption: 1600 – <2000 cc	km	0.0109961779	0.0106786547	0.0002969127	0.0000206105	
PHEV (Diesel) – Electricity consumption: 2000 – <3000 cc	km	0.0124460762	0.012086686	0.0003360621	0.000023328	
PHEV (Diesel) – Electricity consumption: <1350 cc	km	0.010448925	0.0101472042	0.0002821361	0.0000195847	
PHEV (Diesel) – Electricity consumption: ≥3000 cc	km	0.0147204592	0.0142953945	0.0003974737	0.000027591	
PHEV (Petrol) – Electricity consumption: 1350 – <1600 cc	km	0.0110609469	0.0107415534	0.0002986616	0.0000207318	
PHEV (Petrol) – Electricity consumption: 1600 – <2000 cc	km	0.0125141604	0.0121528042	0.0003379005	0.0000234556	
PHEV (Petrol) – Electricity consumption: 2000 – <3000 cc	km	0.0154128144	0.0149677574	0.0004161683	0.0000288887	
PHEV (Petrol) – Electricity consumption: <1350 cc	km	0.0103012311	0.010003775	0.0002781482	0.0000193079	
PHEV (Petrol) – Electricity consumption: ≥3000 cc	km	0.0180166309	0.0174963866	0.0004864751	0.0000337691	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
PHEV (Petrol) – Petrol consumption: 1350 – <1600 cc	km	0.0762806973	0.0730796745	0.000971664	0.0022293589	
PHEV (Petrol) – Petrol consumption: 1600 – <2000 cc	km	0.1029212203	0.0986022617	0.0013110111	0.0030079475	
PHEV (Petrol) – Petrol consumption: 2000 – <3000 cc	km	0.1088709371	0.1043023062	0.0013867986	0.0031818323	
PHEV (Petrol) – Petrol consumption: <1350 cc	km	0.0710413945	0.0680602324	0.0009049257	0.0020762364	
PHEV (Petrol) – Petrol consumption: ≥3000 cc	km	0.1243224404	0.1191054067	0.0015836199	0.0036334137	
Petrol hybrid: 1350 – <1600 cc	km	0.1457592943	0.1396426902	0.0018566827	0.0042599214	
Petrol hybrid: 1600 – <2000 cc	km	0.1966647521	0.188411965	0.0025051167	0.0057476704	
Petrol hybrid: 2000 – <3000 cc	km	0.2080336377	0.1993037697	0.0026499336	0.0060799343	
Petrol hybrid: <1350 cc	km	0.1357478876	0.1300513995	0.0017291574	0.0039673307	
Petrol hybrid: ≥3000 cc	km	0.2375588033	0.2275899491	0.0030260254	0.0069428288	
Petrol: 1350 – <1600 cc	km	0.1831521734	0.1754664245	0.0023329934	0.0053527555	
Petrol: 1600 – <2000 cc	km	0.247116844	0.2367468988	0.0031477758	0.0072221695	
Petrol: 2000 – <3000 cc	km	0.2614022871	0.2504328714	0.0033297438	0.0076396719	
Petrol: <1350 cc	km	0.1705724549	0.1634145979	0.0021727529	0.004985104	
Petrol: ≥3000 cc	km	0.298501796	0.2859755464	0.0038023176	0.0087239321	

**Table 8.6: Default light commercial vehicle values (based on pre-2010 fleet and a 2000–3000 cc engine size)**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Light Commercial Vehicle Default</b>					
Diesel	km	0.3056024225	0.3008826399	0.0004510372	0.0042687454
Diesel Hybrid	km	0.273950743	0.269719795	0.0004043227	0.0038266253
Petrol	km	0.3274806995	0.3137383869	0.004171451	0.0095708616
Petrol Hybrid	km	0.2585373943	0.2476882002	0.0032932508	0.0075559434

## 8.2.2. Heavy goods vehicles emission factors

Table 8.7 contains the default emission factors for heavy goods vehicles, based on a 2010–2015 fleet.

**Table 8.7: Emission factors for heavy goods vehicles, based on a pre-2010 fleet**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Pre 2010 Fleet</b>						
HGV diesel hybrid: 10,000 – 12,000 kg	km	0.5943068902	0.5851283003	0.0008771349	0.0083014551	
HGV diesel hybrid: 12,000 – 15,000 kg	km	0.6752634445	0.6648345459	0.0009966183	0.0094322802	
HGV diesel hybrid: 15,000 – 20,000 kg	km	0.8897178929	0.8759769186	0.0013131306	0.0124278436	
HGV diesel hybrid: 20,000 – 25,000 kg	km	1.184324691	1.166033753	0.0017479395	0.0165429989	
HGV diesel hybrid: 25,000 – 30,000 kg	km	1.367683245	1.346560482	0.0020185576	0.0191042056	
HGV diesel hybrid: 5,000 – 7,500 kg	km	0.4098760646	0.4035458598	0.0006049342	0.0057252705	
HGV diesel hybrid: 7,500 – 10,000 kg	km	0.5012872732	0.4935452961	0.0007398476	0.0070021294	
HGV diesel hybrid: < 5,000 kg	km	0.3578708608	0.3523438344	0.00052818	0.0049988464	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
HGV diesel hybrid: ≥ 30,000 kg	km	1.440865825	1.418612816	0.0021265674	0.0201264416	
HGV diesel: 10,000 – 12,000 kg	km	0.7374552345	0.726065834	0.0010884069	0.0103009936	
HGV diesel: 12,000 – 15,000 kg	km	0.8379807572	0.8250388212	0.001236772	0.011705164	
HGV diesel: 15,000 – 20,000 kg	km	0.978716489	0.9636010033	0.0014444833	0.0136710025	
HGV diesel: 20,000 – 25,000 kg	km	1.303078842	1.282953842	0.0019232082	0.0182017921	
HGV diesel: 25,000 – 30,000 kg	km	1.535493851	1.511779388	0.0022662285	0.0214482339	
HGV diesel: 5,000 – 7,500 kg	km	0.5085251108	0.5006713512	0.0007505299	0.0071032297	
HGV diesel: 7,500 – 10,000 kg	km	0.6219179004	0.6123128807	0.0009178858	0.0086871339	
HGV diesel: < 5,000 kg	km	0.4439207082	0.4370647114	0.0006551806	0.0062008162	
HGV diesel: ≥ 30,000 kg	km	1.535493851	1.511779388	0.0022662285	0.0214482339	

Table 8.8 contains the default emission factors for heavy goods vehicles, based on a 2010–2015 fleet.

**Table 8.8: Emission factors for heavy goods vehicles manufactured between 2010 and 2015**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>2010–2015 Fleet</b>						
HGV BEV: 10,000 – 12,000 kg	km	0.0802141796	0.0778979327	0.0021658991	0.0001503477	
HGV BEV: 12,000 – 15,000 kg	km	0.0911495092	0.0885174963	0.0024611688	0.0001708441	
HGV BEV: 5,000 – 7,500 kg	km	0.0553295039	0.0537318215	0.0014939768	0.0001037057	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
HGV BEV: 7,500 – 10,000 kg	km	0.0676467111	0.0656933597	0.0018265592	0.0001267922	
HGV BEV: < 5,000 kg	km	0.0482895454	0.0468951473	0.0013038877	0.0000905105	
HGV diesel hybrid: 10,000 – 12,000 kg	km	0.5632109952	0.5545126562	0.0008312406	0.0078670984	
HGV diesel hybrid: 12,000 – 15,000 kg	km	0.6401465286	0.6302599824	0.0009447894	0.0089417567	
HGV diesel hybrid: 15,000 – 20,000 kg	km	0.8672001758	0.8538069695	0.0012798969	0.0121133095	
HGV diesel hybrid: 20,000 – 25,000 kg	km	1.154301069	1.136473821	0.0017036278	0.01612362	
HGV diesel hybrid: 25,000 – 30,000 kg	km	1.332834397	1.312249846	0.0019671243	0.0186174265	
HGV diesel hybrid: 5,000 – 7,500 kg	km	0.3886986878	0.3826955505	0.0005736787	0.0054294587	
HGV diesel hybrid: 7,500 – 10,000 kg	km	0.4750166033	0.4676803555	0.0007010749	0.0066351729	
HGV diesel hybrid: < 5,000 kg	km	0.3391060966	0.3338688768	0.0005004852	0.0047367346	
HGV diesel hybrid: ≥ 30,000 kg	km	1.404140501	1.382454685	0.0020723647	0.0196134513	
HGV diesel: 10,000 – 12,000 kg	km	0.6972450254	0.6864766391	0.0010290608	0.0097393255	
HGV diesel: 12,000 – 15,000 kg	km	0.7950898675	0.7828103467	0.0011734696	0.0111060513	
HGV diesel: 15,000 – 20,000 kg	km	0.9540542274	0.9393196304	0.0014080844	0.0133265127	
HGV diesel: 20,000 – 25,000 kg	km	1.269838403	1.250226774	0.0018741488	0.0177374798	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
HGV diesel: 25,000 – 30,000 kg	km	1.41808004	1.396178939	0.002092938	0.019808163	
HGV diesel: 5,000 – 7,500 kg	km	0.482790577	0.4753342665	0.0007125484	0.0067437621	
HGV diesel: 7,500 – 10,000 kg	km	0.5900178012	0.5809054528	0.0008708046	0.0082415438	
HGV diesel: < 5,000 kg	km	0.4214029912	0.4148947623	0.0006219468	0.0058862821	
HGV diesel: ≥ 30,000 kg	km	1.493943301	1.470870554	0.0022049042	0.0208678435	

Table 8.9 contains the default emission factors for heavy goods vehicles, based on a post-2015 fleet.

**Table 8.9: Emission factors for heavy goods vehicles manufactured post-2015**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Post 2015 Fleet</b>						
HGV BEV: 10,000 – 12,000 kg	km	0.0891583	0.0865837847	0.0024074033	0.000167112	
HGV BEV: 12,000 – 15,000 kg	km	0.100039225	0.0971505146	0.002701204	0.0001875064	
HGV BEV: 5,000 – 7,500 kg	km	0.0541217213	0.0525589145	0.0014613649	0.0001014419	
HGV BEV: 7,500 – 10,000 kg	km	0.0661777862	0.0642668512	0.0017868961	0.0001240389	
HGV BEV: < 5,000 kg	km	0.0472449766	0.0458807412	0.0012756828	0.0000885526	
HGV diesel hybrid: 10,000 – 12,000 kg	km	0.5495395241	0.54105233	0.0008110629	0.0076761312	
HGV diesel hybrid: 12,000 – 15,000 kg	km	0.624598581	0.6149521604	0.0009218422	0.0087245784	
HGV diesel hybrid: 15,000 – 20,000 kg	km	0.8650556313	0.8516955458	0.0012767317	0.0120833539	

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
HGV diesel hybrid: 20,000 – 25,000 kg	km	1.151620388	1.133834541	0.0016996714	0.0160861754	
HGV diesel hybrid: 25,000 – 30,000 kg	km	1.32961758	1.309082711	0.0019623766	0.0185724931	
HGV diesel hybrid: 5,000 – 7,500 kg	km	0.3790482376	0.3731941437	0.0005594356	0.0052946583	
HGV diesel hybrid: 7,500 – 10,000 kg	km	0.4634896767	0.4563314529	0.0006840623	0.0064741614	
HGV diesel hybrid: < 5,000 kg	km	0.3307959867	0.3256871098	0.0004882203	0.0046206565	
HGV diesel hybrid: ≥ 30,000 kg	km	1.400923684	1.37928755	0.002067617	0.0195685179	
HGV diesel: 10,000 – 12,000 kg	km	0.6892029836	0.6785588002	0.0010171916	0.0096269919	
HGV diesel: 12,000 – 15,000 kg	km	0.7832948729	0.7711975162	0.0011560614	0.0109412953	
HGV diesel: 15,000 – 20,000 kg	km	0.9516416149	0.9369442787	0.0014045236	0.0132928126	
HGV diesel: 20,000 – 25,000 kg	km	1.266889654	1.247323566	0.0018697968	0.0176962908	
HGV diesel: 25,000 – 30,000 kg	km	1.414595155	1.392747876	0.0020877946	0.0197594851	
HGV diesel: 5,000 – 7,500 kg	km	0.4752846713	0.4679442834	0.0007014705	0.0066389174	
HGV diesel: 7,500 – 10,000 kg	km	0.5811715552	0.5721958299	0.0008577485	0.0081179768	
HGV diesel: < 5,000 kg	km	0.4197945828	0.4133111945	0.0006195729	0.0058638154	
HGV diesel: ≥ 30,000 kg	km	1.490458417	1.46743949	0.0021997609	0.0208191656	

Table 8.10 contains the default emission factors for heavy goods vehicles, based on a pre-2010 fleet and a gross vehicle mass of <7500 kg.

**Table 8.10: Default emission factors for heavy goods vehicles**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Heavy Goods Vehicle Defaults</b>					
HGV Diesel	km	0.4762229095	0.4688680313	0.0007028553	0.006652023
HGV Diesel Hybrid	km	0.3838734627	0.3779448471	0.0005665571	0.0053620585

Table 8.11 contains emission factors for freighting goods

The tkm emission factor should be used where there is a mixed consignment on the same truck.

**Table 8.11: Emission factors for freighting goods by road**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Freighting Goods by Road</b>						
All trucks	tkm	0.135	0.132915034	0.0001992459	0.0018857201	
Long-haul heavy truck	tkm	0.105	0.1033783598	0.000154969	0.0014666712	
Urban delivery heavy truck	tkm	0.39	0.383976765	0.0005755993	0.0054476358	

### 8.2.3. GHG inventory development

If an entity uses freight vehicles, they can calculate the emissions from the kilometres travelled. Multiply the distances by the emission factors in Table 8.2 to Table 8.10.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = km travelled by specific freight vehicle one way
- F = appropriate emission factors from Table 8.2 to Table 8.10.

For emissions from freighting goods, users need to know the weight in tonnes of the goods freighted as well as the kilometres travelled. These two numbers multiplied together is the tkm. Multiply the tkm by the emission factors in Table 8.11. Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = tonne × kilometres travelled one way
- F = appropriate emission factors from Table 8.11.

## ROAD FREIGHT: EXAMPLE CALCULATION

During the reporting period, an entity moves 10 tonnes of goods by truck 100 km. They also hire a van (a light commercial vehicle) with a two-litre petrol engine, manufactured in 2012. This is used to drive 800 km. The weight of the goods moved by van is unknown.

```
road_freight_example_data = get_example_road_truck_and_van_goods_emissions_calculation()
```

For the 10 tonnes \* 100 km moved by truck:

### Example calculation of truck emissions for goods moved

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	1,000 x 0.0001992459 kg CO <sub>2</sub> -e per tkm	0.199 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	1,000 x 0.132915034 kg CO <sub>2</sub> -e per tkm	133 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	1,000 x 0.0018857201 kg CO <sub>2</sub> -e per tkm	1.89 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	1,000 x 0.135 kg CO <sub>2</sub> -e per tkm	135 kg CO <sub>2</sub> -e

For the hired van, use the emission factors for the 2010–2015 fleet, petrol 1600–2000 cc. (Note: if the quantity of fuel used is known, users can more accurately calculate emissions using the litres of fuel used rather than distance). In this example the fuel usage is unknown, so the entity applies the emission factors for km travelled to calculate the total CO<sub>2</sub>-e emissions.

For the goods moved by van:

### Example calculation of van emissions for goods moved

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	800 x 0.003493687 kg CO <sub>2</sub> -e per km	2.79 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	800 x 0.2627631808 kg CO <sub>2</sub> -e per km	210 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	800 x 0.0080158187 kg CO <sub>2</sub> -e per km	6.41 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	800 x 0.2742726865 kg CO <sub>2</sub> -e per km	219 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

Total CO<sub>2</sub>-e emissions from freighted goods = 135 kg CO<sub>2</sub>-e + 219 kg CO<sub>2</sub>-e = 354 kg CO<sub>2</sub>-e

For vehicles that run on electricity, care should be taken not to double-count emissions from electricity use that is already captured from reporting of an entities on-site electricity consumption.

## 8.2.4. Emission factor derivation methodology

The 2022 fleet statistics were taken from the Te Manatū Waka Ministry of Transport Vehicle Fleet Emissions Model. This provides energy (fuel and electricity) use per 100 km travelled by vehicle. The litres of fuel (or kWh of electricity) consumed per 100 km are provided in [Table 8.12](#) and [Table 8.13](#).

**Table 8.12: Light commercial vehicles (energy consumption per 100 km)**

Emission source	Type	Units	Pre 2010 Fleet	2010-2015 Fleet	2015-2020 Fleet	Post 2020 Fleet
Petrol	<1350 cc	Litres	8.966812	7.944049	7.522928	7.157506

Emission source	Type	Units	Pre 2010 Fleet	2010-2015 Fleet	2015-2020 Fleet	Post 2020 Fleet
Petrol	1350 - <1600 cc	Litres	9.628114	8.529923	8.077744	7.685372
Petrol	1600 - <2000 cc	Litres	12.990669	11.508942	10.898842	10.369437
Petrol	2000 - <3000 cc	Litres	13.741639	12.174256	11.528887	10.968878
Petrol	>=3000 cc	Litres	15.691921	13.902087	13.165124	12.525636
Diesel	<1350 cc	Litres	8.2994	7.352763	6.962987	6.655973
Diesel	1350 - <1600 cc	Litres	7.986627	7.075666	6.700578	6.405135
Diesel	1600 - <2000 cc	Litres	10.631949	9.419259	8.919936	8.526636
Diesel	2000 - <3000 cc	Litres	11.40018	10.099866	9.564463	9.142744
Diesel	>=3000 cc	Litres	11.543649	10.226971	9.68483	9.257804
Petrol hybrid	<1350 cc	Litres	7.079062	6.271618	5.939154	5.696209
Petrol hybrid	1350 - <1600 cc	Litres	7.601143	6.73415	6.377166	6.116304
Petrol hybrid	1600 - <2000 cc	Litres	10.255791	9.086007	8.604349	8.252383
Petrol hybrid	2000 - <3000 cc	Litres	10.848662	9.611255	9.101753	8.72944
Petrol hybrid	>=3000 cc	Litres	12.388358	10.975331	10.393519	9.968366
Diesel hybrid	<1350 cc	Litres	7.439819	6.59548	6.264289	6.016229
Diesel hybrid	1350 - <1600 cc	Litres	7.159441	6.346921	6.028212	5.7895
Diesel hybrid	1600 - <2000 cc	Litres	9.530783	8.449141	8.024869	7.707092
Diesel hybrid	2000 - <3000 cc	Litres	10.219447	9.05965	8.604721	8.263982
Diesel hybrid	>=3000 cc	Litres	10.348057	9.173663	8.71301	8.367983
PHEV (Petrol) - Petrol consumption	<1350 cc	Litres	3.704709	3.282147	3.108157	2.981016
PHEV (Petrol) - Petrol consumption	1350 - <1600 cc	Litres	3.977931	3.524205	3.337384	3.200866
PHEV (Petrol) - Petrol consumption	1600 - <2000 cc	Litres	5.367197	4.75501	4.502943	4.318747

Emission source	Type	Units	Pre 2010 Fleet	2010-2015 Fleet	2015-2020 Fleet	Post 2020 Fleet
PHEV (Petrol) - Petrol consumption	2000 - <3000 cc	Litres	5.677467	5.02989	4.763251	4.568407
PHEV (Petrol) - Petrol consumption	>=3000 cc	Litres	6.483241	5.743757	5.439275	5.216778
PHEV (Petrol) - Electricity consumption	<1350 cc	kWh	11.339051	10.086184	9.728393	9.467238
PHEV (Petrol) - Electricity consumption	1350 - <1600 cc	kWh	12.175306	10.83004	10.445862	10.165447
PHEV (Petrol) - Electricity consumption	1600 - <2000 cc	kWh	13.774926	12.252916	11.818264	11.501008
PHEV (Petrol) - Electricity consumption	2000 - <3000 cc	kWh	16.965612	15.091058	14.555728	14.164985
PHEV (Petrol) - Electricity consumption	>=3000 cc	kWh	19.831755	17.640518	17.014749	16.557996
PHEV (Diesel) - Diesel consumption	<1350 cc	Litres	3.893505	3.451634	3.278311	3.148493
PHEV (Diesel) - Diesel consumption	1350 - <1600 cc	Litres	3.746774	3.321555	3.154764	3.029838
PHEV (Diesel) - Diesel consumption	1600 - <2000 cc	Litres	4.987776	4.421717	4.199681	4.033378
PHEV (Diesel) - Diesel consumption	2000 - <3000 cc	Litres	5.348177	4.741217	4.503137	4.324817
PHEV (Diesel) - Diesel consumption	>=3000 cc	Litres	5.415483	4.800884	4.559808	4.379244
PHEV (Diesel) - Electricity consumption	<1350 cc	kWh	11.501624	10.230794	9.867874	9.602975
PHEV (Diesel) - Electricity consumption	1350 - <1600 cc	kWh	11.046929	9.826338	9.477765	9.223339
PHEV (Diesel) - Electricity consumption	1600 - <2000 cc	kWh	12.104012	10.766623	10.384695	10.105922

Emission source	Type	Units	Pre 2010 Fleet	2010-2015 Fleet	2015-2020 Fleet	Post 2020 Fleet
PHEV (Diesel) - Electricity consumption	2000 - <3000 cc	kWh	13.699983	12.186253	11.753966	11.438436
PHEV (Diesel) - Electricity consumption	>=3000 cc	kWh	16.203504	14.413157	13.901873	13.528684
Electric vehicle	<1350 cc	kWh	23.788219	21.159826	20.409216	19.861339
Electric vehicle	1350 - <1600 cc	kWh	25.5426	22.720363	21.914395	21.326113
Electric vehicle	1600 - <2000 cc	kWh	28.898447	25.705419	24.793561	24.127988
Electric vehicle	2000 - <3000 cc	kWh	35.592192	31.659563	30.536491	29.716753
Electric vehicle	>=3000 cc	kWh	41.605081	37.008079	35.695278	34.737054

**Table 8.13: Heavy goods vehicles (energy consumption per 100 km)**

Emission source	Type	Units	Pre 2010 Fleet	2010-2015 Fleet	Post 2015 Fleet
HGV diesel	<5,000 kg	Litres	16.56	15.72	15.66
HGV diesel	5,000 - 7,500 kg	Litres	18.97	18.01	17.73
HGV diesel	7,500 - 10,000 kg	Litres	23.2	22.01	21.68
HGV diesel	10,000 - 12,000 kg	Litres	27.51	26.01	25.71
HGV diesel	12,000 - 15,000 kg	Litres	31.26	29.66	29.22
HGV diesel	15,000 - 20,000 kg	Litres	36.51	35.59	35.5
HGV diesel	20,000 - 25,000 kg	Litres	48.61	47.37	47.26
HGV diesel	25,000 - 30,000 kg	Litres	57.28	52.9	52.77
HGV diesel	>=30,000 kg	Litres	57.28	55.73	55.6
HGV diesel hybrid	<5,000 kg	Litres	13.35	12.65	12.34
HGV diesel hybrid	5,000 - 7,500 kg	Litres	15.29	14.5	14.14
HGV diesel hybrid	7,500 - 10,000 kg	Litres	18.7	17.72	17.29

Emission source	Type	Units	Pre 2010 Fleet	2010-2015 Fleet	Post 2015 Fleet
HGV diesel hybrid	10,000 - 12,000 kg	Litres	22.17	21.01	20.5
HGV diesel hybrid	12,000 - 15,000 kg	Litres	25.19	23.88	23.3
HGV diesel hybrid	15,000 - 20,000 kg	Litres	33.19	32.35	32.27
HGV diesel hybrid	20,000 - 25,000 kg	Litres	44.18	43.06	42.96
HGV diesel hybrid	25,000 - 30,000 kg	Litres	51.02	49.72	49.6
HGV diesel hybrid	>=30,000 kg	Litres	53.75	52.38	52.26
HGV BEV (battery electric vehicle)	<5,000 kg	kWh	46.81	44.38	43.42
HGV BEV (battery electric vehicle)	5,000 - 7,500 kg	kWh	53.63	50.85	49.74
HGV BEV (battery electric vehicle)	7,500 - 10,000 kg	kWh	65.57	62.17	60.82
HGV BEV (battery electric vehicle)	10,000 - 12,000 kg	kWh	77.75	73.72	81.94
HGV BEV (battery electric vehicle)	12,000 - 15,000 kg	kWh	88.35	83.77	91.94

The equation used to calculate the emission factor for each GHG is:

$$\frac{\text{real-world fuel consumption} \times \text{emission conversion factor}}{100 \text{ km}}$$

Dividing by 100 gives a factor for litres (or kWh) per fuel per km. Use this with the fuel emission factors to calculate emissions per km.

We multiplied the values for fuel consumption by the emission conversion factors provided in [Table 3.3](#).

The default emission factors for freighting vehicles include the following assumptions based on Te Manatū Waka Ministry of Transport's *The New Zealand 2022 Vehicle Fleet: Data Spreadsheet*.

- Light commercial vehicles are on average 12.5 years old<sup>28</sup>, which corresponds to a 2010 year of manufacture.
- The most common engine size is 2000–3000 cc, therefore, we used a pre-2010 fleet and a 2000-3000 cc engine size for the default values.

- Heavy trucks are on average 18 years old and the most common gross vehicle mass is <7500 kg, therefore we selected a pre-2010 vehicle fleet with a gross vehicle mass of <7500 kg.
- Using the Motor Vehicle Register<sup>29</sup>, 79 per cent of goods vans/trucks and utility vehicles are diesel. Therefore diesel vehicles are assumed for the all-trucks factor.

Emission factors for freighting goods (tkm) are from the Te Manatū Waka Ministry of Transport’s presentation ‘Real-world fuel economy of heavy trucks’.<sup>30</sup>

This source provides emission factors in terms of g CO<sub>2</sub>-e/tkm, not for each of the three GHGs (see Table 8.14). Therefore, we calculated emission factors for carbon dioxide, methane and nitrous oxide based on the GHG split ratio of the fuel used, which was diesel (see Table 3.3). This ratio is applied to produce the emission factors provided in Table 8.11.

**Table 8.14: Data used to calculate the road freight (tkm) emission factor**

Truck type	Typical g CO <sub>2</sub> -e / tkm
Long-haul heavy truck	105
Urban delivery heavy truck	390
All trucks	135

### 8.2.5. Assumptions, limitations and uncertainties

The Vehicle Fleet Emissions Model historical year results have been carefully calibrated to give a total road fuel use that matches MBIE’s road fuel sales figures. The major source of uncertainty for the freighting goods emission factor is that net tonne-kilometres must be inferred from truck (RUC) returns and the Waka Kotahi NZ Transport Agency (NZTA) truck weigh-in-motion statistics.

The sources used to develop these emission factors will have inbuilt assumptions, limitations and uncertainties. To investigate these, see the documents referenced.

## 8.3. Rail freight

In New Zealand, KiwiRail owns the rail infrastructure and has provided the information to calculate the emission factor. The emission factor for freighting goods by rail is in Table 8.15.

**Table 8.15: Emission factors for rail freight**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Rail Freight</b>						
Rail Freight	tkm	0.0283586316	0.0279193069	0.0000444172	0.0003949075	

### 8.3.1. GHG inventory development

Users should collect data on the weight of goods freighted (tonnes), and the distance travelled (kilometres). For each journey, multiply the total tonnes by the total km travelled.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = tonnes of freight × km travelled
- F = emission factors in Table 8.15.

#### RAIL FREIGHT: EXAMPLE CALCULATION

During the reporting period, an entity freights 8 tonnes of materials 150 km by rail. This occurs four times in the reporting year.

To calculate tkm:  $8 \times 150 \times 4 = 4,800$  tkm

For the 8 tonnes moved 150 km by rail four times:

#### Example calculation of standard private vehicle consumption

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	$4,800 \times 0.0000444172$ kg CO <sub>2</sub> -e per tkm	0.213 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	$4,800 \times 0.0279193069$ kg CO <sub>2</sub> -e per tkm	134 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	$4,800 \times 0.0003949075$ kg CO <sub>2</sub> -e per tkm	1.90 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	$4,800 \times 0.0283586316$ kg CO <sub>2</sub> -e per tkm	136 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

### 8.3.2. Emission factor derivation methodology

KiwiRail provided the following information used to calculate the emission factors.

**Table 8.16: Information provided by KiwiRail**

Calculation component	Unit	Amount in 2024
Freight-only fuel	Litres	35,232,708.46
Freight volumes (net)	NTKs (000s)	3,342,305.39
Electricity (net) North Island Main Trunk (NIMT)	kWh	3,084,011

Note: NTK (net tonne km) is the sum of the tonnes carried multiplied by the distance travelled.

To calculate emissions from freight-only fuel, multiply the litres by the diesel emission factor in Table 3.3:

$$\begin{aligned} \text{emissions from fuel} = \\ \text{freight-only fuel} \times \text{diesel emission factor} \end{aligned}$$

To calculate emissions from electricity, multiply the net kWh by the emission factors in [Table 5.2](#) or [Table 5.3](#):

$$\begin{aligned} \text{emissions from electricity} = \text{electricity NIMT} \\ \times \text{purchased electricity emission factors} \end{aligned}$$

To calculate emissions from transmission and distribution losses from the purchased electricity, multiply the kWh by the emission factors in [Table 5.5](#):

$$\begin{aligned} \text{emissions from T\&D losses} = \\ \text{electricity NIMT} \times \begin{matrix} \text{T\&D losses for purchased} \\ \text{electricity emission factors} \end{matrix} \end{aligned}$$

Divide these total emissions by the freight volumes in tonnes to give emissions per tkm:

$$\text{emission per tkm} = \frac{\begin{aligned} &\text{fuel emissions} \\ &+ \text{electricity emissions} \\ &+ \text{T\&D losses emissions} \end{aligned}}{\text{freight volumes (net)} \times 1000}$$

### 8.3.3. Assumptions, limitations and uncertainties

The figure for net tkm includes the weight for third-party tare weight containers. KiwiRail does not own or control those containers and it is the responsibility of the customer to load and unload them. The alternative for these customers would be to transport freight by road. Therefore, these figures reflect the actual freight (including the weight of empty and loaded containers) that KiwiRail moved.

## 8.4. Air freight

In the absence of New Zealand data, we have adopted the air freight emission factors from the latest [UK Greenhouse gas reporting: Conversion factors 2024](#). These emission factors are Scope 3. Refer to [Section 7.5](#) for further guidance on radiative forcing to inform your choice of emission factor. While the radiative forcing multiplier of 1.7 used in this guidance is based on current scientific evidence and research, this figure is subject to significant uncertainty.

Emissions from aviation have both direct (CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O) and indirect (non-CO<sub>2</sub> emissions eg, water vapour, contrails, NO<sub>x</sub>) climate change effects. Two sets of emission factors for air freight are presented here; one that includes the indirect effects of non-CO<sub>2</sub> emissions and one that represents direct effects only.

The short-haul emission factor applies to international flights of less than 3,700 km. The long-haul factor applies to flights of more than 3,700 km.

Entities should include the indirect effects of non-CO<sub>2</sub> emissions when reporting air freight emissions to capture the full climate impact of their travel. However, it should be noted that there is significant scientific uncertainty around the magnitude of the indirect effect of non-CO<sub>2</sub> aviation emissions and it is an active area of research. Further information can be found in paragraphs 8.5 to 8.7 in the [2024 UK DESNZ Methodology Paper for Conversion Factors](#).

**Table 8.17: Air freight emissions without radiative forcing multiplier**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Without radiative forcing multiplier</b>					
Freight flights: Domestic	tkm	2.76015	2.73321	0.00393	0.02301
Freight flights: Long haul	tkm	0.64875	0.64327	0.00006	0.00542
Freight flights: Short haul	tkm	0.98469	0.97639	0.00008	0.00822

**Table 8.18: Air freight emissions with radiative forcing multiplier**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>With radiative forcing multiplier</b>					
Freight flights: Domestic	tkm	4.6734	4.64646	0.00393	0.02301
Freight flights: Long haul	tkm	1.09904	1.09356	0.00006	0.00542
Freight flights: Short haul	tkm	1.66816	1.65986	0.00008	0.00822

### 8.4.1. GHG inventory development

Users should collect data on the weight in tonnes of goods freighted by air and the distance travelled. For each journey, multiply the total tonnes by the total km travelled.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = tonnes of freight × km travelled
- F = appropriate emission factors in [Table 8.17](#) or [Table 8.18](#).

## AIR FREIGHT: EXAMPLE CALCULATION

During the reporting period, an entity air freights 0.5 tonnes of materials 10,000 km. This occurs six times in the reporting year. The entity decides to use emission factors with the radiative forcing multiplier applied.

To calculate tkm: 0.5 tonnes × 10,000 km × 6 times = 30,000 tkm

### Example calculation of standard private vehicle consumption

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	30,000 × 0.00006 kg CO <sub>2</sub> -e per tkm	1.80 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	30,000 × 1.09356 kg CO <sub>2</sub> -e per tkm	32,800 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	30,000 × 0.00542 kg CO <sub>2</sub> -e per tkm	163 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	30,000 × 1.09904 kg CO <sub>2</sub> -e per tkm	33,000 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

## 8.4.2. Emission factor derivation methodology

The [2024 UK DESNZ Methodology Paper for Conversion Factors](#) contains full details on the derivation of these emission factors.

## 8.4.3. Assumptions, limitations and uncertainties

As we adopted these emission factors from the UK DESNZ emissions for air freight to and from the UK, we assume the same factors apply to New Zealand. We have not considered the difference in the size of aircraft transporting domestic air freight – this limits the accuracy of these emission factors to better reflect New Zealand domestic air freight. The [2024 UK DESNZ Methodology Paper for Conversion Factors](#) goes into more detail behind the GHG conversion factors.

We included the emission factors with radiative forcing to account for additional radiative forcing from emissions arising from aircraft transport at altitude (jet aircraft).

## 8.5. Coastal and international shipping freight

We calculated the domestic coastal shipping emission factor, [Table 8.19](#) based on the findings from the Te Manatū Waka Ministry of Transport presentation ‘Real-world fuel economy of heavy trucks’,<sup>31</sup> prepared for the 2019 Transport Knowledge Conference. We adopted the international shipping emission factors from the [UK Greenhouse gas reporting: Conversion factors 2024](#).

**Table 8.19: Coastal shipping emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Domestic Coastal Freight</b>					
Container freight	tkm	0.046	0.0455782611	0.0001138579	0.000307881

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
Oil products	tkm	0.016	0.0158533082	0.0000396027	0.0001070891
Other bulk	tkm	0.03	0.0297249529	0.0000742551	0.000200792

Note: These numbers are rounded to three decimal places unless the number is significantly small.

**Table 8.20: International shipping emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>International Sea Freight</b>					
Bulk carrier: 0-9999 dwt	tkm	0.02956	0.0292	0.00001	0.00035
Bulk carrier: 10,000-34,999 dwt	tkm	0.008	0.0079	0.00000224	0.0001
Bulk carrier: 100,000-199,999 dwt	tkm	0.00304	0.003	0.00000112	0.00004
Bulk carrier: 200,000+ dwt	tkm	0.00253	0.0025	0.00000112	0.00003
Bulk carrier: 35,000-59,999 dwt	tkm	0.00577	0.0057	0.00000224	0.00007
Bulk carrier: 60,000-99,999 dwt	tkm	0.00415	0.0041	0.00000112	0.00005
Bulk carrier: Average	tkm	0.00353	0.00349	0.00000112	0.00004
Container ship: 0-999 TEU	tkm	0.03675	0.0363	0.00001	0.00044
Container ship: 1000-1999 TEU	tkm	0.0325	0.0321	0.00001	0.00039
Container ship: 2000-2999 TEU	tkm	0.02025	0.02	0.00001	0.00024
Container ship: 3000-4999 TEU	tkm	0.01681	0.0166	0.00001	0.0002
Container ship: 5000-7999 TEU	tkm	0.01681	0.0166	0.00001	0.0002
Container ship: 8000+ TEU	tkm	0.01265	0.0125	0.00000448	0.00015
Container ship: Average	tkm	0.01612	0.01592	0.00001	0.00019

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
General cargo: 0-4999 dwt	tkm	0.01407	0.0139	0.00000448	0.00017
General cargo: 0-4999 dwt 100+ TEU	tkm	0.02005	0.0198	0.00001	0.00024
General cargo: 10,000+ dwt	tkm	0.01204	0.0119	0.00000448	0.00014
General cargo: 10,000+ dwt 100+ TEU	tkm	0.01113	0.011	0.00000336	0.00013
General cargo: 5000-9999 dwt	tkm	0.016	0.0158	0.00001	0.00019
General cargo: 5000-9999 dwt 100+ TEU	tkm	0.01772	0.0175	0.00001	0.00021
General cargo: Average	tkm	0.01321	0.01305	0.00000448	0.00016
Refrigerated cargo: All dwt	tkm	0.01306	0.0129	0.00000448	0.00016
RoRo-Ferry: 0-1999 LM	tkm	0.06105	0.0603	0.00002	0.00073
RoRo-Ferry: 2000+ LM	tkm	0.05012	0.0495	0.00002	0.0006
RoRo-Ferry: Average	tkm	0.05159	0.05095	0.00002	0.00062
RoRo-Ferry: Large RoPax ferry	tkm	0.37612	0.3715	0.00012	0.0045
Vehicle transport: 0-3999 CEU	tkm	0.05832	0.0576	0.00002	0.0007
Vehicle transport: 4000+ CEU	tkm	0.0324	0.032	0.00001	0.00039
Vehicle transport: Average	tkm	0.03852	0.03805	0.00001	0.00046

Note: CEU = car equivalent unit; dwt = deadweight tonnes; LM = lanemetre; TEU = twenty-foot equivalent unit.

### 8.5.1. GHG inventory development

Users should collect data on the weight in tonnes of goods freighted, and the distance travelled. For each journey, multiply the total tonnes by the total km travelled.

Applying the equation  $E = Q \times F$ , this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = tonnes of freight × km travelled
- F = appropriate emission factors from [Table 8.19](#) or [Table 8.20](#)

### MULTIPLE FREIGHT MODES: EXAMPLE CALCULATION

An entity sends 300 kg of its product to a customer. It travels by road freight (All trucks) 50 km to the port, then 500 km by coastal shipping (container freight) to another domestic port. It is then loaded onto rail to its destination 250 km from the port.

Road freight emissions:

$$0.3 \text{ tonnes} \times 50 \text{ km} = 15 \text{ tkm}$$

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	15.0 x 0.135 kg CO <sub>2</sub> -e per tkm	2.03 kg CO <sub>2</sub> -e

Coastal shipping emissions:

$$0.3 \text{ tonnes} \times 500 \text{ km} = 150 \text{ tkm}$$

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	150.0 x 0.046 kg CO <sub>2</sub> -e per tkm	6.90 kg CO <sub>2</sub> -e

Rail freight emissions:

$$0.3 \text{ tonnes} \times 250 \text{ km} = 75 \text{ tkm}$$

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	75.0 x 0.0283586316 kg CO <sub>2</sub> -e per tkm	2.13 kg CO <sub>2</sub> -e

Total freight emissions:

$$2.03 \text{ kg CO}_2\text{-e} + 6.90 \text{ kg CO}_2\text{-e} + 2.13 \text{ kg CO}_2\text{-e} = 11.1 \text{ kg CO}_2\text{-e}$$

Note: Numbers may not add due to rounding.

## 8.5.2. Emission factor derivation methodology

We based the emission factors for coastal shipping on figures included in the Te Manatū Waka Ministry of Transport presentation 'Real world fuel economy of heavy trucks',<sup>32</sup> prepared for the 2019 Transport Knowledge Conference.

This source provides emission factors in terms of g CO<sub>2</sub>-e/tkm, not for each of the three GHGs (see Table 66). Therefore, we calculated emission factors for carbon dioxide, methane and nitrous oxide based on the GHG split ratio of the fuel used, which was heavy fuel oil. This ratio is applied to produce the emission factors provided in [Table 8.19](#).

**Table 8.21: Coastal shipping data**

Mode	Typical g CO <sub>2</sub> e/tkm
Coastal shipping (oil products)	16

Mode	Typical g CO2e/tkm
Coastal shipping (other bulk)	30
Coastal shipping (container freight)	46

For international shipping, we used the Freight Information Gathering System (FIGS)<sup>33</sup> to identify which types of ships visit New Zealand, and their average sizes. We then adopted the [UK Greenhouse gas reporting: Conversion factors 2024](#) for the relevant ships and adapted the average emission factors to reflect ship sizes visiting New Zealand.

We identified the following shipping types as visiting New Zealand:

- container ships
- reefer (refrigerated cargo ship)
- bulk carrier
- RoRo (roll-on, roll-off)
- oil/gas tanker
- vehicle carrier
- general cargo.

We used MoT's FIGS<sup>34</sup> to find out the average sizes of ships visiting New Zealand. Ships are measured in deadweight tonnes (dwt), twenty-foot equivalent unit (TEU), car equivalent unit (CEU) or lanemetre (LM).

- Bulk carrier is 36,900 dwt and therefore in the 35,000–59,999 dwt category.
- General cargo is 15,800 dwt and therefore in the 10,000+ dwt category.
- Container ship is 3,194 TEU and therefore in the 3,000–4,999 TEU category.
- Vehicle carrier (transport) is unknown and therefore the same as the UK average.
- RoRo ferry is unknown and therefore the same as the UK average.
- As there is only one emission factor for all refrigerated cargo an average was not necessary.

Emission factors for these have been adopted from the [UK Greenhouse gas reporting: Conversion factors 2024](#). Refer to that document for details on the methodology.

### 8.5.3. Assumptions, limitations and uncertainties

We assumed the New Zealand coastal shipping fleet is similar to that in the [STREAM Freight Handbook](#). These figures have a high degree of uncertainty as they are based on international data for coastal shipping.

We carried over the assumptions for the international shipping emission factors from the [2024 UK DESNZ Methodology Paper for Conversion Factors](#).

## 9. Water supply and wastewater treatment emission factors

Emissions result from energy use in water supply and wastewater treatment plants. Some treatment plants also generate emissions from the treatment of organic matter. We calculated the emission factors using data from Water New Zealand and [New Zealand's Greenhouse Gas Inventory 1990–2023](#).

### 9.1. Overview of changes since previous update

Table 9.1: Summary of changes to water supply and wastewater treatment emission factors

Domain	Emission factors	Size of change	Explanation for change
Water supply & wastewater	Average for wastewater treatment plants	+8.2%	Change is driven by the increase in the latest annual electricity factor, which is used to derive this factor.
	Water supply	+39.1% (m3) +25.4 (per capita)	Change is driven by the increase in the latest annual electricity factor, which is used to derive this emissions factor.

### 9.2. Water supply

Table 9.2 provides water supply emission factors. We calculated the factors using Water New Zealand data.

Table 9.2: Water supply emission factors

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)
<b>Water Supply</b>					
Water supply emission factors (m3)	m3	0.048549206	0.0471473099	0.0013108989	0.0000909972
Water supply emission factors (per capita)	per capita	5.464455649	5.306665243	0.1475482201	0.0102421857

#### 9.2.1. GHG inventory development

Users should collect data on cubic metres (m<sup>3</sup>) of water used, if available. In the absence of this information, the per capita emission factor can be applied.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = quantity of water used (m<sup>3</sup>) or persons using water supply (per capita)
- F = appropriate emission factors from [Table 9.2](#)

### WATER SUPPLY: EXAMPLE CALCULATION

An entity's assets have water meters. Throughout the reporting year they use 1,000 m<sup>3</sup> of water.

#### Example calculation of water supply consumption

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	1,000 x 0.0013108989 kg CO <sub>2</sub> -e per m <sup>3</sup>	1.31 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	1,000 x 0.0471473099 kg CO <sub>2</sub> -e per m <sup>3</sup>	47.1 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	1,000 x 0.0000909972 kg CO <sub>2</sub> -e per m <sup>3</sup>	0.0910 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	1,000 x 0.048549206 kg CO <sub>2</sub> -e per m <sup>3</sup>	48.5 kg CO <sub>2</sub> -e

Note: Numbers may not add due to rounding.

## 9.2.2. Emission factor derivation methodology

We adopted the Water New Zealand 2020/21 National Performance Review<sup>35</sup> methodology to calculate the water supply emission factors. The Water New Zealand review gathered data from participating water industry bodies, which represent approximately 75 per cent of New Zealand's population. 27 participants in the survey provided reliable information on the energy use of their water systems, which was used to calculate national averages. In the 2020/21 period, the operation of water supply pumps used 757 TJ of energy to supply 471 million m<sup>3</sup> of water, and treatment plants used an estimated 1130 TJ of energy in the treatment of about 409 million m<sup>3</sup> of water. This equates to a median energy intensity of 1.6 megajoules (MJ) of energy per cubic metre of water supplied and 2.8 MJ of energy per cubic metre of water treated.

We used a weighted average of participant energy use and water supply data to calculate the emission factors.

We calculated the emission factors for each gas by summing the weighted averages from each participant's data. The basic equation for each gas is as follows:

$$\frac{\text{energy use}}{\text{water supply}} \times \text{electricity emission factor} \times \text{unit conversion factor}$$

This equation gives the emissions per m<sup>3</sup> of water supplied, where the following values were used to calculate the emission factors:

- energy use = the gigajoule (GJ) of energy used by the water system that year
- water supply = m<sup>3</sup> of water supplied that year
- electricity emission factor = the relevant gas emission conversion factor (ie, CO<sub>2</sub>, N<sub>2</sub>O, CH<sub>4</sub>)
- unit conversion factor = 277.778 (converting GJ to kWh).

If entities do not know the volume of water used, they can estimate it based on a calculated per capita (per person) emission factor. To develop a per capita emission factor, we used an average of 116 m<sup>3</sup> of water per person per year, which is calculated from the following equations and information:

The first equation:

$$\text{average volume of water supplied per person} = \frac{\text{water supplied}}{\text{population served by WWTP}}$$

The second equation:

$$\begin{aligned} \text{emission factors for water supplied per capita} = \\ \text{average volume of water supplied per person} \\ \times \text{emission factors for water supplied in m}^3 \end{aligned}$$

Where the following data were used to calculate the emission factors:

- m<sup>3</sup> of water supplied nationwide is 531,000,000<sup>36</sup>
- population served by wastewater treatment plants is approximately 4.54 million.<sup>37</sup>

### 9.2.3. Assumptions, limitations and uncertainties

The data adopted from Water New Zealand do not account for emissions outside those associated with the national electricity grid, and therefore, may underestimate the total GHG emissions depending on the water supplier's facilities and processes.

The assumptions used for water supply per person are inherently uncertain and entities should only use them in the absence of water volume data. They do not account for factors such as: seasonal use of water and water-intensive activities (such as gardening, lifestyle choices and geography). Therefore, per person water supply reflects only an average of the water supply per person. Furthermore, the figure is based on a national average of water usage throughout the year and may overestimate emissions from office use per capita. This is because employees do not spend all their time in the office, and it is likely that most of their water usage will be outside working hours.

## 9.3. Wastewater treatment

We recommend that users refer directly to the Water New Zealand's guidelines<sup>38</sup> for emission factors for specific types of wastewater treatment plants. Weighted average emission factors for wastewater treatment remain in the measuring emissions guide for general use.

We converted energy use (kWh) to GHG emissions and added these to the treatment process emissions to give the total emissions from wastewater treatment in New Zealand.

We provide wastewater treatment emission factors in [Table 9.3](#) and [Table 9.4](#). Some industries produce wastewater that is particularly high in biological oxygen demand (BOD). For this reason, we developed

industrial wastewater emission factors for the meat, poultry, pulp and paper, wine and dairy sectors. Manufacturing entities in these sectors should use specific industrial wastewater factors. All other entities should use the domestic wastewater factors. Where the domestic wastewater treatment type is unknown, we suggest using the average for wastewater treatment plants (see Table 9.3).

**Table 9.3: Domestic wastewater treatment emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Domestic Wastewater</b>						
Average for wastewater treatment plants (m3)	m3 of water supplied	0.5155803686	0.0811191106	0.2059894198	0.2284718383	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively
Average for wastewater treatment plants (per capita)	per capita	47.57272418	7.484879775	19.00669313	21.08115127	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively
Septic tanks	per capita	175.2	0	149.9	25.3	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively

**Table 9.4: Industrial wastewater treatment emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Industrial Wastewater</b>						

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Dairy processing	m3 of milk	0.1022415429	0	0	0.1022415429	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively
Meat (excl poultry)	tonne of kills	52.57605571	0	50.05	2.526055714	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively
Poultry	tonne of kills	51.7323125	0	48.125	3.6073125	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively
Pulp & paper	tonne of product	11.7936	0	11.7936	0	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Wine	tonne of crushed grapes	5.79402936	0	5.79402936	0	The uncertainty for domestic and industrial wastewater methane and nitrous oxide emission factors are ±40% and ±90% respectively

### 9.3.1. GHG inventory development

Domestic water users should collect data on m<sup>3</sup> of water sent to treatment. If metered water data is not available, the per capita emission factor can be applied instead. Industrial entities can calculate the emissions using appropriate activity data and the correlating emission factors.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = quantity of water treated (m<sup>3</sup>) or persons using water facilities (per capita)
- F = appropriate emission factors from [Table 9.3](#) and [Table 9.4](#).

#### WASTEWATER: EXAMPLE CALCULATION

During the reporting period an entity uses 100 m<sup>3</sup> of water in its offices. They assume that all water is also sent to be treated. This entity also owns a winery that crushed 10 tonnes of grapes during the reporting period.

The office wastewater is domestic, therefore:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	100 x 0.2059894198 kg CO <sub>2</sub> -e per m3 of water supplied	20.6 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	100 x 0.0811191106 kg CO <sub>2</sub> -e per m3 of water supplied	8.11 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	100 x 0.2284718383 kg CO <sub>2</sub> -e per m3 of water supplied	22.8 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	100 x 0.5155803686 kg CO <sub>2</sub> -e per m3 of water supplied	51.6 kg CO <sub>2</sub> -e

The winery wastewater is industrial wastewater (wine), therefore:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	10 x 5.79402936 kg CO <sub>2</sub> -e per tonne of crushed grapes	57.9 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	10 x 0 kg CO <sub>2</sub> -e per tonne of crushed grapes	0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	10 x 0 kg CO <sub>2</sub> -e per tonne of crushed grapes	0 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	10 x 5.79402936 kg CO <sub>2</sub> -e per tonne of crushed grapes	57.9 kg CO <sub>2</sub> -e

The total wastewater emissions are:

$$51.6 \text{ kg CO}_2\text{-e} + 57.9 \text{ kg CO}_2\text{-e} = 109 \text{ kg CO}_2\text{-e}$$

Note: Numbers may not add due to rounding.

## 9.3.2. Emission factor derivation methodology

### 9.3.2.1. Domestic wastewater treatment

We derived the domestic wastewater treatment plant emission factors from the total energy use emissions in the wastewater treatment plants, and the gases emitted during the treatment process.

The emission factors for septic tanks are sourced directly from Water New Zealand (2021).

Since direct carbon dioxide emissions from wastewater treatment are biogenic, the methodologies described here for all treatment types other than septic tanks are only for methane and nitrous oxide. We calculated the emission factors using equations in the [2006 IPCC Guidelines for National Greenhouse Gas Inventories](#). Updated methodologies for some categories are available in the [2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories](#). Using updated methodologies in the 2019 Refinement would be inconsistent with [New Zealand's Greenhouse Gas Inventory 1990–2023](#) reporting at the time of publication of this guide, because this part of the inventory uses the IPCC 2006 Guidelines. The 2019 Refinement will be considered for future inventories, and the guide will be revised after the relevant National Inventory Report has been updated. The example calculations are done using AR5 GWPs.

To calculate methane emissions, first calculate the total organic product in domestic wastewater (TOW):

$$\text{total organic product in domestic wastewater} = \sum_i P_i \times \text{BOD} \times I$$

Where the following data were used to calculate the emission factors:

- $P$  = the population for wastewater treatment plant  $i$
- $i$  = type of treatment plant
- BOD = 26 (kg/capita/year) country-specific, per-capita Biological Oxygen Demand
- $I$  = the correction factor for additional industrial and commercial BOD (default 1.25 or 1 for septic tanks but varies for several sites).

Then calculate methane emissions per capita:

$$\text{methane emissions (kg CH}_4\text{ per capita)} = \frac{\text{MCF} \times \text{B}_0 \times \text{TOW} \times \text{GWP}}{\text{population served}}$$

Where the following data were used to calculate the emission factors:

- MCF = 0.02528, the weighted-average methane correction factor (MCF) for wastewater treatment plants in 2021
- B0 = 0.625, converts the BOD to maximum potential methane emissions
- TOW = the total organic product in wastewater from the equation above
- GWP = 28 (IPCC AR5), converts methane into CO<sub>2</sub>-e
- population served = the population served by all wastewater treatment plants.

To calculate methane emissions per water volume, divide methane emissions per capita by the average water volume (m<sup>3</sup>) treated per capita (101 m<sup>3</sup>).

To calculate nitrous oxide emissions from wastewater treatment plants we used two equations. The first equation calculates the amount of nitrogen per person:

$$\text{per capita nitrogen in effluent (kg N per year)} = \text{protein} \times F_{\text{NPR}} \times F_{\text{NON-CON}} \times F_{\text{IND-COM}}$$

Where the following data were used:

- protein = annual per capita protein consumption (36.135 kg per year from Beca, 2007)
- F<sub>NPR</sub> = fraction of nitrogen in protein (0.16, IPCC 2006)
- F<sub>NON-CON</sub> = factor for non-consumed protein added to the wastewater (1.4, IPCC 2006)
- F<sub>IND-COM</sub> = factor for industrial and commercial co-discharged protein into the sewer system (1.25, IPCC 2006).

Table 9.5 details the values used in the equation above.

**Table 9.5: Domestic wastewater treatment emissions calculation components**

Calculation component	Number	Additional information	Source
Population	1	This is a per-person calculation	
Per capita protein consumption	36.135	kg/year	Beca 2007, 99g/day
Fraction of N in protein	0.16		IPCC default
Fraction of non-consumption protein	1.4		IPCC default
Fraction of industrial and commercial co-discharged protein	1.25		IPCC default
N removed with sludge	0	Default is zero	IPCC default

Then the second equation calculates nitrous oxide emissions based on the result from the first equation:

$$\text{N}_2\text{O emissions (kg CO}_2\text{e per capita)} = \text{per capita nitrogen in effluent} \\ \times \text{EF}_{\text{effluent}} \times \frac{44}{28} \times \text{GWP}$$

Where the following data were used:

- per capita nitrogen in effluent = from equation above
- effluent = emission factor of 5.0e-3 kg N<sub>2</sub>O-N/kg N (IPCC 2006)
- 44/28 ratio of N<sub>2</sub>O to N<sub>2</sub>
- GWP = 265 (IPCC AR5).

Divide these emissions per capita by the average volume of water treated (96 m<sup>3</sup>) per capita to give the emissions per m<sup>3</sup>.

### 9.3.2.2. Industrial wastewater treatment

As with domestic wastewater, we derived the emission factors for industrial wastewater treatment from the total energy use emissions in the wastewater treatment plants and the gases emitted during the treatment process.

For the purpose of this guide, it is assumed there are no direct carbon dioxide emissions from the treatment of wastewater, as all carbon dioxide emissions are biogenic. Therefore, we have calculated only methane and nitrous oxide emissions.

The equation to calculate methane emissions is:

$$\text{methane emission factor (kg CO}_2\text{e t}^{-1}\text{)} = \text{mbCOD} \times \text{EF} \times \text{GWP}$$

Where:

- mbCOD = the unit biodegradable chemical oxygen demand load in kg per tonne of material processed
- EF = CH<sub>4</sub> emission factor (kg CH<sub>4</sub>/kg COD<sub>b</sub>)
- GWP = global warming potential.

The following tables detail the information used in the calculations to provide the industrial wastewater treatment emission factors.

#### Table 9.6: Industrial wastewater treatment methane emissions calculation information

Factor	Pulp and paper	Meat (excl poultry)	Poultry	Wine	Source
Biodegradable chemical oxygen demand load (kg CODb/tonne)	36	50	50	12.42	Cardno 2015
CH4 emission factor (kg CH4/kg CODb)	0.0117	0.03575	0.034375	0.016661	Cardno 2015
GWP	28	28	28	28	IPCC AR5

Sources: Cardno 2015<sup>39</sup>

It is assumed that the methods used to treat wastewater from dairy processing do not result in methane emissions.

The equation used to calculate nitrous oxide emissions is:

$$\text{nitrous oxide emission factor (kg CO}_2\text{e t}^{-1}\text{)} = \text{mbCOD} \times \text{N:COD} \times \text{EF} \times \frac{44}{28} \times \text{GWP}$$

Where:

- mbCOD = unit biodegradable COD load (kg CODb/t)
- N:COD = total nitrogen to biodegradable COD ratio
- EF = Nitrous oxide emission factor (kg N<sub>2</sub>O/kg CODb)
- 44/28 = ratio of N<sub>2</sub>O to N<sub>2</sub>
- GWP = global warming potential.

Table 9.7 details the information used in the calculations to provide the industrial wastewater treatment emission factors. Note that for dairy processing, users should first convert the quantity of milk to tonnes using a density factor of 1.031 tonnes per m<sup>3</sup>.

**Table 9.7: Industrial wastewater treatment nitrous oxide emissions calculation information**

Factor	Dairy processing	Meat (excl poultry)	Poultry	Source
Biodegradable chemical oxygen demand load (kg CODb/tonne)	2	50	50	Cardno 2015
Total N: biodegradable COD ratio	0.044	0.09	0.09	Cardno 2015
Nitrous oxide emission factor (kg N <sub>2</sub> O/kg CODb)	0.00279	0.001348	0.001925	Cardno 2015

Factor	Dairy processing	Meat (excl poultry)	Poultry	Source
GWP	265	265	265	IPCC AR5

Based on the Cardno report<sup>40</sup> we assume that there are no nitrous oxide emissions from the methods used to process wastewater from the wine and pulp and paper industries.

### 9.3.3. Assumptions, limitations and uncertainties

We calculated these emission factors on the best available data using industry-wide sources and international default factors where appropriate. As the wastewater emissions include electricity emissions, the same electricity emissions uncertainties carry through. [Table 9.8](#) details the uncertainties with this source category.

**Table 9.8: Uncertainties with wastewater treatment emission source category**

Emission Source	Uncertainty in activity data	Uncertainty in emission factors
Domestic and industrial CH4	10%	40%
Domestic and industrial N2O	10%	90%

# 10. Materials and waste emission factors

## 10.1. Overview of changes since previous update

Table 10.1: Summary of changes to materials and waste emission factors

Domain	Emission factors	Size of change	Explanation for change
Waste	Municipal solid waste	-12.3%	The change to municipal solid waste emission factors is due to a reduction in the assumed proportion of landfill gas composed of methane in the model used for calculating these emissions factors.
	Non-municipal solid waste	New emissions factors	The 2025 Greenhouse Gas Inventory introduced a new set of emissions factors to calculate non-municipal waste emissions, with the categories aligned to the Waste to Landfill emissions factors. The 2025 Measuring Emissions Guide has been updated to reflect these new categories. * These emissions factors were corrected on 11 June 2025.

## 10.2. Construction materials

In June 2023, BRANZ published version 3 of its CO<sub>2</sub>NSTRUCT dataset<sup>41</sup>. These emissions are indirect (Scope 3) if the entity does not own or control the facilities making the materials.

We recommend that users refer directly to the free CO<sub>2</sub>NSTRUCT dataset for emission factors for construction materials. The dataset provides embodied greenhouse gas and energy values for building materials including concrete, glass, timber, and metals, as well as products such as bathroom and kitchen fittings.

The CO<sub>2</sub>NSTRUCT dataset takes emission factors from EPDs for construction products and is regularly updated. Users could also check the EPD Australasia platform<sup>42</sup> for any interim updates to emission factors.

Other useful sources for construction emission factors include the Waka Kotahi New Zealand Transport Agency’s Project Emissions Estimation Tool (PEET),<sup>43</sup> which can be used to estimate GHG emissions in the early stages of a land transport infrastructure project.

The Ministry of Business, Innovation and Employment’s [Building for Climate Change Programme \(BfCC\)](#) has been set up to reduce emissions from constructing and operating buildings, and to make sure buildings are

prepared for the future effects of climate change. Through the BfCC programme, MBIE is leading the Building and Construction Sector policy for New Zealand's Emissions Reduction Plan, setting out policies and strategies to meet the Government's emission budget.

Users should note that in the [GHG Protocol](#), construction materials are classified as Scope 3, Category 1: *Purchased goods and services*. Buildings are classified as Scope 3, Category 2: *Capital goods*, which includes the upstream or cradle-to-gate emissions associated with the production of capital goods, such as construction materials. These can form a large proportion of an entity's GHG inventory.

## 10.3. Waste disposal

Waste disposal emissions account only for the GHG emitted from end-of-life waste disposal. Currently, this guide covers emissions from waste-to-landfill for municipal and non-municipal landfills, as well as biological treatment (composting and anaerobic digestion).

The units of emissions are kg CO<sub>2</sub>-e per kg of material. The anaerobic decomposition of organic waste in landfills generates methane. Entities should adjust inventories to account for the landfills that collect and destroy landfill gas. Where methane is collected and destroyed by flaring or combustion to generate energy, the carbon dioxide emitted from the combustion process is regarded as part of the natural carbon cycle. Biogenic carbon dioxide, which is part of the natural carbon cycle, is absorbed by living organic matter and released at the end of its life and is not included in these emission factors since it has no net effect on greenhouse gases.

Emission factors for anaerobic digestion and composting are reported as forms of biological treatment of waste.

The type, age, design, engineering, and management practices of the landfill influences the GHG conversion factor, based on whether there is a methane gas collection system.

**Table 10.2: Description of landfill types**

Landfill type	Description
Municipal (class 1) landfills with gas recovery	Municipal, well-managed landfill where a landfill gas recovery system is installed. Some of the CH <sub>4</sub> produced during the organic decomposition of waste is captured and destroyed.
Municipal (class 1) landfills without gas recovery	Municipal, well-managed landfill where all the CH <sub>4</sub> produced during organic decomposition of waste escapes into the atmosphere, apart from that which is oxidised inside the landfill.
Non-municipal (class 2-5) landfills	Non-municipal landfills that accept a broader range of wastes where the CH <sub>4</sub> produced during organic decomposition of waste escapes into the atmosphere.

[Appendix C](#) includes a list of class 1 landfills with gas recovery.

If entities are interested in calculating the emissions from transporting waste materials, they could do so by independently accounting for the distance travelled, using freight emission factors (see [Section 8.2](#)).

We calculated the waste-to-landfill emission conversion factors based on [New Zealand's Greenhouse Gas Inventory 1990–2023](#). [Table 10.3](#), [Table 10.4](#) and [Table 10.5](#) show the factors.

**Table 10.3: Waste disposal to municipal (class 1) landfills with gas recovery**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Waste to Landfill - With Gas Recovery</b>						
Known Composition: Waste - Food	kg	0.59136	0	0.59136	0	40%
Known Composition: Waste - Garden	kg	0.48384	0	0.48384	0	40%
Known Composition: Waste - Nappies	kg	0.21504	0	0.21504	0	40%
Known Composition: Waste - Other (Inert)	kg	0	0	0	0	40%
Known Composition: Waste - Paper	kg	0.86016	0	0.86016	0	40%
Known Composition: Waste - Sludge	kg	0.1344	0	0.1344	0	40%
Known Composition: Waste - Textile	kg	0.43008	0	0.43008	0	40%
Known Composition: Waste - Wood (combined)	kg	0.333312	0	0.333312	0	40%
Known Composition: Wood (treated)	kg	0.05376	0	0.05376	0	40%
Known Composition: Wood (untreated)	kg	0.75264	0	0.75264	0	40%
Unknown Composition: General waste	kg	0.2033083817	0	0.2033083817	0	Not quantified
Unknown Composition: Office waste	kg	0.58404864	0	0.58404864	0	Not quantified

**Table 10.4: Waste disposal to municipal (class 1) landfills without gas recovery**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Waste to Landfill - Without Gas Recovery</b>						
Known Composition: Waste - Food	kg	1.848	0	1.848	0	40%
Known Composition: Waste - Garden	kg	1.512	0	1.512	0	40%
Known Composition: Waste - Nappies	kg	0.672	0	0.672	0	40%
Known Composition: Waste - Other (Inert)	kg	0	0	0	0	40%
Known Composition: Waste - Paper	kg	2.688	0	2.688	0	40%
Known Composition: Waste - Sludge	kg	0.42	0	0.42	0	40%
Known Composition: Waste - Textile	kg	1.344	0	1.344	0	40%
Known Composition: Waste - Wood (combined)	kg	1.0416	0	1.0416	0	40%
Known Composition: Wood (treated)	kg	0.168	0	0.168	0	40%
Known Composition: Wood (untreated)	kg	2.352	0	2.352	0	40%
Unknown Composition: General waste	kg	0.6353386927	0	0.6353386927	0	Not quantified
Unknown Composition: Office waste	kg	1.825152	0	1.825152	0	Not quantified

**Table 10.5: Waste disposal to non-municipal (class 2-5) landfills**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Non-Municipal Waste</b>						
Known Composition: Waste - Average for non-municipal solid waste	kg	0.1539413904	0	0.1539413904	0	IPCC uncertainties
Known Composition: Waste - Food	kg	0.4312	0	0.4312	0	IPCC uncertainties
Known Composition: Waste - Green Waste	kg	0.3528	0	0.3528	0	IPCC uncertainties
Known Composition: Waste - Inert (all other waste)	kg	0	0	0	0	IPCC uncertainties
Known Composition: Waste - Nappies	kg	0.1568	0	0.1568	0	IPCC uncertainties
Known Composition: Waste - Paper	kg	0.6272	0	0.6272	0	IPCC uncertainties
Known Composition: Waste - Sludge	kg	0.196	0	0.196	0	IPCC uncertainties
Known Composition: Waste - Textiles	kg	0.3136	0	0.3136	0	IPCC uncertainties
Known Composition: Waste - Wood (timber)	kg	0.2352	0	0.2352	0	IPCC uncertainties

**Table 10.6: Biological treatment of waste emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Biological Treatment of Waste</b>						

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Anaerobic digestion	kg	0.0224	0	0.0224	0	IPCC uncertainties
Composting	kg	0.1756	0	0.112	0.0636	IPCC uncertainties

### 10.3.1. GHG inventory development

There are two methodologies that entities can follow for calculating waste emissions.

1. Where composition of waste is known.
2. Where composition of waste is unknown.

The choice of methodology depends on the knowledge of waste composition. It is preferable to know the composition of waste as it allows more accurate calculation of emissions. The example calculations are done using IPCC AR5 GWPs.

Users should collect data on the quantity (kg) and type of waste disposed.

Applying the equation  $E = Q \times F$  this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = quantity of waste disposed (kg)
- F = appropriate emission factors from [Table 10.3](#) to [Table 10.5](#).

#### WASTE DISPOSAL: EXAMPLE CALCULATION

A hotel produces waste in its kitchen, guest rooms and garden. They send it to the regional landfill, which is known to have landfill gas recovery.

If the waste comprises 150 kg food waste, 50 kg general waste from guest rooms and 60 kg of garden waste, the hotel calculates emissions as follows:

Emission Source	Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Food Waste	Total CO <sub>2</sub> -e emissions	150 x 0.59136 kg CO <sub>2</sub> -e per kg	88.7 kg CO <sub>2</sub> -e
General Waste	Total CO <sub>2</sub> -e emissions	50 x 0.2033083817 kg CO <sub>2</sub> -e per kg	10.2 kg CO <sub>2</sub> -e
Garden Waste	Total CO <sub>2</sub> -e emissions	60 x 0.48384 kg CO <sub>2</sub> -e per kg	29.0 kg CO <sub>2</sub> -e

The hotel's total emissions from waste disposal are:

$$88.7 \text{ kg CO}_2\text{-e} + 10.2 \text{ kg CO}_2\text{-e} + 29.0 \text{ kg CO}_2\text{-e} = 128 \text{ kg CO}_2\text{-e}$$

Note: Numbers may not add due to rounding

### 10.3.2. Emission factor derivation methodologies

We broke down data derived from the National Inventory Report into the categories in [Table 10.7](#) alongside their proportion of the waste to landfills.

**Table 10.7: Composition of waste sent to NZ landfills**

Component	Estimated composition of waste to municipal landfills	Estimated composition of waste to non-municipal landfills
Food	9.0120 %	0.0000 %
Green Waste	5.7424 %	3.0000 %
Paper	5.8899 %	5.4671 %
Wood (timber)	12.6230 %	32.7028 %
Textiles	5.0214 %	9.9298 %
Nappies	2.4711 %	0.0500 %
Sludge	1.9224 %	0.4757 %
Inert (all other waste)	57.3176 %	48.3746 %

**Note:** The composition for municipal landfills: sold waste: updated 2020, sludge added Oct 2021, wood updated Feb 2023. The composition of non municipal solid waste: new composition obtained from surveys and levy data for the 2025 submission of the GHG inventory. Columns may not total to 100% due to rounding.

Substances such as plastics, metals and glass are inert because their decomposition in landfills does not directly produce GHG emissions. Only waste that contains degradable organic carbon produces methane as it breaks down.

We provide no methodology for nitrous oxide emissions from waste disposal because the IPCC<sup>44</sup> has found them to be insignificant.

### 10.3.3. When composition of waste is known

If the composition of waste is known, use the specific emission factors for each waste stream based on kilograms of waste produced.

We generated emission factors for each waste category, following a simplification of the IPCC First Order Decay model.

$$\begin{aligned} \text{emission factor}(\text{kg CO}_2\text{e t}^{-1}) = \\ \text{DOC} \times \text{DOC}_f \times F \times \text{MCF} \\ \times \text{conversion} \times (1 - \text{oxidation}) \times (1 - \text{recovery}) \times \text{GWP} \end{aligned}$$

Where:

- DOC = amount of degradable organic carbon in the material
- DOC<sub>f</sub> = fraction of DOC that degrades in landfill
- F = fraction of CH<sub>4</sub> in the gas that is generated inside the landfill
- MCF = methane correction factor (the extent that the landfill is anaerobic)
- conversion = conversion of carbon to methane (molecular weight ratio CH<sub>4</sub>/C)

- recovery = fraction of methane recovered where landfill gas systems are in place, otherwise use 0
- oxidation = oxidation factor of methane that degrades before being emitted
- GWP = global warming potential of methane.

We used the waste information from the National Inventory Report to develop solid waste emission factors for voluntary reporting.

**Table 10.8: Information on managed solid waste**

Waste category	DOC	DOCf	F	MCF	Conversion	Ox	R
Food	0.157143	0.7	0.5	1	1.333333	0.1	0.68
Garden	0.160714	0.56	0.5	1	1.333333	0.1	0.68
Paper	0.32	0.5	0.5	1	1.333333	0.1	0.68
Wood (combined)	0.442857	0.14	0.5	1	1.333333	0.1	0.68
Wood (treated)	0.434783	0.023	0.5	1	1.333333	0.1	0.68
Wood (untreated)	0.429448	0.326	0.5	1	1.333333	0.1	0.68
Textile	0.16	0.5	0.5	1	1.333333	0.1	0.68
Nappies	0.08	0.5	0.5	1	1.333333	0.1	0.68
Sludge	0.05	0.5	0.5	1	1.333333	0.1	0.68
Other (Inert)	0	0	0.5	1	1.333333	0.1	0.68

**Note:** R only applies for landfills with gas recovery.

**Table 10.9: Information on non-municipal solid waste**

Waste category	DOC	DOCf	F	MCF	Conversion	Ox	R
Food	0.11	0.5	0.5	0.42	1.333333	0	0
Green Waste	0.09	0.5	0.5	0.42	1.333333	0	0
Paper	0.16	0.5	0.5	0.42	1.333333	0	0
Wood (timber)	0.06	0.5	0.5	0.42	1.333333	0	0
Textiles	0.08	0.5	0.5	0.42	1.333333	0	0
Nappies	0.04	0.5	0.5	0.42	1.333333	0	0
Sludge	0.05	0.5	0.5	0.42	1.333333	0	0

Waste category	DOC	DOCf	F	MCF	Conversion	Ox	R
Inert (all other waste)	0	0.5	0.5	0.42	1.333333	0	0

### 10.3.4. When composition of waste is unknown

If the composition is unknown, select a general waste or an office waste default emission factor.

We based the default emission factor for general waste on national average composition data from [New Zealand's Greenhouse Gas Inventory 1990–2023](#) (see [Table 10.7](#)).

The following is the composition used to calculate office waste data.

**Table 82: Composition of typical office waste**

**Table 10.10: Composition of typical office waste**

Waste component	Percentage
Food	20.8%
Paper	53.6%
Inert	25.6%

### 10.3.5. Determining with or without landfill gas recovery

If you do not know whether the waste goes to a landfill with or without gas recovery, either find out whether the receiving landfill has gas recovery, or choose one of the conservative assumptions. Nationwide, 96 per cent of waste disposed to municipal (class 1) landfills in 2022 went to a landfill with gas recovery.

We recommend checking [Appendix C](#) to identify if your region has a landfill with gas capture. If it does, use the value with gas recovery. To be more certain, consider contacting the local council or disposal operator and ask them what landfill the waste is disposed to and if it has gas recovery. If it is not possible to identify the landfill, choose one of the following conservative assumptions:

- For a conservatively high estimate of emissions from waste disposed to a municipal (class 1) landfill, assume it is disposed to a landfill without gas recovery.
- For a conservatively low estimate of emissions avoided by diverting waste away from a municipal (class 1) landfill, assume it is from a landfill with gas capture.

### 10.3.6. Composting and anaerobic digestion

We calculated emission factors for composting and anaerobic digestion using IPCC default emission factors as shown in [Table 10.11](#).

**Table 10.11: IPCC default data used to calculate composting and anaerobic digestion**

Calculation component	Composting CH4	Composting N2O	Anaerobic digestion CH4	Anaerobic digestion N2O
EF (kg gas/kg waste)	0.004	0.00024	0.0008	Assumed negligible
GWP (IPCC AR5)	28	265	28	265.0
EF (CO <sub>2</sub> -e) (kg CO <sub>2</sub> -e/kg waste)	0.112	0.0636	0.0224	0

From this table the combined emission factors are calculated as follows:

Treatment method	Emission factor (kg CO <sub>2</sub> -e / kg waste)
Composting	0.1756
Anaerobic digestion	0.0224

### 10.3.7. Assumptions, limitations and uncertainties

The uncertainties for emission factors used in methane emissions from managed municipal landfills is  $\pm 40$  per cent. This is consistent with the estimates in the [IPCC Guidelines. New Zealand's Greenhouse Gas Inventory 1990–2023](#) states that “the emission factor uncertainty is set at this level, while better-quality parameters are used in this category, most of the parameters are based on international data and are not site specific”.

If an entity has an advanced diversion system (to recycling and composting) then using the ‘average waste’ category in the methodology will overestimate emissions. If an entity has no diversion system, then it could underestimate emissions.

The default emission factor for average waste is based on national average composition data from [New Zealand's Greenhouse Gas Inventory 1990–2023](#). Only waste to municipal and non-municipal landfills is considered.

The nitrous oxide emissions associated with anaerobic digestion are assumed to be negligible.

The guide does not cover methodologies to determine emissions from solid waste incineration, as we assume emissions are negligible at the individual entity level.

# 11. Agriculture, forestry and other land-use emission factors

This category covers emissions produced by land use, land-use change and forestry (LULUCF), livestock enteric fermentation, manure management, agricultural soils and fertiliser use.

We selected the emission factors below, based on appropriate available data and the professional opinions of the Ministry for Primary Industries (MPI) and the Ministry for the Environment.

- Land use, land-use change and forestry:
  - forest growth
  - forest harvest and deforestation.
- Agriculture:
  - enteric fermentation from livestock
  - manure management from livestock
  - agricultural soils from livestock
  - fertiliser and lime use.

Users should disclose in their inventories if they include animals grazing on land not owned by the entity.

Entities looking for a more accurate farm-based estimate of their agricultural emissions are encouraged to use the [Ag Matters on-farm emissions calculator](#).

The list of tools approved by the He Waka Eke Noa programme can be found here: [Know your number – Ag Matters](#).

## 11.1. Overview of changes since previous update

**Table 11.1: Summary of changes to agriculture, forestry, and other land-use emission factors**

Domain	Emission factors	Size of change	Explanation for change
Agriculture	Livestock factors	Between -10.5% to -36.2% for Deer and Swine and Non-dairy cattle +5.5% to +7%	The change is due to population, emissions calculation methodologies and how populations are accounted detailed in the New Zealand's latest Greenhouse Gas Inventory (1990–2023). In summary: <ul style="list-style-type: none"> <li>- Population decrease for deer</li> <li>- Revisions in how different populations of poultry have been accounted for</li> <li>- New methodology to calculation emissions for deer and swine</li> </ul>

Domain	Emission factors	Size of change	Explanation for change
Forestry	Land use growth and change	+40.6% (removals) +181.3% (land-use change)	Change is due to an update to the expected harvest age of hardwoods, based on new LUCAS research for the New Zealand's latest Greenhouse Gas Inventory (1990–2023). The expected harvest age has changed as follows: - Pinus radiata from 22 years to 23 years - Other Softwoods from 28 years to 29 years - All hardwoods from 13 years to 24 years

## 11.2. Land use, land-use change and forestry

### 11.2.1. Overview of the sector

GHG emissions from vegetation and soils due to human activities are reported in the LULUCF sector. This guide provides emission factors related to forest growth, forest harvest and deforestation only. The term LULUCF is used for consistency with [New Zealand's Greenhouse Gas Inventory 1990–2023](#).

The LULUCF sector is responsible for both emitting GHGs (primarily carbon dioxide) to the atmosphere (emissions; ie, through harvesting and deforestation) and removing GHG from the atmosphere (removals; ie, through vegetation growth). Most emissions reported in this sector are due to forestry activities such as harvest operations in production forests, and most removals are due to forest growth.

The basis for the methods given here is that the flux of carbon dioxide to and from the atmosphere is due to the changes in carbon stocks in vegetation and soils. When emissions exceed removals, LULUCF is a 'net source', and emissions are positive. When removals exceed emissions, LULUCF is a 'net sink', and emissions are negative.

The guide provides methods to estimate the carbon stock change (or flux) that occurs from forestry activities during the applicable measurement period. We do not include methods to estimate carbon stock changes in non-forest vegetation, soils, harvested wood products, or for the associated nitrous oxide and methane emissions. For more detail, see [New Zealand's Greenhouse Gas Inventory 1990–2023](#).

In line with [ISO 14064-1:2018](#) and the [GHG Protocol](#), entities should consider LULUCF emissions and removals if they have forest land within their measurement boundary, or own land that has been deforested during the measurement period.

Entities with LULUCF emissions should calculate and report these separately from direct and indirect (Scope 1, 2 and 3) emissions.

The emission factors in this guide are New Zealand-specific, derived from national averages.

Although the main aim of this section of the guide is to estimate stock changes from forestry activities, it can also be used to estimate the total carbon stored for a given forest type in a given area. This can help entities

understand the potential impact of some forestry activities on emissions, and how to manage land use for carbon.

## 11.2.2. LULUCF emission factors

### 11.2.2.1. Planted forests

Two approaches are provided to calculate emissions and removals from planted forests. Only one approach can be used, a mixture of approaches is not permitted.

#### **Approach one** – Carbon stock change accounting

This approach estimates the net emissions and removals from forest growth and harvesting each year. The emission factors are based on the Land Use and Carbon Analysis System (LUCAS) national forest inventory.

Annual removals from forest growth (Table 11.2) are estimated as an average annual increment over the average duration of their harvesting cycle. Emission factors are provided for three species groups (*Pinus radiata*, other softwoods, and all hardwoods) and an 'all planted forest category' (this represents an average emission factor for New Zealand's entire planted forest estate, regardless of species). The 'all planted forest' category may only be used when a species breakdown is not available. The emission factors for forest harvesting and deforestation are provided as the entire loss of carbon on the clearing of planted forest at the average harvest (Table 11.3).

Note, if species-specific emission factors for forest growth are used, the corresponding species-specific values must be used to account for land-use change emissions. Likewise, if the 'all planted forest' emission factor is used for forest growth, then it must also be used to account for land-use change emissions.

#### **Approach two** – Averaging accounting

The averaging approach estimates carbon dioxide removals from the planting of new forests (afforestation) up to the age when they reach their average long-term carbon stock. The long-term average carbon stock represents the average carbon that is estimated to be stored over successive rotations.

Once carbon dioxide removals have been measured up to the long-term average carbon stock, there are assumed to be no further emissions or removals (ie, no additional removals from growth nor emissions from harvest). The averaging approach requires information on forest plant date, so the age can be determined, and for the forest to be in its first rotation (forests that have been replanted following a harvesting event are beyond their long-term average carbon stock).

The age that the long-term average carbon stock is reached varies depending on species. Any forest that is over the age<sup>45</sup> of the long-term average carbon stock is considered to have an emission factor of zero. The 'all planted forest' category may only be used when a species breakdown is not available (this represents an average emission factor for New Zealand's planted forest estate, regardless of species).

This approach broadly aligns with the approach that New Zealand will take to account for emissions and removals in post-1989 planted forest under the Paris Agreement. The averaging approach can be appropriate for participants who can identify the plant date of their forests, or do not have data available on harvesting activity.

Deforestation emissions are still accounted in full, as in approach one (Table 11.3). If species-specific emission factors for forest growth are used, the corresponding species-specific values must be used to account for land-use change emissions. Likewise, if the 'all planted forest' emission factor is used for forest growth, then it must also be used to account for land-use change emissions.

## AFFORESTATION, DEFORESTATION AND HARVESTING

Afforestation occurs when forest is established on previously unforested land.

Deforestation occurs when forest land is cleared for another land use.

Harvesting refers to the harvest of planted production forests for timber, which are then replanted.

### 11.2.2.3. Natural forests

The emission factors for natural forest growth (shown in [Table 11.2](#)) are based on the LUCAS national forest inventory. We provide separate emission factors if the forest is pre-1990 or post-1989. Post-1989 regenerating natural forest is regenerating natural forest that was established from 1 January 1990 onwards. Pre-1990 natural forest is natural forest that was established before 1 January 1990. Within pre-1990 natural forest we provide separate emission factors if the forest is tall or regenerating ie, recovering from conversion from another land use, logging, or other anthropogenic disturbance.

The emission factor for natural forest deforestation (shown in [Table 11.3](#)) is based on the average stock at the national level, calculated from the LUCAS national forest inventory.

**Table 11.2: LULUCF forest growth emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	Uncertainties
<b>Forest Growth - Natural Forests</b>			
Post-1989 Regenerating natural forest	ha	-7973.151769	44.50%
Pre-1990 Regenerating natural forest	ha	-1566.381483	119.50%
Pre-1990 Tall natural forest	ha	0	
<b>Forest Growth - Planted Forests - Approach One: Stock Change Accounting</b>			
All Planted forests	ha	-35140.43872	13.30%
All hardwoods	ha	-26256.37156	146.80%
Other softwoods	ha	-29956.33595	23.30%
Pinus radiata	ha	-36565.42587	13.30%
<b>Forest Growth - Planted Forests - Approach Two: Averaging Accounting</b>			
All hardwoods - First rotation (Age 24 years and under)	ha	-26256.37156	146.80%
All planted forest above the long-term average age	ha	0	
All planted forests - First rotation (Age 23 years and under)	ha	-35140.43872	13.30%

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	Uncertainties
Other Softwoods – First rotation (Age 29 years and under)	ha	-29956.33595	23.30%
Pinus radiata – First rotation (Age 23 years and under)	ha	-36565.42587	13.20%

**Table 11.3: LULUCF land-use change emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	Uncertainties
<b>Land-Use Change – Natural Forests</b>			
Post-1989 Regenerating natural forest: Deforestation	ha	141350	27%
Pre-1990 Regenerating natural forest: Deforestation	ha	280293.6545	27.20%
Pre-1990 Tall natural forest: Deforestation	ha	898577.3185	21%
<b>Land-Use Change – Planted Forests – Approach One: Stock Change Accounting</b>			
All Planted forests: Harvest or Deforestation	ha	983932.2842	21.80%
All hardwoods: Harvest or Deforestation	ha	787691.1469	147.80%
Other Softwoods: Harvest or Deforestation	ha	1198254.189	29.10%
Pinus radiata: Harvest or Deforestation	ha	1023831.924	21.80%
<b>Land-Use Change – Planted Forests – Approach Two: Averaging Accounting</b>			
All Planted forests: Deforestation	ha	983932.2842	21.80%
All Planted forests: Harvest	ha	0	
All hardwoods: Deforestation	ha	787691.1469	147.80%
All hardwoods: Harvest	ha	0	
Other Softwoods: Deforestation	ha	1198254.189	29.10%
Other Softwoods: Harvest	ha	0	
Pinus radiata: Deforestation	ha	1023831.924	21.80%
Pinus radiata: Harvest	ha	0	

### 11.2.3. GHG inventory development

To calculate LULUCF emissions, entities need activity data on each forest type, the area harvested and any changes to forested land within the organisational boundary for the measurement period. Different forest types have different emission factors, while deforestation and harvest rates change over time.

First, determine the type of forest and the area it covers. The New Zealand parameters to define a forest are a minimum area of 1 hectare, the potential to reach a minimum height of 5 metres and a minimum crown cover of 30 per cent.

#### Forest types

**1. Pre-1990 Tall natural forest:** Areas, that on 1 January 1990, were and presently comprise of mature indigenous forest.

**2. Pre-1990 Regenerating natural forest:** Areas, that on 1 January 1990, were and presently comprise of indigenous and naturally occurring vegetation, including broadleaved hardwood shrubland, mānuka-kānuka and other woody shrubland, with potential to reach forest definition under its current management. This category represents mid-successional regenerating forest.

**3. Post-1989 Regenerating natural forest:** Areas of forest established from 1 January 1990 onwards that comprise of indigenous tree species arising from natural regeneration. This category represents early successional regenerating forest and may also have some exotic species present.

**4. Planted forest:** plantations of forest species mainly used for forestry, including:

- radiata pine (*Pinus radiata*)
- softwoods, such as Douglas fir (*Pseudotsuga menziesii*)
- hardwoods, such as eucalypts (*Eucalyptus* spp.)
- other planted species (with potential to reach  $\geq 5$  metre height at maturity in situ).

The following information can be used to determine natural forest types:

1. The LUCAS Land Use Map<sup>46</sup> can provide area by vegetation type (pre-1990 and post-1989 natural forest) at 1990, 2008, 2012, 2016 and 2020. It requires geospatial expertise to analyse and extract the data by region. This is free to use and supports users in monitoring changes in their own land management practices.
2. The New Zealand Land Cover Database (LCDB)<sup>47</sup> provides multi-temporal land cover. This can be used to differentiate between tall and regenerating pre-1990 natural forest. Two LCDB classes are classified as tall forest; indigenous forest and broadleaved indigenous hardwoods. All other categories are classified as regenerating forest. It requires geospatial expertise to analyse and extract the data for sub-national analysis.
3. Alternatively, if the age of the forest is known or can be estimated, this can be used to determine forest type:
  - Planted from 1990 onwards: post-1989 regenerating natural forest
  - Planted before 1990: pre-1990 regenerating natural forest
  - Planted 100 or more years ago: pre-1990 tall natural forest

Entities will also need records of forest harvest and deforestation activities (including area in ha) to calculate the emissions from LULUCF. Sources of this information include:

- corporate or farm records for enterprises and entities
- geospatial analysis of the property or region

- the LUCAS Land Use Map
- the New Zealand Land Cover Database (LCDB)
- if Approach two (averaging) is used, the planting date (to calculate the age of the forest) will be required as well as evidence that the forest is in its first rotation.

Using the sources detailed above to gather information on the land use, forest type and size, entities can apply the equation  $E = Q \times F$ :

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = area of land (ha)
- F = appropriate emission factors (for land use) from Table 11.2 and Table 11.3.

## LAND USE, LAND-USE CHANGE AND FORESTRY: EXAMPLE CALCULATIONS 1

### Using Approach one for planted forest

An entity owns 4 ha of land: 3 ha are planted forest (*Pinus radiata*) and 1 ha is pre-1990 regenerating natural forest. During the reporting year the entity harvested the planted forest for timber.

3 ha of planted forest (*Pinus radiata*) were harvested, therefore:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	3 x 1023831.924 kg CO <sub>2</sub> -e per ha	3,070,000 kg CO <sub>2</sub> -e

The removals (expressed as a negative) for the regenerating pre-1990 natural forest are:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	1 x -1566.381483 kg CO <sub>2</sub> -e per ha	-1,570 kg CO <sub>2</sub> -e

The sum of the above totals is the total emissions:

- -1,570 kg CO<sub>2</sub>-e + 3,070,000 kg CO<sub>2</sub>-e = 3,070,000 kg CO<sub>2</sub>-e

Note: Negative emissions are a carbon sink. Numbers may not add due to rounding.

## LAND USE, LAND-USE CHANGE AND FORESTRY: EXAMPLE CALCULATIONS 2

### Using Approach two for planted forest:

An entity owns 40 ha of land: 10 ha are planted forest (Other softwoods) below the long-term average age (< 28 years since time of planting), 20 ha are planted forest (*Pinus radiata*) above the long-term average age (> 22 years since time of planting) and a further 10 ha of planted forest (*Pinus radiata*) were deforested during the reporting year.

The removals (expressed as negative) for the 10 ha of planted forest (Other softwoods) below the long-term average age (< 28 years) are:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	10 x -29956.33595 kg CO <sub>2</sub> -e per ha	-300,000 kg CO <sub>2</sub> -e

The removals (expressed as a negative) for the 20 ha of planted forest (*Pinus radiata*) above the long-term average (> 22 years):

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	20 x 0 kg CO <sub>2</sub> -e per ha	0 kg CO <sub>2</sub> -e

The emissions for the 10 ha of planted forest (*Pinus radiata*) that were deforested:

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	10 x 1023831.924 kg CO <sub>2</sub> -e per ha	10,200,000 kg CO <sub>2</sub> -e

The sum of the above totals is the total emissions:

- 0 kg CO<sub>2</sub>-e kg CO<sub>2</sub>-e + -300,000 kg CO<sub>2</sub>-e kg CO<sub>2</sub>-e + 10,200,000 kg CO<sub>2</sub>-e kg CO<sub>2</sub>-e = 9,940,000 kg CO<sub>2</sub>-e kg CO<sub>2</sub>-e

Note: Negative emissions are a carbon sink. Numbers may not add due to rounding.

### 11.2.3.1. Activity data uncertainties

National mapping uncertainty for natural forest and pre-1990 planted forest land is ±5 per cent, and ±8 per cent for post-1989 forest land. As the guide combines planted forest types, we recommend applying the higher uncertainty of ±8 per cent.

### 11.2.4. Emission factor derivation methodology

As stated above, two approaches are provided to calculate emissions and removals from planted forests. Approach one (carbon stock change accounting) estimates the net emissions and removals from forest growth and harvesting each year. Approach two (averaging accounting) estimates carbon dioxide removals from the planting of new forests up to the age when they reach their average long-term carbon stock.

The approach to emissions estimation for Approach one (stock change accounting) follows this equation:

$$\Delta C = \sum_{ij} [A_{ij} \cdot (C_i - C_L)_{ij}]$$

Where:

- $\Delta C$  = carbon stock change in the pool, kg C yr<sup>-1</sup>
- A = area of land, ha
- ij = corresponds to forest type, and whether harvested or deforested
- C<sub>i</sub> = rate of gain of carbon, kg C ha<sup>-1</sup> yr<sup>-1</sup>
- C<sub>L</sub> = rate of loss of carbon, kg C ha<sup>-1</sup> yr<sup>-1</sup>.

The area refers to the area of each forest type and whether harvested or deforested in the year of the inventory. The general approach is to multiply the area data by an emission factor to provide the source or sink estimates.

Quantities of carbon can be expressed in different ways: carbon (C), CO<sub>2</sub> and CO<sub>2</sub>-e.

To convert carbon to carbon dioxide, multiply by <sup>44</sup>/<sub>12</sub> (ie, the molecular conversion of carbon to carbon dioxide).

The approach to emissions estimation for Approach two (averaging) follows this equation:

$$\Delta C = \sum [A_{a_i} \cdot C_i + A_b \cdot 0]$$

Where:

- $\Delta C$  = carbon stock change in the pool, kg C yr<sup>-1</sup>
- $i$  = corresponds to forest type
- $A_a$  = area of planted forest land that is yet to reach its long-term average, ha
- $A_b$  = area of planted forest land that has reached its long-term average, ha
- $C_i$  = rate of gain of carbon, kg C ha<sup>-1</sup> yr<sup>-1</sup>.

### 11.2.5. Assumptions, limitations and uncertainties

The emission factors are based on national average data, therefore the uncertainties will not necessarily reflect sub-national circumstances.

For natural forests, deforestation and harvest loss, data are based on the national stock average, which comes from the most recent carbon stock inventory for these forests.

The emission factors for planted forest (Approach one) and natural forest in this guide are based on [New Zealand's Greenhouse Gas Inventory 1990–2023](#). These emission factors represent the most up-to-date forestry data available. ETS look-up tables are another source of emission factors; however, these are not updated as frequently. The emission factors are based on national average data and the uncertainties will not necessarily reflect sub-national circumstances and will not be exactly the same as the ETS estimates of carbon sequestration which differentiate based on tree age, region and to a limited extent, the species. Selection of the most appropriate emission factor should be guided by the requirements of the intended use and by the user's inventory. The age at which the long-term average carbon stock is reached for planted forests (Approach two) are based on Wakelin et al.<sup>48</sup>

## 11.3. Agriculture

Emissions from agriculture are produced in several ways. This section includes emissions from enteric fermentation, manure management and fertiliser use, in more detail:

- Methane from enteric fermentation is a by-product of ruminant digestion. Cattle and sheep are the largest sources of methane in this sector.
- Storing and treating manure, including spreading it onto pasture, produces methane and nitrous oxide.
- Losses also occur from manure that is deposited by livestock directly onto pasture.
- Applying nitrogen (urea-sourced or synthetic) fertiliser onto land produces nitrous oxide and carbon dioxide (urea) emissions.
- Applying lime and dolomite fertilisers results in carbon dioxide emissions.

If an entity directly owns and manages livestock, agriculture emission sources are direct (Scope 1).

Note the livestock emissions you calculate using these implied emission factors are intended to be an approximate estimate of emissions only, and are based on the average per-animal biological emissions of New Zealand's main farmed livestock categories. Implied emission factors are provided per head of livestock type per year.

Actual livestock emissions for an individual farm will differ depending on a number of factors, including live-weights, productivity, and feed quality. Entities looking for a more accurate farm-based estimate of their agricultural emissions are encouraged to use alternative GHG calculator tools. The list of tools approved by the He Waka Eke Noa programme can be found here: [Know your number – Ag Matters](#).

### 11.3.1. Enteric fermentation

Enteric fermentation is the process by which ruminant animals produce methane through digesting feed. We provide emission factors for dairy cattle, non-dairy cattle, sheep and deer and other minor livestock categories in [Table 11.4](#).

**Table 11.4: Implied emission factors from enteric fermentation**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Enteric fermentation</b>						
Alpaca and llama	per head	224	0	224	0	15.5%
Dairy cattle	per head	2649.341783	0	2649.341783	0	15.5%
Deer	per head	547.67824	0	547.67824	0	15.5%
Goats	per head	250.9684211	0	250.9684211	0	15.5%
Horses	per head	504	0	504	0	15.5%
Mules and asses	per head	280	0	280	0	15.5%
Non-dairy cattle	per head	1950.136772	0	1950.136772	0	15.5%
Sheep	per head	348.6860224	0	348.6860224	0	15.5%
Swine	per head	25.58803376	0	25.58803376	0	15.5%

**Note:** For enteric fermentation there is no estimation for poultry.

#### 11.3.1.1. GHG inventory development

Entities should collect data on the number and type of livestock as at 30 June during the measurement period (regardless of whether the period is a calendar or financial year) to calculate emissions from enteric fermentation.

Applying the equation  $E = Q \times F$ , this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = number of animals (per head per livestock type)
- F = appropriate emission factors from [Table 11.4](#).

#### ENTERIC FERMENTATION: EXAMPLE CALCULATION

An entity owns 2,400 sheep and 210 dairy cows on 30 June during the reporting period. They graze on land owned by the entity.

##### Cow calculations

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	210 x 2649.341783 kg CO <sub>2</sub> -e per per head	556,000 kg CO <sub>2</sub> -e

##### Sheep calculations

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	2,400 x 348.6860224 kg CO <sub>2</sub> -e per per head	837,000 kg CO <sub>2</sub> -e

The sum of the above totals is the total emissions:

- 556,000 kg CO<sub>2</sub>-e kg CO<sub>2</sub>-e + 837,000 kg CO<sub>2</sub>-e kg CO<sub>2</sub>-e = 1,390,000 kg CO<sub>2</sub>-e kg CO<sub>2</sub>-e

Note: Numbers may not add due to rounding.

### 11.3.1.2. Emission factor derivation methodology

New Zealand's Greenhouse Gas Inventory 1990–2023 publishes total emissions for enteric fermentation per livestock type, along with population numbers. The Ministry for Primary Industries (MPI) publishes total emissions for enteric fermentation per livestock type, along with population numbers. MPI supplied these same data for the creation of implied emission factors. We used this information to calculate the emission factors based on the following equation:

$$\text{implied emission factor per animal} = \frac{\text{enteric fermentation}}{\text{population}}$$

Note that the emission factors are based on data supplied for [New Zealand's Greenhouse Gas Inventory 1990–2023](#).

To ensure consistency, entities should report their population of livestock as at 30 June, regardless of the measurement period.

MPI defines non-dairy cattle as beef breeds of cattle, including dairy-beef, as well as any beef breeding stock.

**Table 11.5: Enteric fermentation figures per livestock type**

Animal	2023 Population	Total Emissions (kt CH <sub>4</sub> )
Dairy cattle	5,884,628	556.799673
Non-dairy cattle	3,654,032	254.495078
Sheep	24,359,267	303.347711
Deer	741,599	14.50563

Note: kt = kilotonne.

Source: Based on figures from the Agricultural Inventory Model used in New Zealand's Greenhouse Gas Inventory 1990–2023.

Animal	2023 Population	Total Emissions (kt CH <sub>4</sub> )
Swine	249,796	0.228278
Goats	78,055	0.699619
Horses	31,184	0.561312
Alpaca and llama	15,443	0.123546
Mules and asses	1,500	0.015

Note: kt = kilotonne.

Source: Based on figures from the Agricultural Inventory Model used in New Zealand's Greenhouse Gas Inventory 1990–2023.

Note: NE = Not Estimated

#### 11.3.1.2.1. Alternative methods and tools

There are alternative calculating tools, such as [AgMatters](#), [OverseerFM](#), or the [B+LNZ GHG calculator](#). The implied emission factors in this guide may differ from other tools because of the different in-built assumptions and limitations. It is up to the user to assess the appropriateness of alternative tools.

#### 11.3.1.3. Assumptions, limitations and uncertainties

[New Zealand's Greenhouse Gas Inventory 1990–2023](#) details the uncertainties associated with the activity data used to calculate the emission factors.

The level of uncertainty with enteric fermentation emissions is ±15.5 per cent.

### 11.3.2. Manure management emission factors

Manure management refers to the process of managing the excretion of livestock, particularly when they are not on paddocks, but also covers losses from manure that is deposited by livestock directly onto pasture, and it is distinct from losses from agricultural soils. The storage and treatment of manure produces GHG emissions. We provide the manure management emission factors in [Table 11.6](#)

**Table 11.6: Implied emission factors from manure management**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Manure management</b>						
Alpaca and llama	per head	2.768109758	0	2.768109758	0	CH <sub>4</sub> 20%
Dairy cattle	per head	270.5410534	0	258.1241169	12.41693647	CH <sub>4</sub> 20% / N <sub>2</sub> O 100%
Deer	per head	7.350482966	0	7.350482966	0	CH <sub>4</sub> 20%
Goats	per head	5.6	0	5.6	0	CH <sub>4</sub> 20%
Horses	per head	65.52	0	65.52	0	CH <sub>4</sub> 20%

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Mules and asses	per head	30.8	0	30.8	0	CH4 20%
Non-dairy cattle	per head	26.77655214	0	26.77655214	0	CH4 20%
Poultry	per head	1.379144023	0	0.8043110825	0.5748329402	CH4 20% / N2O 100%
Sheep	per head	3.773736061	0	3.773736061	0	CH4 20%
Swine	per head	186.8957777	0	165.4103901	21.48538759	CH4 20% / N2O 100%

### 11.3.2.1. GHG inventory development

Entities should collect data on the number and type of livestock as at 30 June during the measurement period (regardless of whether the period is a calendar or financial year) to calculate emissions from manure management.

Applying the equation  $E = Q \times F$ , this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = number of animals (per head per livestock type)
- F = appropriate emission factors from [Table 11.6](#).

#### MANURE MANAGEMENT: EXAMPLE CALCULATION

An entity owns 2,400 sheep and 210 dairy cows on 30 June during the reporting period. They graze on land owned by the entity.

##### Cow calculations

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	210 x 258.1241169 kg CO <sub>2</sub> -e per per head	54,200 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	210 x 0 kg CO <sub>2</sub> -e per per head	0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	210 x 12.41693647 kg CO <sub>2</sub> -e per per head	2,610 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	210 x 270.5410534 kg CO <sub>2</sub> -e per per head	56,800 kg CO <sub>2</sub> -e

##### Sheep calculations

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	2,400 x 3.773736061 kg CO <sub>2</sub> -e per per head	9,060 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	2,400 x 0 kg CO <sub>2</sub> -e per per head	0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	2,400 x 0 kg CO <sub>2</sub> -e per per head	0 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	2,400 x 3.773736061 kg CO <sub>2</sub> -e per per head	9,060 kg CO <sub>2</sub> -e

The sum of the above totals is the total emissions:

- CH<sub>4</sub> emissions: 54,200 kg CO<sub>2</sub>-e + 9,060 kg CO<sub>2</sub>-e = 63,300 kg CO<sub>2</sub>-e
- N<sub>2</sub>O emissions: 2,610 kg CO<sub>2</sub>-e + 0 kg CO<sub>2</sub>-e = 2,610 kg CO<sub>2</sub>-e
- Total kg CO<sub>2</sub>-e = 65,900 kg CO<sub>2</sub>-e

Note: Numbers may not add due to rounding.

### 11.3.2.2. Emission factor derivation methodology

We calculated the implied emission factors from figures in the Agricultural Inventory Model, used in New Zealand's Greenhouse Gas Inventory 1990-2023. MPI provided the data in [Table 11.7](#).

**Table 11.7: Manure management source data**

Animal	2023 Population	Methane from manure management (kt CH <sub>4</sub> )	Nitrous oxide from manure management (kt N <sub>2</sub> O)
Dairy cattle	5,884,628	54.248729	0.275732
Non-dairy cattle	3,654,032	3.494371	0
Sheep	24,359,267	3.283052	0
Deer	741,599	0.194683	0
Swine	249,796	1.475673	0.020253
Goats	78,055	0.015611	0
Horses	31,184	0.072971	0
Alpaca and llama	15,443	0.001527	0
Mules and asses	1,500	0.00165	0
Poultry	18,100,783	0.519952	0.039264

Note: kt = kilotonne. Source: The Agricultural Inventory Model used in New Zealand's Greenhouse Gas Inventory 1990-2023.

**Table 11.8: Data used to calculate manure management emissions from dairy cattle**

Animal	2023 Population	Methane from manure management (kg CH <sub>4</sub> )	Nitrous oxide from manure management (kg N <sub>2</sub> O)
Dairy cattle	5,884,628	54,248,728.78	275,732.272

#### MANURE MANAGEMENT: EMISSION FACTORS CALCULATIONS FOR LIVESTOCK TYPE

We calculated the manure management emission factors for each type of livestock as follows:

1. Convert the units to kg of GHG.
2. Divide by population to generate kg of GHG per head (ie, per animal).
3. Calculate kg CO<sub>2</sub>-e/animal by multiplying each GHG by the IPCC AR5 100-year GWP.

Emission factors for dairy cattle ([Table 11.8](#)) were calculated as follows

- Methane emissions =  $54,248,728.78 \div 5,884,628 = 9.22$  kg CH<sub>4</sub> per head
- Nitrous oxide emissions =  $275,732.27 \div 5,884,628 = 0.0469$  kg N<sub>2</sub>O per head

- Total kg CO<sub>2</sub> equivalent = (9.2187 x 28) + (0.0469 x 265) = 271 kg CO<sub>2</sub>-e per head

Note: The final emission factor derived in this example calculation is marginally different to the emission factor in Table 11.6 due to rounding.

### 11.3.2.3. Assumptions, limitations and uncertainties

New Zealand's Greenhouse Gas Inventory 1990–2023 states that the major sources of uncertainty in emissions from manure management are the accuracy of emission factors for manure management system distribution, the activity data on the livestock population and the use of the various manure management systems. Based on the IPCC methodologies<sup>49</sup>, the uncertainty factor for methane emissions is ±20 per cent and for nitrous oxide emissions ±100 per cent, although different uncertainty values are reported in the New Zealand Inventory. New Zealand's Greenhouse Gas Inventory 1990–2023 details the assumptions and limitations of these data.

### 11.3.2.4. Alternative methods of calculation

See Section 11.3.1.2.1

## 11.3.3. Agricultural soils

Agricultural soils emit nitrous oxide due to the addition of nitrogen to soils through manure, dung and urine. The guide provides implied emission factors for the impact of common agricultural livestock categories on soil in Table 11.9.

**Table 11.9: Implied emission factors from agricultural soils**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Agricultural soils (live stock)</b>						
Alpaca and llama	per head	61.49372337	0	0	61.49372337	54.1%
Dairy cattle	per head	413.1963493	0	0	413.1963493	54.1%
Deer	per head	63.36053096	0	0	63.36053096	54.1%
Goats	per head	61.5008015	0	0	61.5008015	54.1%
Horses	per head	290.9211643	0	0	290.9211643	54.1%
Mules and asses	per head	129.592155	0	0	129.592155	54.1%
Non-dairy cattle	per head	260.4338891	0	0	260.4338891	54.1%
Poultry	per head	1.525834657	0	0	1.525834657	54.1%
Sheep	per head	29.00377682	0	0	29.00377682	54.1%
Swine	per head	26.93509614	0	0	26.93509614	54.1%

### 11.3.3.1. GHG inventory development

Entities should collect data on the number and type of livestock they had as at 30 June during the measurement period.

Applying the equation  $E = Q \times F$ , this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = number of animals (per head per type)
- F = appropriate emission factors from [Table 11.9](#).

AGRICULTURAL SOILS: EXAMPLE CALCULATION		
An entity owns 2,400 sheep and 210 dairy cows on 30 June during the reporting period. They graze on land owned by the entity.		
<b>Cow calculations</b>		
Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	210 x 0 kg CO <sub>2</sub> -e per per head	0 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	210 x 0 kg CO <sub>2</sub> -e per per head	0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	210 x 413.1963493 kg CO <sub>2</sub> -e per per head	86,800 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	210 x 413.1963493 kg CO <sub>2</sub> -e per per head	86,800 kg CO <sub>2</sub> -e
<b>Sheep calculations</b>		
Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	2,400 x 0 kg CO <sub>2</sub> -e per per head	0 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	2,400 x 0 kg CO <sub>2</sub> -e per per head	0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	2,400 x 29.00377682 kg CO <sub>2</sub> -e per per head	69,600 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	2,400 x 29.00377682 kg CO <sub>2</sub> -e per per head	69,600 kg CO <sub>2</sub> -e
The sum of the above totals is the total emissions:		
<ul style="list-style-type: none"> <li>• 86,800 kg CO<sub>2</sub>-e + 69,600 kg CO<sub>2</sub>-e = 156,000 kg CO<sub>2</sub>-e</li> </ul>		
Note: Numbers may not add due to rounding.		

### 11.3.3.2. Emission factor derivation methodology

We calculated the emission factors from the Agricultural Inventory Model, used in [New Zealand's Greenhouse Gas Inventory 1990–2023](#). These data are in [Table 11.10](#).

**Table 11.10: Agricultural soils source data**

Animal	2023 Population	Agricultural soils emissions (kg N2O)
Dairy cattle	5,884,628	9,175,497.382855
Non-dairy cattle	3,654,032	3,591,070.809994
Sheep	24,359,267	2,666,078.27735
Deer	741,599	177,313.609052
Swine	249,796	25,389.733111

Animal	2023 Population	Agricultural soils emissions (kg N <sub>2</sub> O)
Goats	78,055	18,114.887024
Horses	31,184	34,234.285234
Alpaca and llama	15,443	3,583.63164
Mules and asses	1,500	733.5405
Poultry	18,100,783	104,221.894431

### 11.3.3.3. Assumptions, limitations and uncertainties

New Zealand's Greenhouse Gas Inventory 1990–2023 details the uncertainties associated with the activity data used to calculate the implied emission factors.

### 11.3.4. Fertiliser use

The use of fertiliser produces GHG emissions. Nitrogen fertiliser breaks down to produce nitrous oxide and carbon dioxide (urea). Limestone and dolomite fertilisers break down to produce carbon dioxide. [New Zealand's Greenhouse Gas Inventory 1990–2023](#) reports the total emissions from fertiliser using New Zealand-specific emission factors. We used emission factors supplied by MPI to develop emission factors for:

- the nitrogen content of non-urea nitrogen fertiliser
- the nitrogen content of urea nitrogen fertiliser not coated with urease inhibitor
- the nitrogen content of urea nitrogen fertiliser coated with urease inhibitor
- limestone
- dolomite.

In line with the reporting requirements of [ISO 14064-1:2018](#) and the [GHG Protocol](#), we provide implied emission factors to allow separate calculation of carbon dioxide, methane and nitrous oxide. [Table 11.11](#) lists the nitrogen fertiliser, limestone and dolomite emission factors. Note for nitrogen fertilisers, the input amounts are expressed in terms of the nitrogen component of fertiliser only. [Table 11.12](#) lists example products for the different fertiliser types.

**Table 11.11: Nitrogen fertiliser, limestone and dolomite emission factors**

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
<b>Fertiliser use</b>						
Dolomite	kg	0.4766666667	0.4766666667	0	0	CO <sub>2</sub> –50% to 0%
Limestone	kg	0.3608	0.3608	0	0	CO <sub>2</sub> –50% to 0%
Non-urea nitrogen fertiliser	kg N	4.836817857	0	0	4.836817857	54%

Emissions Source	Unit	kg CO <sub>2</sub> -e/unit	CO <sub>2</sub> /unit (kg CO <sub>2</sub> -e)	CH <sub>4</sub> /unit (kg CO <sub>2</sub> -e)	N <sub>2</sub> O/unit (kg CO <sub>2</sub> -e)	Uncertainties
Urea nitrogen fertiliser coated with urease inhibitor	kg N	4.536270756	1.594202898	0	2.942067857	CO <sub>2</sub> -50% to 0% / N <sub>2</sub> O 54%
Urea nitrogen fertiliser not coated with urease inhibitor	kg N	4.723663613	1.594202898	0	3.129460714	CO <sub>2</sub> -50% to 0% / N <sub>2</sub> O 54%

Note: The emission factors for nitrogen fertilisers are expressed in terms of the nitrogen component of fertiliser only. For example, if an entity applies 100 kg of urea fertiliser, which contains 46 per cent nitrogen, the input amount for the calculation would be 46 kg of nitrogen.

**Table 11.12: Examples of different categories of fertilisers**

Fertiliser type	Example product
Non-urea nitrogen	Diammonium phosphate
Urea nitrogen not coated with urease inhibitor	Nrich urea
Urea nitrogen coated with urease inhibitor	Agrotain, Sustain, N-Protect

### 11.3.4.1. GHG inventory development - nitrogen

Entities should collect data on quantity of nitrogen (in kg) of fertiliser used in the reporting period by type. Applying the equation  $E = Q \times F$ , this means:

- E = emissions from the emissions source in kg CO<sub>2</sub>-e per year
- Q = type of fertiliser used (in kg)
- F = appropriate emission factors from [Table 11.11](#).

FERTILISER USE: EXAMPLE CALCULATION		
An entity uses 80 kg of dolomite and 50 kg of nitrogen from non-urea nitrogen fertiliser in the reporting year.		
<b>Dolomite calculations</b>		
Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	80 x 0 kg CO <sub>2</sub> -e per kg	0 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	80 x 0.4766666667 kg CO <sub>2</sub> -e per kg	38.1 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	80 x 0 kg CO <sub>2</sub> -e per kg	0 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	80 x 0.4766666667 kg CO <sub>2</sub> -e per kg	38.1 kg CO <sub>2</sub> -e
<b>Non-urea nitrogen fertiliser calculations</b>		
Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	50 x 0 kg CO <sub>2</sub> -e per kg N	0 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	50 x 0 kg CO <sub>2</sub> -e per kg N	0 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	50 x 4.836817857 kg CO <sub>2</sub> -e per kg N	242 kg CO <sub>2</sub> -e

Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
Total CO <sub>2</sub> -e emissions	50 x 4.836817857 kg CO <sub>2</sub> -e per kg N	242 kg CO <sub>2</sub> -e
The sum of the above totals is the total emissions:		
<ul style="list-style-type: none"> <li>38.1 kg CO<sub>2</sub>-e + 242 kg CO<sub>2</sub>-e = 280 kg CO<sub>2</sub>-e</li> </ul>		
Note: Numbers may not add due to rounding.		

LIME USE: EXAMPLE CALCULATION		
An entity uses 1,600 kg of lime fertiliser in the reporting year.		
Lime use calculations		
Gas	Calculation	Emissions (kg CO <sub>2</sub> -e)
CH <sub>4</sub> emissions	1,600 x 0 kg CO <sub>2</sub> -e per kg	0 kg CO <sub>2</sub> -e
CO <sub>2</sub> emissions	1,600 x 0.3608 kg CO <sub>2</sub> -e per kg	577 kg CO <sub>2</sub> -e
N <sub>2</sub> O emissions	1,600 x 0 kg CO <sub>2</sub> -e per kg	0 kg CO <sub>2</sub> -e
Total CO <sub>2</sub> -e emissions	1,600 x 0.3608 kg CO <sub>2</sub> -e per kg	577 kg CO <sub>2</sub> -e
Note: Numbers may not add due to rounding.		

### 11.3.4.2. Emission factor derivation methodology

MPI provided data on the quantified direct and indirect GHG emissions produced per tonne of nitrogen in fertiliser in [Table 11.13](#). The final emission factor is the sum of adding the three N<sub>2</sub>O columns and multiplying this by the global warming potential of N<sub>2</sub>O, which is 265. This sum is then added to the value in the CO<sub>2</sub> column on the far right, to produce the final emission factors seen in [Table 11.11](#).

**Table 11.13: Data used to calculate nitrogen fertiliser emission factors**

Fertiliser type	Direct emissions of N <sub>2</sub> O (kg N <sub>2</sub> O/kg of N in fertiliser)	Indirect emissions volatilisation (kg N <sub>2</sub> O/kg of N in fertiliser)	Indirect emissions-leaching (kg N <sub>2</sub> O/kg of N in fertiliser)	CO <sub>2</sub> emissions from urea (kg CO <sub>2</sub> /kg of N in fertiliser)
Non-urea nitrogen	0.015714	0.001571	0.000966	
Urea nitrogen not coated with urease inhibitor	0.009271	0.001571	0.000966	1.594203
Urea nitrogen coated with urease inhibitor	0.009271	0.000864	0.000966	1.594203

The input parameters used to calculate the limestone and dolomite emission factors are in [Table 11.14](#), where the final emission factor is the product of multiplying these three inputs.

**Table 11.14: Data used to calculate limestone and dolomite emission factors**

Fertiliser type	Concentration factor	Emission factor	Molecular conversion CO <sub>2</sub>
Limestone	0.82	0.12	3.666667

Fertiliser type	Concentration factor	Emission factor	Molecular conversion CO <sub>2</sub>
Dolomite	1	0.13	3.666667

It is assumed that the lime applied to soils is 100 per cent pure calcium carbonate. The correction factor in the Table 11.14 accounts for the impurities of the lime, as well as its moisture content. No correction factor is required for dolomite.

Table 11.15 provides the full list of parameters used to calculate the emission factors for nitrogen fertiliser, lime and dolomite.

**Table 11.15: Parameters for calculating emissions from fertilisers**

Description	Value	Source	Reference
Current processor level emissions factor	5.72	Climate Change (Agriculture Sector) Regulations 2010	
Direct emissions factor non-urea-N	0.01	Based on Kelliher and de Klein, 2006	Landcare Research and AgResearch. Unpublished. 2006. Report prepared for the Ministry for the Environment. Review of New Zealand's Fertiliser Nitrous Oxide Emission Factor (EF1) Data.
Direct emissions urea-N	0.0059	Based on van der Weerden et al 2016 (new in 2017 NIR)	van der Weerden T, Cox N, Luo J, Di HJ, Podolyan A, Phillips RL, Saggar S, de Klein CAM, Ettema P, Rys G. 2016. Refining the New Zealand nitrous oxide emission factor for urea fertiliser and farm dairy effluent. Agriculture Ecosystems & Environment 222: 133–137.
FracGASnfert (UI)	0.055	Saggar (2013)	Saggar S, Singh J, Giltrap DL, Zaman M, Luo J, Rollo M, Kim D-G, Rys G, van der Weerden TJ. 2013. Quantification of reductions in ammonia emissions from fertiliser urea and animal urine in grazed pastures with urease inhibitors for agriculture inventory: New Zealand as a case study. Science of the Total Environment 465: 136–146.

Description	Value	Source	Reference
FracGASnfert (non-UI)	0.1	Sherlock et al (2008)	Sherlock RR, Jewell P, Clough T. 2008. Review of New Zealand Specific FracGASM and FracGASF Emissions Factors. Report prepared for the Ministry of Agriculture and Forestry by Landcare Research and AgResearch. Wellington: Ministry of Agriculture and Forestry.
Volatilisation emission factor (EF4)	0.01	2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 4, table 11.3	IPCC. 2006c. Eggleston HS, Buendia L, Miwa K, Ngara T, Tanabe K (eds). 2006 IPCC Guidelines for National Greenhouse Gas Inventories. Volume 4. Agriculture, Forestry and Other Land Use. IPCC National Greenhouse Gas Inventories Programme. Japan: Institute for Global Environmental Strategies for IPCC.
FracLeach - Cropland	0.1	Welten et al. (2021)	
FracLeach - Grassland*	0.08	Welten et al. (2021)	Welten B, Mercer G, Smith C, Sprosen M, Ledgard S. 2021. Refining estimates of nitrogen leaching for the New Zealand agricultural greenhouse gas inventory. Report prepared for the Ministry for Primary Industries.
Leaching emission factor (EF5)	0.0075	2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 4, table 11.3	
Urea emissions factor (CO2 component)	0.2	2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 4, section 11.4.2	
Emissions factor for limestone	0.12	2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 4, section 11.3.2	
Emissions factor for dolomite	0.13	2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 4, section 11.3.2	

Description	Value	Source	Reference
Lime purity (national default)	0.82	Thomson et al (2021)	Thomson BC, Ward KR, Muir PD. 2021. Purity of agricultural lime and dolomite used in New Zealand. Final report prepared for the Ministry for Primary Industries. Wellington: Ministry for Primary Industries.
Dolomite purity (national default)	1	2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 4, chapter 11	
Correction factor for impurities	0.82	Thomson et al (2021)	
N content of urea	0.46	Agriculture inventory model	
Molecular conversion CO <sub>2</sub>	3.666667		
Molecular conversion N <sub>2</sub> O	1.571429		
GWP100 N <sub>2</sub> O	265	IPCC (AR5)	

#### 11.3.4.3. Assumptions, limitations and uncertainties

New Zealand's Greenhouse Gas Inventory 1990–2023 uses the IPCC (2006) Tier 1 methodology when default emission factors are used, which assume conservatively that all carbon in the fertilisers is emitted as carbon dioxide into the atmosphere.

There is no country-specific methodology on carbon dioxide emissions from urea application for New Zealand. Emissions associated with the application of urea are estimated using a Tier 1 methodology (equation 11.13; IPCC, 2006) using the default emission factor for carbon conversion of 0.2.

## A. Appendix — Derivation of fuel emission factors

### A.1. A.1 The importance of calorific value

The energy content of fuels may vary within and between fuel types. Emission factors are therefore commonly expressed in terms of energy units (eg, tonnes CO<sub>2</sub>-e/TJ) rather than mass or volume. This generally provides more accurate emissions estimates. Converting to emission factors expressed in terms of mass or volume (eg, kg CO<sub>2</sub>-e/litre) requires an assumption around which default calorific value should be used.

It is therefore useful to show how we derived the per-activity unit (eg, kg CO<sub>2</sub>-e/litre) emission factors, and which calorific values we used. It is important to note that if you can obtain fuel use information in energy units, or know the specific calorific value of the fuel you are using, you can calculate your emissions more accurately.

Note that we have used gross calorific values.

### A.2. A.2 Methane and nitrous oxide emission factors used in this guide

Although carbon dioxide emissions remain constant regardless of how a fuel is combusted, methane and nitrous oxide emissions depend on the precise nature of the activity in which the fuel is being combusted. The emission factors for methane and nitrous oxide therefore vary depending on the combustion process. Table A2 shows the default methane and nitrous oxide emission factors (expressed in energy units) used in this guide. The calculation in [Section 3.2.3](#) shows how we converted these to a per activity unit (eg, kg CO<sub>2</sub>-e/kg) emission factors.

Note that we have used gross emission factors.

### A.3. A.3 Oxidation factors used in this guide

We sourced all oxidation factors from MBIE and the 2006 [IPCC Guidelines for National Greenhouse Gas Inventories](#). Oxidation factors have only been applied to the carbon dioxide emission factors and have not been applied to the methane and nitrous oxide emission factors.

### A.4. A.4 Sector classification

Emission factors for stationary fuels are provided for the residential, commercial and industrial sectors. Consumption statistics for these sectors are based on Australian and New Zealand Standard Industrial Classification (ANZSIC) codes, with the mappings shown in table A1 used for industrial and commercial sectors.

**Table A.1: Mappings used for industrial and commercial sectors**

Sector	ANZSIC codes
Agriculture, Forestry, and Fishing	A
Mineral and Petroleum Extraction	B
Food Processing	C11, C12
Textiles and Leather	C13
Wood, Pulp, Paper and Printing	C14, C15, C16
Chemicals	C17, C18, C19
Non-metallic minerals	C20
Basic Metals	C21, C22
Mechanical/Electrical Equipment	C23, C24
Industry unallocated	C25, D26, D27, D28, D29
Building and Construction	E
Commercial	F-G, H, I, J, K-N, O, P, Q, R-S

Table sourced from MBIE Energy Statistics Sources and Methods, November 2021 v1.2

For more information on ANZSIC 2006, see Stats NZ's Ariā system: [www.aria.stats.govt.nz/aria/](http://www.aria.stats.govt.nz/aria/)

The gross GHG emission factors for fuels are taken from Annex 4 of New Zealand's Greenhouse Gas Inventory 1990–2023.

## A.5. A.5 Reference data

Table A.2: Underlying data used to calculate fuel emission factors

Emission source	User	Unit	Calorific Value (MJ/unit)	T CO <sub>2</sub> /TJ (After Oxidation)	T CH <sub>4</sub> /TJ	T N <sub>2</sub> O/TJ
Biofuel and Biomass						
Wood - Chips	Manufacturing	kg	15.15	89.466667	0.024	0.0032
Wood - Pellets	Manufacturing	kg	18.988	89.466667	0.024	0.0032
Wood - Green	Manufacturing	kg	8.888	89.466667	0.024	0.0032
Wood - Chips	Commercial	kg	15.15	89.466667	0.24	0.0032
Wood - Pellets	Commercial	kg	18.988	89.466667	0.24	0.0032
Stationary Combustion of Fuels						
Coal - Bituminous	Residential	kg	29.590041	89.13	0.285	0.001425

Emission source	User	Unit	Calorific Value (MJ/unit)	T CO <sub>2</sub> /TJ (After Oxidation)	T CH <sub>4</sub> /TJ	T N <sub>2</sub> O/TJ
Coal - Sub-Bituminous	Residential	kg	21.64376	91.99	0.285	0.001425
Coal - Lignite	Residential	kg	15.255589	93.11	0.285	0.001425
Coal - Bituminous	Commercial	kg	29.590041	89.13	0.0095	0.001425
Coal - Sub-Bituminous	Commercial	kg	21.64376	91.99	0.0095	0.001425
Coal - Lignite	Commercial	kg	15.255589	93.11	0.0095	0.001425
Coal - Bituminous	Industry	kg	29.590041	89.13	0.0095	0.001425
Coal - Sub-Bituminous	Industry	kg	21.64376	91.99	0.0095	0.001425
Coal - Lignite	Industry	kg	15.255589	93.11	0.0095	0.001425
Diesel	Commercial	litre	38.492092	69.203964	0.0095	0.00057
LPG	Commercial	kg	50	59.274527	0.00475	0.000095
Heavy Fuel Oil	Commercial	litre	40.739295	74.537407	0.0095	0.00057
Light Fuel Oil	Commercial	litre	40.454041	73.021372	0.0095	0.00057
Diesel	Industry	litre	38.492092	69.203964	0.00285	0.00057
LPG	Industry	kg	50	59.274527	0.00095	0.000095
Heavy Fuel Oil	Industry	litre	40.739295	74.537407	0.00285	0.00057
Light Fuel Oil	Industry	litre	40.454041	73.021372	0.00285	0.00057
Distributed natural gas	Industry	GJ		54.057909	0.0009	0.00009
Distributed natural gas	Commercial	GJ		54.057909	0.0045	0.00009
Distributed natural gas	Industry	kWh		0.194608	0.000003	0
Distributed natural gas	Commercial	kWh		0.194608	0.000016	0
Transport Fuel						
Regular Petrol	Mobile Use	litre	34.582233	66.020087	0.03135	0.0076
Premium Petrol	Mobile Use	litre	35.052833	66.223793	0.03135	0.0076
Diesel	Mobile Use	litre	38.137695	69.203964	0.003705	0.003705
LPG	Mobile Use	litre	26.54	59.274527	0.0589	0.00019
Heavy Fuel Oil	Mobile Use	litre	40.739295	74.537407	0.00665	0.0019

Emission source	User	Unit	Calorific Value (MJ/unit)	T CO <sub>2</sub> /TJ (After Oxidation)	T CH <sub>4</sub> /TJ	T N <sub>2</sub> O/TJ
Light Fuel Oil	Mobile Use	litre	40.454041	73.021372	0.00665	0.0019
Aviation fuel - Kerosene	Mobile Use	litre	36.799907	67.934018	0.000475	0.0019
Aviation gas	Mobile Use	litre	33.866778	65.891495	0.000475	0.0019

Note<sup>1</sup>: The total of each gas contribution is expressed in tonnes of gas (not CO<sub>2</sub>-e as presented elsewhere in this guidance).

Note<sup>2</sup>: The solid and gaseous fuel calorific values remain unchanged from last year. Liquid fuel calorific values were updated using the MBIE energy statistics for oil, available at [www.mbie.govt.nz/building-and-energy/energy-and-natural-resources/energy-statistics-and-modelling/energy-statistics/oil-statistics/](http://www.mbie.govt.nz/building-and-energy/energy-and-natural-resources/energy-statistics-and-modelling/energy-statistics/oil-statistics/).

Note<sup>3</sup>: The gross GHG emission factors for fuels are taken from Annex 4 of [New Zealand's Greenhouse Gas Inventory 1990-2023](#).

Note<sup>4</sup>: The assumed moisture content for wood chips, pellets and green is 25%, 6% and 56% respectively.

## B. Appendix — Alternative methods of calculating emissions from refrigerants and medical gas

This appendix outlines two screening methods (Methods B and C) to estimate emissions from refrigerant leakage when top-up information is not available. Method C is the same as Method B except that it allows the use of default refrigerant quantities as well as default leakage rates.

### B.1. B.1 Method B – Default annual leakage rate

$$E = OE \times GWP$$

Where:

- E = emissions from equipment in kg CO<sub>2</sub>-e
- OE = operation emissions, kg by gas type
- GWP = the 100-year global warming potential of the refrigerant used in equipment (Table 4.2).

$$OE = C \times ALR$$

Where:

- C = original full refrigerant charge in equipment (kg)
- ALR = the default annual leakage emission factor for equipment (%).

The type and quantity of HFC in the equipment will often be shown on the compliance plate. If not, this method requires service agents' advice for refrigerant type and full refrigerant charge of each piece of equipment.

### B.2. B.2 Method C – Default annual leakage rate and default refrigerant charge

$$E = (IE + DE + (C \times ALR)) \times GWP$$

Where:

- E = emissions from equipment in kg CO<sub>2</sub>-e

- IE = installation emissions
- C = default refrigerant charge in each piece of equipment (kg)
- ALR = default annual leakage emission factor for equipment (%)
- DE = disposal emissions (as per method B)
- GWP = the 100-year global warming potential of the refrigerant used in equipment (Table 4.2), where GWP is shown in kg CO<sub>2</sub>-e.

Table B.1 contains default refrigerant charge amounts for the New Zealand refrigeration and air-conditioning equipment stock.

**Table B.1: Default refrigerant charges for refrigeration and air-conditioning equipment**

Refrigeration unit type	Default refrigerant charge (kg)	Default leakage rate (operating-ALR)	Default leakage rate (installation-AEF)	Default leakage rate	
				Method B	Method C
Small refrigerator or freezer (<150 litres)	0.07	3%	n/a	Recommended	Acceptable
Medium refrigerator or freezer (150-300 litres)	0.11	3%	n/a	Recommended	Acceptable
Large refrigerator or freezer (>300 litres)	0.15	3%	n/a	Recommended	Acceptable
Small commercial standalone chiller (<300 litres)	0.25	8%	n/a	Acceptable	Screening method only
Medium commercial stand-alone chiller (300-500 litres)	0.45	8%	n/a	Acceptable	Screening method only
Large commercial stand-alone chiller (>500 litres)	0.65	8%	n/a	Acceptable	Screening method only
Small commercial standalone freezer (<300 litres)	0.2	8%	n/a	Acceptable	Screening method only

Refrigeration unit type	Default refrigerant charge (kg)	Default leakage rate (operating-ALR)	Default leakage rate (installation-AEF)		
			Method B	Method C	
Medium commercial stand-alone freezer (300-500 litres)	0.3	8%	n/a	Acceptable	Screening method only
Large commercial stand-alone freezer (>500 litres)	0.45	8%	n/a	Acceptable	Screening method only
Water coolers	0.04	3%	n/a	Recommended	Acceptable
Dehumidifiers	0.17	3%	n/a	Recommended	Acceptable
Small self-contained air conditioners (window mounted or through the-wall)	0.2 kg per kW cooling capacity	1%	0.50%	Acceptable	Screening method only
Non-ducted and ducted split commercial air conditioners (<20 kW)	0.25 kg per kW cooling capacity	3%	0.50%	Acceptable	Screening method only
Commercial air conditioning (>20kW)	Wide range	Wide range	Wide range	Unacceptable	Unacceptable
Cars/vans	0.7	10%	n/a	Recommended	Acceptable
Trucks	1.2	10%	n/a	Acceptable	Screening method only
Buses	2.5 (but up to 10)	10%	n/a	Acceptable	Screening method only
Refrigerated truck trailer units	10	25%	0.50%	Acceptable	Unacceptable
Self-powered or 'cabover' refrigerated trucks	6	25%	0.50%	Acceptable	Unacceptable
'Off-engine' or 'direct drive' refrigerated vans and trucks	2.5	25%	0.50%	Acceptable	Unacceptable

Refrigeration unit type	Default refrigerant charge (kg)	Default leakage rate (operating-ALR)	Default leakage rate (installation-AEF)	Default leakage rate	
				Method B	Method C
Three-phase refrigerated containers	5.5	25%	0.50%	Acceptable	Unacceptable
Single-phase refrigerated containers	3	25%	0.50%	Acceptable	Unacceptable
Centralised commercial refrigeration eg, supermarkets	Wide range	Wide range	Wide range	Unacceptable	Unacceptable
Industrial and commercial cool stores	Wide range	Wide range	Wide range	Unacceptable	Unacceptable

Note<sup>1</sup>: In the absence of consistent information for New Zealand, the default assumption for the assembly (installation) emissions rate is the rounded-off IPCC 2006 mid-range value. It is not applicable (relevant) for many pre-charged units.

Note<sup>2</sup>: Internal dimensions up to 100x50x30cm for 150 litres; 150x50x40cm for 300 litres; 200x50x50cm for 500 litres.

**Table B.2: Detailed 100-year GWPs for various refrigerant mixtures**

Refrigerant type (trade name)	Refrigerant type								Total GWP
	HFC-23	HFC-32	HFC-125	HFC-134a	HFC-143a	HFC-152a	PFC-218	Other	
GWP100 (IPCC Fifth Report, AR5)	12,400	677	3,170	1,300	4,800	138	8,900	0	
R-22								100%	1,760
R-23	100%								12,400
R-134a				100%					1,300
R403B							39%	61%	4,457
R404A			44%	4%	52%				3,943
R406A								100%	1,780
R407C		23%	25%	52%					1,624
R407F		30%	30%	40%					1,674
R408A			7%		46%			47%	3,257
R409A								100%	1,485

Refrigerant type (trade name)	HFC-23	HFC-32	HFC-125	HFC-134a	HFC-143a	HFC-152a	PFC-218	Other	Total GWP
R409B								100%	1,474
R410A		50%	50%						1,924
R413A				88%			9%	3%	1,945
R416A				59%				41%	975
R417A			46.6 %	50%				3.4 %	2,127
R422A			85.1 %	11.5 %				3.4 %	2,847
R436A								100%	1
R436B								100%	1
R502								100%	4,786
R507A			50%		50%				3,985

Note: values might differ from those reported in Table 4.2 due to rounding.

### B.3. B.3 Assumptions

The default factors in methods B and C for operating refrigerant equipment are derived from a report by CRL Energy Ltd to the Ministry for the Environment on the *Assessment of HFC Emission Factors for GHG Reporting Guidelines (2008)*. These are based on data for New Zealand refrigeration and air-conditioning equipment stock.

In the absence of consistent information for New Zealand, the default assumption for the assembly emissions rate is the rounded-off IPCC 2006 mid-range value. This will not apply to many 'pre-charged' units as these are sealed to prevent leakage.

For simplicity, the default operating emission factor does not take account of the variability associated with equipment age.

## C. Appendix — Landfills with and without landfill gas recovery

Table C.1 lists the active landfills in New Zealand with landfill gas recovery (LFGR) in 2022. Users should use emission factors without gas capture if the landfill is not listed in the table.

**Table C.1: Active landfills with landfill gas recovery**

Name	Operator
AB Lime Ltd (Winton)	AB Lime Ltd
Bonny Glenn (Rangitikei District)	Midwest Disposal Ltd
Green Island Landfill	Dunedin City Council
Hampton Downs Landfill	EnviroWaste Services Ltd
Kate Valley (Amberley)	Canterbury Waste Services Ltd
Marlborough Regional Council (Bluegums)	Marlborough District Council
Omarunui Landfill	Hastings District Council
Redruth Landfill	Timaru District Council
Redvale Landfill	Transpacific waste management
Silverstream Landfill	Hutt City Council
Southern Landfill	Wellington City Council
Spicer Landfill	Porirua City Council
Tirohia Landfill (Paeroa)	HG Leach & Co. Ltd
Victoria Flats Landfill (Queenstown/ Cromwell)	Scope Resources Ltd
Whangarei Resort	Northland Regional Landfill Ltd. Partnership
Whitford Landfill – Waste Disposal Services	Transpacific waste management
York Valley Landfill	Nelson City Council

Source: Ministry for the Environment

We invite users to contribute to the improvement of table C1 by indicating if it should include any other known active landfill with gas recovery. Please email [Emissions-guide@mfe.govt.nz](mailto:Emissions-guide@mfe.govt.nz)

## D. Appendix — Spend-based emission factors

In 2023, Auckland Council has published emission factors using a spend-based emissions accounting approach. Using data from Stats NZ Tatauranga Aotearoa, emission intensities are calculated for 199 commodity types. These can be linked to an entity's expenditure on goods and services. It is assumed that goods and services purchased from outside of New Zealand generate the same quantities of emissions per dollar of expenditure as equivalent goods and services produced in New Zealand.

In terms of consumption, spend-based emissions accounting focuses on calculating the emissions 'embodied' in the goods and services people consume. In other words, all emissions released directly and indirectly throughout the industrial supply chain that generated each good or service.

Entities completing a GHG inventory may find this dataset useful for estimating Scope 3 emissions, which may be difficult to do in the absence of activity or supplier specific data. The generated emission intensities and datasets have potential applications beyond GHG inventory management, such as assessing entities' consumption patterns to identify potential opportunities to reduce GHG emissions, or analysing the impact of different development trajectories.

Note these emission factors will only give you an estimation of your supply chain emissions. We recommend using these factors only if better quality activity data isn't available. These emissions factors do not relate to specific products and to ensure an accurate measure of emissions and reflect choices between different products supplier specific data is required.

Access the Auckland Council *Consumption Emissions Modelling* report here: <https://www.knowledgeauckland.org.nz/publications/consumption-emissions-modelling/>.

## E. Appendix — Glossary

AR4	The IPCC Fourth Assessment Report
AR5	The IPCC Fifth Assessment Report
Activity data	Data on the magnitude of human activity resulting in emissions or removals taking place during a given period
ANZSIC	Australian and New Zealand Standard Industrial Classification
Base year	The first year in the reporting series
BEV	Battery electric vehicle
BfCC	Building for Climate Change
Biodiesel	A type of biofuel similar to diesel that is made from natural elements such as plants, vegetables and reusable materials
Bioethanol	A type of biofuel similar to ethanol that is made from natural elements such as plants, vegetables and reusable materials
Biofuels	Any fuel derived from biomass
Biologically sequestered carbon	The removal of carbon dioxide from the atmosphere and captured by plants and micro-organisms
BOD	Biological oxygen demand, the amount of dissolved oxygen needed by micro-organisms to break down biological organic matter in water
BRANZ	Building Research Association of New Zealand
CAA	Civil Aviation Authority
Carbon sink	A natural or artificial process that removes carbon from the atmosphere
CEU	Car equivalent unit
CFCs	Chlorofluorocarbons
CH <sub>4</sub>	Methane
CNGP	Carbon Neutral Government Programme
CO <sub>2</sub>	Carbon dioxide
CO <sub>2</sub> -e	Carbon dioxide equivalent
COD	Chemical oxygen demand
CHSB	The Cornell Hotel Sustainability Benchmarking Index Tool
<i>De minimis</i>	A permissible quantity of emissions that a company can leave out of its inventory, based on an insignificant GHG contribution, usually <1 per cent of an entity's total inventory for an individual emissions source. The threshold is defined by the entity
Deforestation	The clearing of forest land that is then converted to a non-forest land use
DESNZ	Department for Energy Security and Net Zero - a UK government department
dwt	Deadweight tonnes
EECA	Energy Efficiency and Conservation Authority
Emission factor	A coefficient that quantifies the emissions or removals of a gas per unit activity
Enteric fermentation	The process by which ruminant animals digest feed and produce methane
FIGS	Freight Information Gathering System
FOCA	Federal Office of Civil Aviation - a Swiss government department
Forest land	Land containing tree species that will reach a height of at least 5 metres, with a canopy cover of at least 30% and be of at least 1 hectare in size
Fugitive emissions	

	The emission of gases from pressurised equipment due to leaks or unintended releases of gases, usually from industrial activities
GHG	Greenhouse gas
GHG inventory	A quantification of an entity's greenhouse gas sources, sinks, emissions and removals
GHG Protocol	The Greenhouse Gas Protocol Accounting and Reporting Standard provides guidance for entities preparing a GHG inventory
GHG report	A standalone report to communicate an entity's GHG-related information to intended users
GJ	Gigajoule (unit of measure, one billion joules)
Grazing off	Cattle feeding on paddock not owned by their farmer
GWP	Global warming potential, a factor describing the radiative forcing impact of one mass-based unit of a given GHG relative to an equivalent unit of carbon dioxide over a given period (typically 100 years)
HBFCs	Hydrobromofluorocarbons
HCFCs	Hydrochlorofluorocarbons
HFC	Hydrofluorocarbon, an alternative refrigerant gas that minimises damage to the ozone hole
HGV	Heavy goods vehicles
IATA	International Air Transport Association
ICAO	International Civil Aviation Organisation
Inert	Chemically inactive (eg, plastic waste)
IPCC	Intergovernmental Panel on Climate Change
ISO 14064-1:2018	International Organization for Standardisation standard on greenhouse gases – Part 1: Specification with guidance at the organisation level for quantification and reporting greenhouse gas emissions and removals
kt	Kilotonne (unit of measure, one thousand tonnes)
LCDB	Land Cover Database
LFGR	Landfill gas recovery
LM	Lanemetre
LPG	Liquefied petroleum gas
LUCAS	Land Use and Carbon Analysis System
LULUCF	Land use, land-use change and forestry
Materiality	To be considered as having significance to an entity
Mature indigenous forest	A forest comprising predominantly native species, where there are no clearly visible indications of human activities and the ecological processes are not significantly disturbed. The forest will contain large trees with multi-layered canopies and be considered a climax community
MBIE	Ministry of Business, Innovation and Employment
MCF	Methane correction factor
MfE	Ministry for the Environment
MoT	Te Manatū Waka Ministry of Transport
MPI	Ministry of Primary Industries
Municipal	landfill Landfill that accepts household waste as well as other wastes
NDC	Nationally determined contributions under the Paris Agreement
NF3	Nitrogen trifluoride
N2O	Nitrous oxide

NTK	Net tonne km
NZ ETS	New Zealand Emissions Trading Scheme
NZCS	New Zealand Climate Standards
NZTA	Waka Kotahi New Zealand Transport Agency
ODS	Ozone depleting substances
Organisational boundary	The boundary of the entity/organisation as it applies to measurement of GHG emissions. This typically aligns with legal and/or organisational structure; a financial boundary must be drawn within this too
OverseerFM	A New Zealand software platform that enables farmers and growers to estimate and improve nutrient use on farms
PFC	Perfluorocarbon
PHEV	Plug-in hybrid electric vehicle
pkm	Passenger-kilometre (unit of measure for transport)
Radiative forcing	The difference between solar energy absorbed by the Earth and that radiated back to space. Human activity has impacts which alter radiative forcing
Refrigerants	A substance or mixture used in a heat pump and refrigeration cycle
Removals	Withdrawal of a GHG from the atmosphere by GHG sinks
Reporting boundary	The emission sources included within an entity's/organisation's operations, including direct and indirect emission sources. It includes choosing which indirect emission sources to report
Reticulated gas	A piped gas system to deliver a gas such as LPG or natural gas to a consumer
RUC	Road user charge
Scope	Emission sources are categorised by Scope to manage risks and impacts of double counting. There are three scopes in greenhouse gas reporting: Scope 1 (direct emissions), Scope 2 (energy indirect emissions) and Scope 3 (other indirect emissions)
SF <sub>6</sub>	Sulphur hexafluoride
Stationary combustion fuel	Fuel used in an unmoving engine, eg, a power plant or boiler
TEU	Twenty-foot equivalent unit
tkm	Tonne-kilometre (unit of measure for freight)
UNFCCC	United Nations Framework Convention on Climate Change
Unique emission factor	A value given to an activity based on how emissions intensive it is. Experienced professionals must verify a unique emission factor. See Climate Change (Unique Emission Factors) Regulations 2009 for further information
Uplift factor	Applied to account for the combined 'real-world' effects on fuel consumption (such as non-direct flight paths)

## F. Appendix — Files

Here are the available files for download:

### F.0.1. Published files for 2025

Published date	Version	File type	Description	Download
2026-02-24	2025.3	CSV	Current emissions factors in long CSV format.	EmissionFactors_2025_v3_long.csv
2026-02-24	2025.3	CSV	Current emissions factors in wide CSV format.	EmissionFactors_2025_v3_wide.csv
2026-02-24	2025.3	XLSX	Current emissions factors workbook (README + data tabs).	EmissionFactors_2025_v3.xlsx
2026-02-24	2025.3	XLSX	Current interactive workbook with activity inputs and calculated totals.	EmissionFactors_2025_v3_interactive_workbook.xlsx
2026-02-24	2025.3	PDF	Current Measuring Emissions Catalogue PDF.	Measuring-Emissions-Catalogue-2025-v3.pdf

### F.0.2. Historical downloads

Published date	Version	File type	Description	Download
<b>2025</b>				
2025-02-01	2025.2	XLSX	Historical flat-file emissions factors workbook (pre-classification migration).	Flat_EmissionFactors_2025_2.xlsx
<b>2024</b>				
2024-07-29	2024.1	PDF	Detailed Measuring Emissions guidance PDF.	Measuring-emissions_Detailed-guide_2024_ME1829.pdf
2024-07-29	2024.1	XLSX	Historical flat-file emissions factors workbook.	Measuring_Emissions_Flat_EmissionFactors_2024.xlsx
<b>2023</b>				
2023-08-01	2023.1	PDF	Detailed Measuring Emissions guidance PDF.	Measuring-Emissions-Guidance_DetailedGuide_2023_ME1764.pdf
2023-08-01	2023.1	XLSX	Historical flat-file emissions factors workbook.	Measuring-Emissions-Guidance_EmissionFactors_FlatFile-Aug2023.xlsx
<b>2022</b>				
2022-08-01	2022.1	PDF		

Published date	Version	File type	Description	Download
			Detailed Measuring Emissions guidance PDF.	Detailed-guide-PDF-Measuring-emissions-guidance-August-2022.pdf
2022-08-01	2022.1	XLSX	Historical flat-file emissions factors workbook.	Emission-factors-flat-file-Measuring-emissions-guidance-August-2022.xlsx

1. [https://unfccc.int/kyoto\\_protocol](https://unfccc.int/kyoto_protocol)
2. <https://www.unep.org/ozonaction/who-we-are/about-montreal-protocol>
3. Published by the International Organization for Standardization. This standard is closely based on the GHG Protocol.
4. Developed jointly by the World Resources Institute (WRI) and the World Business Council for Sustainable Development (WBCSD).
5. Environmental Product Declaration: [epd-australasia.com/](http://epd-australasia.com/).
6. Environmental Product Declaration: [epd-australasia.com/](http://epd-australasia.com/).
7. Environmental Product Declaration: [epd-australasia.com/](http://epd-australasia.com/).
8. Water New Zealand, *Carbon Accounting Guidelines for Wastewater Treatment: CH<sub>4</sub> and N<sub>2</sub>O*
9. Freight Information Gathering System, overseas ships: [www.transport.govt.nz/statistics-and-insights/freight-and-logistics/](http://www.transport.govt.nz/statistics-and-insights/freight-and-logistics/).
10. The average fuel efficiency was based on Auckland Transport's GHG inventory of 2023/24.
11. BRANZ CO2NSTRUCT: [www.branz.co.nz/co2nstruct](http://www.branz.co.nz/co2nstruct).
12. Environmental Product Declaration: [epd-australasia.com/](http://epd-australasia.com/).
13. Waka Kotahi New Zealand Transport Agency: [www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat](http://www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat).
14. [www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5\\_Volume5/V5\\_3\\_Ch3\\_SWDS.pdf](http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5_Volume5/V5_3_Ch3_SWDS.pdf).
15. Ministry for the Environment's wastewater treatment plants database.
16. GHG Protocol Scope 2 Guidance: [https://ghgprotocol.org/sites/default/files/standards/Scope%20%20Guidance\\_Final\\_Sept26.pdf](https://ghgprotocol.org/sites/default/files/standards/Scope%20%20Guidance_Final_Sept26.pdf)
17. Environmental Product Declaration: [epd-australasia.com/](http://epd-australasia.com/).
18. Waka Kotahi New Zealand Transport Agency: [www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat](http://www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat).
19. [www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5\\_Volume5/V5\\_3\\_Ch3\\_SWDS.pdf](http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5_Volume5/V5_3_Ch3_SWDS.pdf).
20. Water New Zealand, *Carbon Accounting Guidelines for Wastewater Treatment: CH<sub>4</sub> and N<sub>2</sub>O*
21. Freight Information Gathering System, overseas ships: [www.transport.govt.nz/statistics-and-insights/freight-and-logistics/](http://www.transport.govt.nz/statistics-and-insights/freight-and-logistics/).
22. The average fuel efficiency was based on Auckland Transport's GHG inventory of 2023/24.
23. Kerosene ([ils.co.nz](http://ils.co.nz)).
24. <https://archive.ipcc.ch/ipccreports/sres/aviation/121.htm#8223>
25. <https://www.aviation.govt.nz/aircraft/aircraft-registration/aircraft-register-search/>.
26. <https://ecommons.cornell.edu/items/85eddae3-2b5b-41fb-88ad-75a0b53f8424>.
27. <https://greenview.sg/resources/chsb-index/>.
28. BRANZ CO2NSTRUCT: [www.branz.co.nz/co2nstruct](http://www.branz.co.nz/co2nstruct).
29. Environmental Product Declaration: [epd-australasia.com/](http://epd-australasia.com/).
30. Waka Kotahi New Zealand Transport Agency: [www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat](http://www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat).
31. [www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5\\_Volume5/V5\\_3\\_Ch3\\_SWDS.pdf](http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5_Volume5/V5_3_Ch3_SWDS.pdf).
32. Ministry for the Environment's wastewater treatment plants database.

33. Water New Zealand, *Carbon Accounting Guidelines for Wastewater Treatment: CH<sub>4</sub> and N<sub>2</sub>O*↔
34. Freight Information Gathering System, overseas ships: [www.transport.govt.nz/statistics-and-insights/freight-and-logistics/](http://www.transport.govt.nz/statistics-and-insights/freight-and-logistics/).↔
35. Waka Kotahi New Zealand Transport Agency: [www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat](http://www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat).↔
36. [www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5\\_Volume5/V5\\_3\\_Ch3\\_SWDS.pdf](http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5_Volume5/V5_3_Ch3_SWDS.pdf).↔
37. Ministry for the Environment's wastewater treatment plants database.↔
38. Water New Zealand, *Carbon Accounting Guidelines for Wastewater Treatment: CH<sub>4</sub> and N<sub>2</sub>O*↔
39. Cardno (2015) Greenhouse Gas Emissions from Industrial Wastewater Treatment – Inventory Basis Review.↔
40. Cardno (2015) Greenhouse Gas Emissions from Industrial Wastewater Treatment – Inventory Basis Review.↔
41. BRANZ CO2NSTRUCT: [www.branz.co.nz/co2nstruct](http://www.branz.co.nz/co2nstruct).↔
42. Environmental Product Declaration: [epd-australasia.com/](http://epd-australasia.com/).↔
43. Waka Kotahi New Zealand Transport Agency: [www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat](http://www.nzta.govt.nz/roads-and-rail/highways-information-portal/technical-disciplines/environment-and-sustainability-in-our-operations/environmental-technical-areas/climate-change/climate-change-mitigation/project-emissions-estimation-tool-peat).↔
44. [www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5\\_Volume5/V5\\_3\\_Ch3\\_SWDS.pdf](http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5_Volume5/V5_3_Ch3_SWDS.pdf).↔
45. Age is defined as the number of years since afforestation.↔
46. LUCAS Land Use Map.↔
47. New Zealand Land Cover Database.↔
48. Wakelin SJ, Paul THS, West T, Dowling, LJ. Unpublished. Reporting New Zealand's Nationally Determined Contribution under the Paris Agreement using Averaging Accounting for Post-1989 forests. Contract report prepared for the Ministry for the Environment by New Zealand Forest Research Institute Ltd (trading as Scion) in 2021.↔
49. See volume 4, chapter 10 of 2006 IPCC Guidelines for National Greenhouse Gas Inventories.↔